GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6 DFS MS 2016 1467

Dated: 03/10/2016

FIRE SAFETY CERTIFICATE

Certified that the Shree Laxmi Narayan Sewa Ashram Trust (Regd.), Mandawali Fazalpur (Near Balco Society Mkt.) Delhi-92 Comprised of Basement, ground plus two upper floors owned/occupied by Shree Laxmi Narayan Sewa Ashram Trust have complied with the fire prevention and fire safety requirements in accordance with rules 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Fire Service on 27/08/16 in the presence of Mr. R.S. Negi (Manager) of the Community Hall and that the building is fit for occupancy class "D'Assembly Building with effect from.....for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010, printed overleaf.

Issued on 23/10/16...at New Delhi by

(Vipin Kental)
Chief Fire Officer

To,

Manager,
Shree Laxmi Narayan Sewa Ashram Trust (Regd.),
Mandawali Fazalpur (Near Balco Society Mkt.) Delhi..
Copy to:-

 The Deputy Health Officer (EDMC), SHD (N)-Zone, Health Department, Delhi-110032

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form `J` [sub rule (1) of rule (37)] along with a copy of this Certificate, six months prior to its expiry.

THE PUBLISHED AND MICE Name & address of the building : Shree Laxmi Narayan Sewa Ashram Trust (Regd.) Mandawali Fazalpur (Near Balco Society Mkt.) Delhi. : B+G+2 Upper floors 2. Building is comprised of : Assembly (Banquet Hall) 3. Type of Occupancy : New Case 4. Type of Case 5. Details of Previous NOC : Nil : F6/DFS/MS/BP/2004/72 Dated-12/01/04 6. Fire Safety direction letter No : 27/08/16 7. Date of Inspection 8. Name of the Inspecting Officers: : R.K. Yadav (ADO) 9. Name of the designation of Officer : R.S.Negi (Manager) from the building side : 2004 10. Year of Construction : dated 01/08/16 11. Applicant's letter No Minimum Standards on fire prevention Provided at Remarks Requirement MR/NMR and fire safety U/R33 /NBC Site Access to building 1 MR Road width 6 m 18 m Gate width 4.5 m 4.5 m MR Width of internal road N.A. N.A. N.A. Number, Width, Type and Arrangement of Exits 2 a. Number of Staircases Upper Floor 2 no. 2 no. MR Basement MR 2 no. 2 no. b. Width of Staircases Upper Floor 1.5 m 1.5 m each MR Basement 1.5 m 1.5 m each MR c. Protection of exits Fire check door Required provided MR Pressurization Required MR provided e. No. of continuous staircases to terrace MR 2 no. 2 no. g. Width of Corridor N.A. N.A. N.A. h. No. of door 2 no. 2 no. MR i. Door Size 2 m, 1.10m MR 2 m & 1.60 m 3 Compartmentation. provided MR Fire check door Required Sealing of electrical shafts Required Provided MR Fire rating of shaft door N.A. N.A. N.A. Water curtain N.A. N.A. N.A. Fire Dampers N.A. N.A. N.A. 4 Smoke Management System. provided MR Ventilated Basement Ventilated Ventilated MR Upper floor 5 Fire Extinguisher provided MR Total numbers 10 no.

CO₂ & ABC

ISI marked

types

IS marking

MR

MR

provided

provided

MIZ

6	First-aid-Hose Reels.					
	Total numbers of each floor	1 no.	Provided	MR		
	Length of hose reel hose	30 m	Provided	MR		
	Nozzle diameter	5 mm	Provided	MR		
7	Automatic fire detection and alarming sys					
	Type of detectors	Required	Provided	MR		
	Location of main panel	Required	Provided	MR		
	Location of repeater panel	Required	Provided	MR		
	Alternate source of power	Required	Provided	MR		
	Hooters's location	Required	Provided	MR		
8	MOEFA	Required	provided	MR		
9	Public address System.	N.A.	N.A.	N.A.		
10	Automatic Sprinkler System.			-		
	basement	Required	Provided	MR		
	upper floor	Required	provided	MR		
	sprinkler above false ceiling	Required	provided	MR		
11	Internal Hydrants		and the same of th			
	size of riser/down-comer	100 mm	Provided	MR		
	Total no. of hydrants each floor	1 no.	Provided	MR		
	Hose Box per floor	1 no.	Provided	MR		
12	Yard Hydrants.	and an armed armed armed armed an armed				
	Total number of hydrants	Required	provided	MR		
	Hose Box	Required	provided	MR		
13	Pumping Arrangements.					
	Ground Level	T		****		
	➢ Discharge of main Pump	900 Lpm	Provided	MR		
	> Head of Main Pump	40 M	Provided	MR		
	Number of main pumps	1 No.	Provided	MR		
	> Jockey pump out put	180 Lpm	provided	MR		
	> Jockey pump head	40 M	provided	MR		
	> Standby pump out put	900 Lpm	provided	MR		
	> Standby pump Head	40 M	provided	MR		
	> Auto Starting /Manual stopping	Required	Manual	MR		
	> Pump House Access	N.A.	N.A.	N.A.		
	Terrace Level					
	Discharge of pump	900 LPM	Provided	MR		
	➢ Head of the Pump	40 m	Provided	MR		
	> Power supply	Required	Provided	MR		
	> Auto Starting of pump	Required	provided	MR		
14	Captive Water Storage for Fire Fighting.					
	Underground tank capacity	50,000 Liters	Provided	MR		
	Draw-off connection	Required	Provided	MR		
	Fire service inlet	Required	provided	MR		
	Access to tank	Required	provided	MR		
	Overhead Tank capacity	10,000 Liters	Provided	MR		

16	Provision of Lifts.	and the second	and the state of t			
	Pressurization of Lift Shaft Pressurization of Lift lobby Communication in lift car Firemen's grounding switch Lift Signage	Required	Provided	MR		
		Required	provided	MR		
		Required	Provided	MR		
		Required	provided	MR		
		Required	Provided	MR		
17	Standby power supply	Required	Provided	MR-		
18	Refuge Area.					
	Total area Location	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
19	Fire Control Room					
	Detector system panel Flow switch panel PA system panel Batter backup Building Floor Plans	N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
		N.A.	N.A.	N.A.		
20	Special Fire Protection systems for protection of special Risks, if any:	N.A.	N.A.	N.A.		

The fire extinguishers provided in the building were tested/ checked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rule 2010.

Signature of the Inspecting Officer Name- R.K. Yadav Designation- ADO (LN)

Dico(xps) 019/a

46/ cl. NO2 15/9/16/4/16.

Su, FT heller is put up for signature please.