## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2016/1475

Dated : 4//6//6

## FIRE SAFETY CERTIFICATE

Issued -4/14/16 at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 2257/Joint C.P./Lic. (H) dated 26/08/16.
- 2. The Manager, Odeon Continental Guest House, 7964, A.K. Road, Gali No. 6, Pahar Ganj, New Delhi.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

|        | INSPE  | ECTION REPOR  | RT                            |                   |  |  |
|--------|--|---|-------------------------------|-------------------|--|--|
| 1.     | Name & address of the building                               | Odeon Cont  | inental Guest Hous            | e located at      |  |  |
|        |  | 7964, A.K. I  | Road, Gali No. 6, P           | ahar Ganj,        |  |  |
|        |  | New Delhi   |                               |                   |  |  |
| 3.     | Type of Occupancy:-  |   | Residential, Sub Division-A-1 |                   |  |  |
|        |  | Gr. + 05 Upper floors (total 18 Guest rooms) Ground floor (Reception+ 02 guest rooms+01office), |                               |                   |  |  |
|        |  | 1 <sup>st</sup> floor to 4 <sup>th</sup> f  | loor (04 guest rooms a        | t each floor) and |  |  |
|        |  | ed with brick wall  |                               |                   |  |  |
| 3.     | Type of case:- Renewal                                       |   |                               |                   |  |  |
| 4.     | Details of previous FSC:- No. F6/DFS/MS/GH/2013/NDZ/1020 dat |   |                               |                   |  |  |
|        |  | 03/10/13.   |                               |                   |  |  |
|        | Fire safety directives No                                    | N/A   |                               |                   |  |  |
|        | Date of inspection:-   | 26/09/16 (ADQ/GG)   |                               |                   |  |  |
| 7.     | Name of the inspecting officer:                              | - Sh. Manoj k   | Kumar Sharma (AI              | )O/CC)            |  |  |
|        | Name & designation of officer                                | Cl. Chand(  | Managan)                      |                   |  |  |
|        | he building side:-   | Sh. Chand()   | Manager)                      |                   |  |  |
|        | Year of construction:-                                       | 2007<br>2257/Joint C.P./Lic. (H) dated 26/08/16.  |                               |                   |  |  |
| 10.    | Applicant's letter No:-                                      | 223 1130IIIt C.   | 1 ./ Lie. (11) dated 2        | Old Case          |  |  |
| S.No.  | Minimum Standards on fire                                    | Requirement/  | Provided at site              | Remarks           |  |  |
| 5.110. | Prevention and fire safety                                   | Existing fire   |                               | MR/NMR            |  |  |
|        | U/R 33   | safety  |                               |                   |  |  |
|        | O/R 33   | arrangements  |                               |                   |  |  |
| 1.     | Access to Building   |   |                               |                   |  |  |
|        | 1) Road width  | N/A   | 02 mtr.                       | N/A               |  |  |
|        | 2) Gate width  | N/A   | N/A                           | N/A               |  |  |
|        | 3)Width of internal road                                     | N/A   | N/A                           | N/A               |  |  |
| 2.     | Number, Width Type & Arra                                    |   | cits                          |                   |  |  |
|        | A. Number of staircases                                      | 8   |                               |                   |  |  |
|        | 1. Upper floors  | 01 Nos.   | 01 Nos.                       | MR                |  |  |
|        | 2. Basements   | N/A   | N/A                           | N/A               |  |  |
|        | B. Width of staircase  |   |                               |                   |  |  |
|        | 1. Upper floors  | 0.80 mtr.   | 1.22 to 1.27                  | MR                |  |  |
|        |  |   | Mtr.                          |                   |  |  |
|        | 2. Basements   | N/A   | N/A                           | N/A               |  |  |
|        | C. Protection of exits                                       |   |                               |                   |  |  |
|        | 1. Fire check door   | N/A   | N/A                           | N/A               |  |  |
|        | 2. Pressurization  | N/A   | N/A                           | N/A               |  |  |
|        | D. No. of continuous   | 01  | 01                            | MR                |  |  |
|        | staircase to terrace   |   | 27/4                          | 27/4              |  |  |
|        | E. Width of corridor   | N/A   | N/A                           | N/A               |  |  |
|        | F. Door size   | 01 mtr.   | 01 mtr.                       | MR                |  |  |
| 3.     | Compartmentation   | 27/4  | DT/A                          | NI/A              |  |  |
|        | 1) Fire check door   | N/A   | N/A                           | N/A               |  |  |
|        | 2) Sealing of electrical shafts                              | N/A   | N/A                           | N/A               |  |  |
|        | 3) Fire rating of shaft door                                 | N/A   | N/A                           | N/A               |  |  |
|        | 4) Water curtain   | N/A   | N/A                           | N/A<br>N/A        |  |  |
|        | 5) Fire Dampers  | N/A   | N/A                           | IN/A              |  |  |
| 4.     | Smoke Management System                                      | 20 A CDII   | NI/A                          | N/A               |  |  |
|        | 1) Basements   | 30 ACPH   | N/A                           | MR                |  |  |
|        | 2) Upper floors  | 12 a/c per  | Natural                       | IVII              |  |  |
|        |  | hour  |                               |                   |  |  |

Man

| 5.       | Fire Extinguishers                             |            |            |         |  |  |
|----------|--|------------|------------|---------|--|--|
|          | 1) Total numbers                               | 12         | 12         | MR      |  |  |
|          | 2) Types                                       | ABC & CO2  | ABC & CO2  | MR      |  |  |
|          | 3) ISI marking                                 | Required   | Provided   | MR      |  |  |
| 6.       | First-Aid Hose Reel                            |            |            |         |  |  |
|          | 1) Total number of eachfloor                   | 01         | 01         | MR      |  |  |
|          | 2) Length of hose reel hose                    | 30 mtr.    | 30 mtr.    | MR      |  |  |
|          | 3) Nozzle diameter                             | 05 mm      | 05 mm      | MR      |  |  |
| 7.       | Automatic Fire Detection & Alarming System     |            |            |         |  |  |
| 7.       | 1) Type of detectors                           | N/A        | N/A        | N/A     |  |  |
|          | 2) Location of main panel                      | N/A        | N/A        | N/A     |  |  |
|          | 3) Location of repeater panel                  | N/A        | N/A        | N/A     |  |  |
|          | 4) Alternate source of power                   | N/A        | N/A        | N/A     |  |  |
|          | 5) Hooter's Location                           | N/A        | N/A        | N/A     |  |  |
| 0        | MOEFA  | Required   | Provided   | MR      |  |  |
| 8.<br>9. | Public Address System                          | Required   | Provided   | MR      |  |  |
|          | Automatic Sprinkler System                     | Required   | TTOTAGG    |         |  |  |
| 10.      | 1) Basement                                    | N/A        | N/A        | N/A     |  |  |
|          | 2) Upper floors                                | N/A        | N/A        | N/A     |  |  |
|          | 3) Sprinkler above false                       | N/A        | N/A        | N/A     |  |  |
|          |  | 14/71      | 11/11      |         |  |  |
| 11       | ceiling  |            |            |         |  |  |
| 11.      | Internal Hydrants  1) Size of riser/down-comer | N/A        | N/A        | N/A     |  |  |
|          | 2) Number of hydrants per                      | N/A        | N/A        | N/A     |  |  |
|          | floor  | IVA        | 14/11      |         |  |  |
|          |  | N/A        | N/A        | N/A     |  |  |
| 10       | 3) Hose box                                    | INA        | 14/71      | 1 1/1 2 |  |  |
| 12.      | Yard Hydrants                                  | N/A        | N/A        | N/A     |  |  |
|          | 1) Total number of hydrants                    | N/A        | N/A        | N/A     |  |  |
|          | 2) Hose box                                    | INA        | 14/11      | 1 11 1  |  |  |
| 13.      | Pumping Arrangement                            | NI/A       | N/A        | N/A     |  |  |
|          | 1) Ground level                                | N/A        | N/A        | N/A     |  |  |
|          | a) Discharge of main                           | N/A        | IN/A       | IVIA    |  |  |
|          | pump   | N/A        | N/A        | N/A     |  |  |
|          | b) Head of main pump                           |            | N/A        | N/A     |  |  |
|          | c) Number of main pump                         | N/A<br>N/A | N/A        | N/A     |  |  |
|          | d) Jockey pump out put                         |            | N/A        | N/A     |  |  |
|          | e) Jockey pump head                            | N/A        | N/A        | N/A     |  |  |
|          | f) Stand by pump output                        | N/A        | N/A<br>N/A | N/A     |  |  |
|          | g) Stand by pump head                          | N/A        | N/A<br>N/A | N/A     |  |  |
|          | h) Auto starting/Manual                        | N/A        | N/A        | IN/A    |  |  |
|          | stopping                                       |            |            |         |  |  |
|          | 2) Terrace level                               | 450 I D) ( | 450 I DM   | MR      |  |  |
|          | a) Discharge of pump                           | 450 LPM    | 450 LPM    | MR      |  |  |
|          | b) Head of pump                                | 30 mtr.    | 30 mtr.    |         |  |  |
|          | c) Power supply                                | Required   | Provided   | MR      |  |  |
|          | d) Auto starting of pump                       | Required   | Provided   | MR      |  |  |
| 14.      | Captive Water Storage for Fire Fighting        |            |            |         |  |  |
|          | 1) Under ground tank                           | N/A        | N/A        | N/A     |  |  |
|          | capacity                                       | 1          | 27/4       | NI/A    |  |  |
|          | a) Draw-off connection                         | N/A        | N/A        | N/A     |  |  |

|     | b) Fire service inlet  | N/A        | N/A        | N/A |
|-----|--|------------|------------|-----|
|     | c) Access to tank  | N/A        | N/A        | N/A |
|     | d) Over head tank capacity   | 2,500 ltr. | 2,500 ltr. | MR  |
| 15. | Exit Signage.  | Required   | Provided   | MR  |
| 16. | Provision of Lifts.  |            |            |     |
|     | a) Pressurization of lift shaft  | N/A        | N/A        | N/A |
|     | b) Pressurization of lift lobby  | N/A        | N/A        | N/A |
|     | c) Communication in lift car   | N/A        | N/A        | N/A |
|     | d) Fireman's switch  | N/A        | N/A        | N/A |
|     | e) Lift signage  | N/A        | N/A        | N/A |
| 17. | Stand by Power Supply  | Required   | Provided   | MR  |
| 18. | Refuge Area  | N/A        | N/A        | N/A |
|     | Total area location  | N/A        | N/A        | N/A |
| 19. | Fire Control Room  | N/A        | N/A        | N/A |
|     | a) Detector system panel   | N/A        | N/A        | N/A |
|     | b) Flow switch panel   | N/A        | N/A        | N/A |
|     | c) PA system panel   | N/A        | N/A        | N/A |
|     | d) Battery backup  | N/A        | N/A        | N/A |
|     | e) Building floor plan   | N/A        | N/A        | N/A |
| 20. | Special Fire Protection System for Protection of special Risk, if any: 01 CO2 & 01 ABC fire extinguisher provided near electric panel. |            |            | MR  |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2013/NDZ/1020 dated 03/10/13 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

DO(CD)

Wyland 27/9/16

DychopyDZ)