GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DLEHI - 110 001

No. F.6/DFS/MS/Hotel/SZ/2016/ 1483

Dated: 05/10/16

FIRE SAFETY CERTIFICATE

Certified that the Vikram Hotel at 1 & 2 Ring Road, Lajpat Bhawan, New Delhi-110024 comprises of Basement, Ground floor, Mezzanine floor and 4 Upper floors was granted FSC by this department vide letter No. F6/DFS/MS/Hotel/2013/605 dated 23/07/2013. The premises was re-inspected by the officer concerned of this department on 24/09/2016 in the presence of Mr. Rajender Saini (Chief Engineer) & Mr. Shahjimon Mohan (Chief Security Officer) and found that the said Hotel building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Group A Residential (Hotel Building)" with effect from -05-12016 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010.

Issued on at New Delhi by.

(Vipin Kental) **Chief Fire Officer** Tel: 011-23412225

Copy to:-

- 1. The Joint Commissioner of Police (Lic.), First Floor, P.S. Defence Colony, New Delhi-110049
- 2. The General Manager, Vikram Hotel at 1 & 2 Ring Road, Lajpat Bhawan, New Delhi-110024

Conditions for the validity of fire safety certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 5. This fire safety certificate may not in any way be treated as regularization of unauthorized construction, if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

Vikram Hotel at 1 & 2 Ring Road, Lajpat Bhawan, New Delhi-110024

INSPECTION REPORT

1. Name & address of the building: Vikram Hotel at 1 & 2 Ring Road, Lajpat Bhawan, New Delhi-110024

:Group A Hotel Building 2. Type of Occupancy

3. Type of Case : Renewal [Basement, Ground, Mezzanine + 4 upper floors]

4. Details of Previous NOC: F6/DFS/MS/Hotel/2013/605 dated 23/07/2013

5. Fire Safety directives letter No: NA 6. Date of inspection : 24/09/2016 7. Name of Inspecting Officers: A.K. Malik

8. Name and designation of officers

From the building side

: Mr. Rajender Saini (Chief Engineer)

9. Year of Construction : 1968 10. Applicant's letter No. : 2266/Joint.C.P./Lic(H)/New Delhi dated 29/08/2016									
S.		num Standards on fire	Old NOC	Provided at site	Remarks				
No.	2000	ntion and fire safety U/R 33	(17/03/92)Requirement	Trovided at site	MR/NMR				
1.		Access to building							
	•	Road width	Required	10m	MR				
	•	Gate width	2 x 6m approx.	5m	MR(old				
	•	Width of internal road	Required	7m (one side)	case)				
			*		MR(old				
			8		case)				
2.		Number, Width, Type & Arrangement of Exits							
		nber of staircases	D 1	O T 2) (D				
	•	Upper Floors	Required	2 No's	MR				
_	1. 337	Basements	Required	2 No's	MR				
	b. Width of staircases								
		Upper Floor	Required Required	1.5m & 0.95m 1.25m & 0.95m	MR				
	C Dro	Basement tection of exits	Required	1.2311 & 0.9311	MR				
	C. F10	Fire check door	Required	Provided	MR				
		Pressurization	NA	NA	NA				
	d. No	o. of continuous staircases to	Required	2 No's	MR				
	terr		Required	1.7m	MR				
	2 1000	dth of Corridor	Required	1m (final exit)	MR				
		oor Size	Required	Till (lillar exit)	IVIIC				
3.	Comp	artmentation	***						
	•	Fire check door	Required	Provided	MR				
	•	Sealing of electrical shafts	Required	Provided	MR				
	•	Fire Rating of shaft door	Required	Provided	MR				
	•	Water Curtain	NA	NA	NA				
	•	Fire Dampers	NA	NA	NA				
4.	Smok	Smoke Management System							
	•	Basements	NA	Provided	NA				
	•	Upper floors	NA	Provided	NA				
5.	Fire E	xtinguishers							
	•,	Total numbers	Fire Extinguishers	52 Nos	MR				
	•	Types		ABC-22,W.CO ₂ -	MR				
	• .	IS marking	ISI marked	14, CO ₂ -14, M. Foam-2					
			151 marked	Yes	MR				
6.	First-	First-Aid Hose Reels							
	•	Total numbers on each floor	Hose Reel on each floor	1 No.	MR				
		Length of hose reel hose		30 m	MR				
	•	Nozzle diameter		5 mm	MR				
7.	Auton	Automatic fire detection and alarming system							
	•	Type of detectors	Required	Smoke & Heat	MR				
	•	Location of Main Panel	Required	Ground Floor	MR				
		Location of Repeater Panel	NA	NA	NA				
	•	Alternate source of power	Required	Provided	MR				

	Vikram Hotel at 1 & 2 Ring Road, Lajpat Bhawan, New Delhi-110024							
10.	Automatic Sprinkler System							
	• Basement	Required	Provided	MR				
	Ground Floor	Required	Provided	MR				
	Sprinkler above false ceiling	Required	Provided	MR				
11.	Internal Hydrants							
	Size of riser/down-comer	100mm	Provided	MR				
	Number of hydrants per floor	1 No's	Provided	MR				
10	Hose Box	1 No's	Provided	MR				
12.	Yard Hydrants[Provided & Maintained by Tower management]							
	 Total number of hydrants 	Required	2 No's	MR				
10	Hose Box	Required	2 No's	MR				
13.	Pumping Arrangements							
	Ground Level							
	Discharge of main Pump	Required	1800 LPM	MR				
	> Head of Main pump	Required	60m	MR				
	Number of main pumps Lockey Pump out out	Required	1 No's	MR				
	Jockey Pump out putJockey pump head	Required	180 LPM	MR				
	Jockey pump headStandby Pump out put	Required	60m	MR				
	Standby Pump Head	NA	NA	NA				
	> Auto Starting/Manual	NA	NA	NA				
	Stopping	Required	Provided	MR				
	Pump House Access	Required	Provided	MR				
	Terrace level							
	Discharge of pump	Required	900 LPM	MR				
	> Head of the pump	Required	40 M	MR				
	> Power Supply	Required	Provided	MR				
	Auto Starting of pump	Required	Provided	MR				
14.	Captive Water Storage for fire fighting							
	 Underground tank capacity 	80,000 Lts	Provided	MR				
	Draw-off connection	Required	Provided	MR				
	Fire service inlet	Required	Provided	MR				
	Access to tank	Required	Provided	MR				
	Overhead Tank capacity	25,000 Lts	Provided	MR				
15.	Exit Signage.	Required	Provided	MR				
16.	Provision of Lifts.							
	Pressurization of Lift Shaft	NA	NA	NA				
	Pressurization of Lift lobby	NA	NA	NA				
	Communication In lift Car	NA	NA	NA				
	Fireman's Grounding Switch	Required	Provided	MR				
	Lift Signage	NA	Provided	NA				
17.	Standby power supply	Required	Provided	MR				
18.	Refuge Area.							
	> Total Area	NA	NA	NA				
	Location	NA	NA	NA				
19.	Fire Control Room							
	Detector System Panel	NA	Provided	NA				
	Flow Switch Panel	NA	NA	NA				
	PA System Panel	NA	Provided	NA				
	Batter backup	NA	Provided	NA				
	Building Floor Plans	NA	NA	NA				
20.	Special Fire Protection System for	NA	CO ₂ flooding system	NA				
	Protection of special Risks, if any:		provided in HT & LT Panels.					

Three/four quest rooms are found under renevation during the

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, It is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Accordingly FSC in shape of DFA is put up for approval.

Signature of Inspecting Officer Name:- A.K. Malik Designation:-DO (SD)

Sin FT, is hwup for 89. plean.