## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001**

18/1-118 F6/DF3/MS/GN/2016/52/1528 Dated: No.

## FIRE SAFETY CERTIFICATE

Certified that M/s Blue Pearl Guest house is located at 16A/3, W.E.A, Karol Bagh, New Delhi-110005 is comprised of basement, ground plus three upper floor using basement for storage, ground as reception, lobby, office and shops, first, second and third floor each having 10 guest rooms respectively and a pantry with two rooms for staffs in temporary shed with D.G. set on terrace owned / occupied by M/s Blue Pearl Guest house was granted FSC by this department vide letter No.F6/DFS/MS/GH/2013/531 dated 08/07/2013. The premises was re-inspected by the officer concerned of this department on 27/09/16 in the presence of Mr. Rajesh Kumar Pandey, Manager of the guest house and found that the said guest house have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class residential (guest house) with effect from -13/13/16 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010.

(VIPEN KENTAL) Chief Fire Officer

Copy to:-

py to:
1. The Manager, M/s Blue Pearl Guest house, 16A/3, W.E.A, Karol Bagh, New Delhi-110005 18 10 (6)

2. The Joint C.P.(Lic.), Police Station, Defence Colors 1st G.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

## **INSPECTION REPORT**

1. Name & address of the building:- M/s Blue Pearl Guest House, 16A/3, W.E.A, Karol Bagh, New Delhi-5

2. Type of Occupancy :- Residential (Guest House)

3. Type of Case :- Renewal

4. Details of previous NOC :- F.6/DFS/MS/GH/2013/531 DATED 08-07-2013

5. Fire Safety directives letter No :- N/A

6. Date of inspection :- 27.09.2016

7. Name of the Inspecting Officers: M.K Chattopadhyay, DO (SW), CDC

8. Name and designation of officers

from the building side : Mr. Rajesh Kumar Pandey, Manager

9. Year of Construction : 2009

10. Applicant's letter No. : nil dated nil

M/s Blue Pearl Guest house is comprised of basement, ground plus three upper floor using basement for storage, ground as reception, lobby, office and shops, first, second and third floor each having 10 guest rooms and pantry with two rooms for staffs in temporary shed.

S. No.		nimum Standards on fire ntion and fire safety U/R 33	Requirements as peletter dated 08-07-20		Provided at site	Remarks MR/NMR	
1	Access to building						
	•	Road width	09 mts		Provided	MR	
	•	Gate width	4.5 mts		Directly accessible from the road	MR	
	•	Width of internal road	N/A		N/A	N/A	
2	Number, Width, Type & Arrangement of Exits						
	a. Number of staircases		-	-	•	-	
		Upper Floors	01	01		MR	
		Basements	02	02		MR	
	b. Width of staircases		-	-			
	0. W1	• Upper Floors	1.25 mts	1.3	30 mts	MR	
	. •	Basements	As per sanctioned building plan dated 20-04-2009	3.1	10 mts & 1.05 mts	MR	
	c. Protection of exits		-	_	. 1	_	
	•	Fire check door	N/A	N/	'A	N/A	
	•	Pressurization	N/A	N/		N/A	
	e. No	o. of continuous staircases to	01	01		MR	
	terrace g. Width of Corridor h. Door Size		1.25 mts		25 mts	MR	
			1 mts	85	cm	MR being old case	
2							
3	Com	partmentation.  Fire check door	N/A	N/	/A	N/A	
		Sealing of electrical shafts	N/A	N/	/A	N/A	
		Fire Rating of shaft door	N/A	N/	'A .	N/A	
			N/A	N/	'A	N/A	



	Fire Dampers				1
4	Smoke Management System.				
	• Basements	30 a/c per hour	Exhaust fan provided		MR
	Upper floors	12 a/c per hour	Natural Ventilation		MR
5	Fire Extinguishers				
	Total numbers	03 no's at each floor	Provided	M	R
	• Types	WCO2,ABC, CO2 type	Provided	M	R
	IS marking	ISI marked	Provided	M	R
6	First-Aid Hose Reels.				
	<ul> <li>Total numbers on each floor</li> </ul>	01	Provided	MR	
	• Length of hose reel hose 30 m		Provided	MR	
	Nozzle diameter	5 mm	Provided	MR	
7	Automatic fire detection and alarn				Parity.
	• Type of detectors	N/A	N/A	N/	'A
	<ul> <li>Location of Main Panel</li> </ul>	N/A	N/A	N/	'A
λ	<ul> <li>Location of Repeater Panel</li> </ul>	N/A	N/A	N/	'A
	Alternate source of power	N/A	N/A	N/	'A
	Hooters' Location	N/A	N/A	N/	'A
8	MOEFA	Required	Provided	M	R
9	Public Address System.	Required	Provided	MR	
10	Automatic Sprinkler System.				
	• Basement	Required	Provided		MR
	• Upper Floor	N/A	N/A		N/A
	<ul> <li>Sprinkler above false</li> </ul>	N/A	N/A		N/A
	ceiling				
11	Internal Hydrants	27/4	27/4		<b>NT/A</b>
	• Size of riser/down-comer	N/A	N/A		N/A
	<ul> <li>Number of hydrants per</li> </ul>	N/A	N/A		N/A
	floor	N/A	N/A		N/A
	Hose Box				
12	Yard Hydrants.	N/A	N/A		N/A
	Total number of hydrants	N/A	N/A		N/A
1.5	Hose Box	14/17	14/71		11/11
13	Pumping Arrangements.				-
	Ground Level		N/A	N/A	
	Discharge of main Pump	N/A	N/A N/A	. N/	
				TAT/	

V/			M-	(0		
4		> Number of main pumps	N/A	N/A	N/A	
1		> Jockey Pump out put	N/A	N/A	N/A	
		> Jockey pump head	N/A	N/A	N/A	
		> Standby Pump out put	N/A	N/A	N/A	
		> Standby Pump Head	N/A	N/A	N/A	
		> Auto Starting/ Manual	N/A	N/A	N/A	
		stopping	N/A	N/A	N/A	
		> Pump House Access	-	-	-	
	•	Terrace level	450 LPM (02 no's)	Provided	MR	
		> Discharge of pump	30 mts	Provided	MR	
		> Head of the pump	Required	Provided	MR	
		<ul><li>Power Supply</li><li>Auto Starting of pump</li></ul>	Required	Provided	MR	
14	Canti	ve Water Storage for fire figl	ting.			
		Underground tank capacity	N/A	N/A	N/A	
4	100	Draw-off connection	N/A	N/A	N/A	
A	1012	Fire service inlet	N/A	N/A	N/A	
	>	Access to tank	N/A	N/A	N/A	
	•	Overhead Tank capacity	10, 000 lts	10,000 lts	MR	
15	Exit S	Signage.	Required	Provided	MR	
16		sion of Lifts. Lift is under in	1			
	•	Pressurization of Lift Shaft	N/A	N/A	N/A	
	•	Pressurization of Lift lobby	N/A	N/A	N/A	
	•	Communication in lift Car	Required	Provided	MR	
	•	Fireman's Grounding	Required	Provided	MR	
		Switch	Required	Provided	MR	
		Lift Signage		To the second	IVIIC	
17	Stand	lby power supply	Required	Provided	MR	
18	Refuge Area.					
	>	Total Area	N/A	N/A		
	>	Location	N/A	N/A	N/A	
19	Fire Control Room					
		Detector System Panel	N/A			
		Flow Switch Panel	N/A	N/A	N/A	
		PA System Panel	N/A	N/A	N/A	
		Batter backup	N/A	N/A	N/A	
			N/A	N/A	N/A	
	<b>A</b>	Total Area Location  Control Room  Detector System Panel  Flow Switch Panel  PA System Panel	N/A  N/A  N/A  N/A  N/A	N/A N/A N/A N/A	N/A	

20	Special Fire Protection Systems for	N/A	N/A	N/A
	Protection of special Risks, if any			2

The fire protection system provided in the building were checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2013/531 dated 08/07/2013, renewal under rules 35 of the Delhi Fire Service Rules 2010 is recommended.

Accordingly, DFA is put up please.

(M.K. CHATTOPADHYAY) Divisional Officer (SW), CDC

What about compliance of short comings