GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

No. F6/DFS/MS/2016/SZ/1542

Dated: 19/10/16

FIRE SAFETY CERTIFICATE

Certified that the **Anand Niketan Club and Multipurpose Hall** located at Anand Niketan, New Delhi-110021, comprised of Basement, Ground plus One upper floor was granted FSC by this department vide letter No. F6/DFS/MS/2013/SZ/116 dated 01.11.2013. the premises was reinspected by the officer concerned of this department on 16.09.2016 in the presence of Mr. Satender Kumar Sharma and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fir for occupancy class **Group-D Assembly Building** with effect from 19 1/6 1/6 for a period of **Three years** in accordance with rule 36 unless renewed under rile 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 19/16/1/2 at New Delhi by

Vipin Kental Chief Fire Officer Ph.: 011-23412225

Copy to: -

1. Anand Niketan Club and Multipurpose Hall, Anand Niketan, New Delhi-110021

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety and means of escape facilities shall be maintained in good working condition at all time. Any lapse rendering the fire safety or means of evacuation facilities non-functional shall be the responsibility of the management.
- 2. Building Sanctioning authority may verify any deviation with regard to construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null & void.
- 3. The staff shall be trained for operating fire fighting system and mock evacuation drill be conducted at regular interval and record be maintained.
- 4. The basement shall be used strictly as per the provisions of Building Bye Laws.
- 5. The Owner/Occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules, 2010. The form is available on www.dfs.delhigovt.nic.in.
- 6. The water capacity of 50,000 Ltr shall always remain available in the swimming pool for firefighting purpose all the time.
- 7. The Owner/Occupier shall apply for renewal of this Fire Safety Certificate to the Director in the form 'J' [sub rule (1) of rule 37] along with copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in.

		ION REPORT				
1	Name & Address of the Building	Anand Niketan Club and Multipurpose Hall located at				
1			Anand Niketan, New Delhi–110021			
2	Type of Occupancy	Assembly Building "Group-D"				
3	Building Comprised of	Basements, Ground plus one upper floor.				
4	Type of Case	Renewal				
5	Details of Previous NOC	F6/DFS/MS/2013/SZ/1166 dated 01/11/2013				
6	Fire Safety Directives Letter No		2001/272 dated 14/02/20	01		
7	Date of Inspection	16.09.2016				
8	Name of the Inspecting Officers	ADO R.N. Singh				
9	Name & Designation of Officers from the building side	Mr. Satender Kumar Sharma.				
10	Year of construction	2004				
11	Applicant letter No.	ANC/182 dated 22/08/2016				
. No	Minimum standards on Fire Prevention	NBC / BBL Provided at Site Remark				
. IVO	and Fire Safety U/R 33	Requirements	Florided at Site	MR/NMF		
1	Access to Building.	Requirements		10110/101011		
	1. Road width	9 Mts.	9 Mts.	MR		
	2. Gate width	5 Mts.	5 Mts.	MR		
	3. Width of internal road	NA	NA	NA		
2	Number, width, type and arrangements o	1	IVA	IVA		
	a. Number of Staircase	i exits.				
	1. Upper floors	3 Nos.	3 Nos.	MR		
	2. Basement floor	2 Nos.	2 Nos.	MR		
	b. Width of Staircase	Z IVOS.	2 1405.	IVIN		
		1.50 844-	1 F == 1 20 == 9 120 ==	MR		
	Upper floors	1.50 Mts.	1.5 m, 1.20 m & 120 m			
	2. Basement floor	4 50 844-	4.50 0.4.20	(old case)		
	D. J. Minner of the control of the c	1.50 Mts.	1.50 m & 1.20 m	MR (old		
	c. Protection of exits	Doguirod	Provided	MR		
	Fire check door Pressurization	Required NA	NA	10.222		
				NA		
	d. No. of continuous staircase to terrace	1 Nos.	1 Nos.	MR		
	e. Width of corridor	NA	NA	NA		
	f. Door size	1 m	2.15 m Final exit	MR		
3	Compartmentation.	D : 1	D : I I	0.40		
	1. Fire check door.	Required	Provided	MR		
	2. Sealing of electrical shafts.	NA	NA	NA		
	3. Fire rating of shaft door.4. Water curtain	NA	NA	NA		
	5. Fire dampers.	NA	NA .	NA		
_	<u> </u>	Yes	Provided	MR		
4.	Smoke Management system.	20 /	E	8.40		
	1. Basement	30 a/c per hour	Exhaust fan provided	MR		
	2. Upper floors	12 a/c per hour	Exhaust fan provided	MR		
5.	Fire Extinguishers.	T		145		
	1. Total numbers	ICI M.	31 Nos.	MR		
	2. Types	ISI Marked	Co2-14, ABC- 10, WC-3, DCP-2, Foam-2	MR		
	3. ISI Marking		Provided	MR		
6.	First Aid Hose Reels.	1	I	l		
	Total numbers on each floor.	2 Nos.	Provided	MR		
				1		
	2. Length of hose-reel hose.	30 Mts.	Provided	MR		

Case: Renewal

Page-1

Anand Niketan Club & Multipurpose Hall

hy

1. Type of detection and Alarming s 1. Type of detectors 2. Location of Main Panel 3. Location of Repeater Panel 4. Alternate source of power 5. Hooter's location MOEFA Public Address System Automatic Sprinkler System 1. Basement 2. Upper floors 3. Sprinkler above false ceiling Internal Hydrants.	Smoke & Heat Required NA Required Required Required Required Required NA	Smoke. Ground floor NA Provided. Each floor Provided Provided Provided	MR MR NA MR MR MR MR MR						
3. Location of Repeater Panel 4. Alternate source of power 5. Hooter's location MOEFA Public Address System Automatic Sprinkler System 1. Basement 2. Upper floors 3. Sprinkler above false ceiling Internal Hydrants.	NA Required Required Required Required Required NA	NA Provided. Each floor Provided Provided	MR MR MR						
4. Alternate source of power 5. Hooter's location MOEFA Public Address System Automatic Sprinkler System 1. Basement 2. Upper floors 3. Sprinkler above false ceiling Internal Hydrants.	Required Required Required Required Required NA	Provided. Each floor Provided Provided	MR MR MR						
5. Hooter's location MOEFA Public Address System Automatic Sprinkler System 1. Basement 2. Upper floors 3. Sprinkler above false ceiling Internal Hydrants.	Required Required Required Required NA	Each floor Provided Provided	MR MR MR						
MOEFA Public Address System Automatic Sprinkler System 1. Basement 2. Upper floors 3. Sprinkler above false ceiling Internal Hydrants.	Required Required Required Required NA	Provided Provided	MR MR						
Public Address System Automatic Sprinkler System 1. Basement 2. Upper floors 3. Sprinkler above false ceiling Internal Hydrants.	Required Required Required NA	Provided Provided	MR						
Automatic Sprinkler System 1. Basement 2. Upper floors 3. Sprinkler above false ceiling Internal Hydrants.	Required NA								
Basement Upper floors Sprinkler above false ceiling Internal Hydrants.	NA	Provided							
Upper floors Sprinkler above false ceiling Internal Hydrants.	NA	Provided							
3. Sprinkler above false ceiling Internal Hydrants.		FIOVICEC	MR						
Internal Hydrants.		NA	NA						
	NA	NA	NA						
 Size of Riser / Down-comer 	100 mm	100 mm	MR						
2. Number of Hydrant per floor	2 Nos.	2 Nos.	MR						
3. Hose box.	2 Nos.	2 Nos.	MR						
Yard Hydrants.									
1. Total number of hydrants.	3 Nos.	3 Nos.	MR						
2. Hose box.	3 Nos.	3 Nos.	MR						
Pumping arrangements.									
1. Ground Level		-							
a) Discharge of main pump.	1620 LPM	1620 LPM	NMR						
b) Head of main pump.	56 Mtr.	56 Mtr.	MR						
c) Number of main pumps.	1 No	1 No	MR						
d) Jockey Pump output.	180 LPM	180 LPM	MR						
e) Jockey Pump head.	56 Mtr	56 Mtr	MR						
f) Standby Pump output.	1620 LPM		MR						
The state of the s	56 Mtr.	56 Mtr.	MR						
h) Auto Starting / Manual Stopping.	Required	Provided	MR						
2. Terrace Level									
a) Discharge of pump.	NA	NA	NA						
b) Head of pump.	NA		NA						
c) Power supply.	NA		NA						
d) Auto starting of pump.	NA		NA						
Captive water storage for Fire Fighting.			11						
Underground tank capacity.	50000 Ltr.	50000 Itr / Serimonia							
2. Draw-off connection.	NA	NA Post)	NA						
3. Fire Service Inlet.	Required	Provided	MR						
4. Access to tank.	Required	Provided	MR						
5. Overhead tank capacity.	20000 Ltr.	20000 Ltr.	MR						
Exit Signage.	Required	Provided	MR						
Provision of Lifts.									
1. Pressurization of lift shaft.	NA	NA	NA						
2. Pressurization of lift lobby.	NA	NA	NA						
3. Communication in lift car.	NA	NA	NA						
4. Fireman's switch.	Required		MR						
Lift signage.			MR						
Standby Power Supply			MR						
Refuge Area			1311						
1. Total area	NA	NA	NA						
2. Location			NA						
	Yard Hydrants. 1. Total number of hydrants. 2. Hose box. Pumping arrangements. 1. Ground Level a) Discharge of main pump. b) Head of main pumps. c) Number of main pumps. d) Jockey Pump output. e) Jockey Pump head. f) Standby Pump head. h) Auto Starting / Manual Stopping. 2. Terrace Level a) Discharge of pump. b) Head of pump. c) Power supply. d) Auto starting of pump. Captive water storage for Fire Fighting. 1. Underground tank capacity. 2. Draw-off connection. 3. Fire Service Inlet. 4. Access to tank. 5. Overhead tank capacity. Exit Signage. Provision of Lifts. 1. Pressurization of lift shaft. 2. Pressurization of lift lobby. 3. Communication in lift car. 4. Fireman's switch. 5. Lift signage. Standby Power Supply Refuge Area 1. Total area 2. Location	Yard Hydrants. 1. Total number of hydrants. 2. Hose box. 2. Hose box. 3 Nos. Pumping arrangements. 1. Ground Level a) Discharge of main pump. b) Head of main pumps. c) Number of main pumps. d) Jockey Pump output. e) Jockey Pump head. f) Standby Pump output. g) Standby Pump head. h) Auto Starting / Manual Stopping. 2. Terrace Level a) Discharge of pump. b) Head of pump. c) Power supply. d) Auto starting of pump. 1. Underground tank capacity. 2. Draw-off connection. 3. Fire Service Inlet. 4. Access to tank. 5. Overhead tank capacity. Exit Signage. Provision of Lifts. 1. Pressurization of lift shaft. 2. Pressurization of lift car. 4. Fireman's switch. 5. Lift signage. Required Refuge Area 1. Total area 2. Location	Yard Hydrants. 1. Total number of hydrants. 2. Hose box. 2. Hose box. 3 Nos. 4 No Not. 4 No. 4 No. 4 No. 5						

Case: Renewal

Page-2

Anand Niketan Club & Multipurpose Hall



19.	Fire Control Room.					
	Detector System Panel.	NA	NA	NA		
	2. Flow Switch Panel.	NA	NA	NA		
	3. PA system Panel.	NA	NA	NA		
	4. Battery backup	NA	NA	NA		
	5. Building floor plan	NA	NA	NA		
20.	Special Fire Protection System for the Protection of special Risk, if any :	NA	NA	NA		

The fire protection system provided in the building were checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F6/DFS/MS/2013/SZ/1166 dated 01.11.2013, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name

: R.N. Singh

Designation: ADO

Renewal Case:

Page-3

Anand Niketan Club & Multipurpose Hall

Div. Officer (SD)