GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6 / DFS / MS /GH/2016 / W2/1584

Dated: 26/10/16

FIRE SAFETY CERTIFICATE

Certified that the Shanti Royal Banquets, B-4, , G.T.Road Indl. Area, Delhi comprised of basement+ ground and two upper floors owned/ occupied by Shanti Royal Banquets has already been issue fire safety certificate vide letter no. F6/DFS/MS/2013/239 dated 02/05/2013. The premises was re-inspected by the officer concerned of Fire Service on 28/04/2016 in the presence of Sh. Sanjay Grover (Manager) and observed that all the fire prevention & fire safety arrangements as provided in the premises found in good working condition. The premises have therefore deemed complied with the fire prevention and fire safety accordance with rule 33 of the Delhi Fire Service rule 2010 for a period, of three years in accordance with rules 36 unless renewed under rule. 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <u>WWW.dfs.Delhigovt.nic.in</u>
- 8. All the means of escape shall be kept free of any obstruction all the time to evacuate the occupant, in a safe manner, in the event of emergency.

Issued on .2.6.... at New Delhi by

Chief Fire Officer Ph:-011-23414250

Copy to:-

1. The Additional Commissioner of Police (Lic), 1st floor, Police Station, Defence Colony, New Delhi.

2. The Manager, Shanti Royal Banquets, B-4, , G.T.Road Indl. Area, Delhi

INSPECTION REPORT

Name & address of the building: Shanti Royal Banquets, B-4, , G.T.Road Indl. Area, Delhi.

:ADO (RN)

Type of Occupancy :Guest House(B+G+02 upper floors)

Type of Case :Renewal

Details of previous NOC :F6/DFS/MS/2013/239 dated 02/05/2013

5. Fire Safety directives letter No :old case Date of inspection 6. :10/10/2016 7. Name of the Inspecting Officers

8. Name and designation of officers

from the building side : Sh.Sanjay Grover (Manager)

9. Year of Construction : 2012

10. Applicant's letter No. : Nil dated 23/09/2016

Minin	num Standards on fire prevention and fire safety U/R 33	NBC/ BBL Requirement	Provided at site	Remarks MR/NMR	
Access to building					
•	Road width	09m	20m	MR	
	Gate width Width of internal road	Directly Accessible	Directly Accessible	MR	
	Width of Internal load	NA	NA	NA	
Number, Width, Type & Arrangement of Exits					
a. Numb	per of staircases				
•	Upper Floors	02	03	MR	
•	Basements	02	02	MR	
b. Width	of staircases				
•	Upper Floors Basements	02	1.50m, 2.60m &1.16m	MR Fold Cone	
1, 14	etion of exits	02	1.50m &2.00m	MR	
•	Fire check door		/	2 8	
•	Pressurization	Required	Provided	MR	
d. No. o	of continuous staircases to terrace	NA	NA	NA	
	of Corridor	02	03	MR	
		NA	NA	NA	



Mas

	C D G:					
	f. Door Size	2.0m	2.0m	MR		
3	Compartmentation.					
	Fire check door	Required	Provided	MR		
	 Sealing of electrical shafts 	NA	NA	NA		
	Fire Rating of shaft door	NA	NA	NA		
	Water Curtain	NA	NA	NA		
	Fire Dampers	NA	NA	NA		
		1471	INA	INA		
4	Smoke Management System.					
	• Basements	30 a/c per hour	Provided	MR		
	Upper floors	12 a/c per hour	Natural Ventilated	MR		
5	Fire Extinguishers					
	Total numbers	016nos	16	MR		
	• Types	ABC & Co2	W. Co2 - 08	MR		
	a ISI madrina		Co2 - 08			
6	• ISI marking First-Aid Hose Reels.	Yes	Yes	MR		
6						
6	First-Aid Hose Reels. • Total numbers on each floor	Yes 02	Yes 02	MR MR		
6	First-Aid Hose Reels.					
6	First-Aid Hose Reels. • Total numbers on each floor	02	02	MR		
	First-Aid Hose Reels. • Total numbers on each floor • Length of hose reel hose	02 30m 5mm	02 30m	MR MR		
	 First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter 	02 30m 5mm	02 30m	MR MR		
	First-Aid Hose Reels.	02 30m 5mm	02 30m 5mm	MR MR MR		
	First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming syste Type of detectors	30m 5mm Em. Required	02 30m 5mm	MR MR MR		
	First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming syste Type of detectors Location of Main Panel	30m 5mm Em. Required G.F	02 30m 5mm Provided Provided	MR MR MR MR		
	First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming syste Type of detectors Location of Main Panel Location of Repeater Panel	30m 5mm em. Required G.F NA Required	02 30m 5mm Provided Provided NA Provided	MR MR MR MR MR MR NA		
7	First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming syste Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location	30m 5mm Em. Required G.F NA Required Common Areas	02 30m 5mm Provided Provided NA Provided Provided	MR MR MR MR MR MR MR MR		
7	First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming syste Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA	30m 5mm em. Required G.F NA Required	02 30m 5mm Provided Provided NA Provided	MR MR MR MR MR MR NA		
7 8 8	First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming syste Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location	30m 5mm Em. Required G.F NA Required Common Areas Required	02 30m 5mm Provided Provided NA Provided Provided Provided Provided	MR MR MR MR MR MR MR MR		
6 7 7 10	First-Aid Hose Reels. Total numbers on each floor Length of hose reel hose Nozzle diameter Automatic fire detection and alarming syste Type of detectors Location of Main Panel Location of Repeater Panel Alternate source of power Hooters' Location MOEFA Public Address System.	30m 5mm Em. Required G.F NA Required Common Areas Required	02 30m 5mm Provided Provided NA Provided Provided Provided Provided	MR MR MR MR MR MR MR MR		



NM

	•	Sprinkler above false ceiling	NA	NA	1	
1	Intern	al Hydrants	IVA	NA	NA	
	The state of the s					
	•	Size of riser/down-comer	100mm	100mm	MR	
	•	Number of hydrants per floor Hose Box	02 Nos.	Provided	MR	
			02 Nos.	Provided	MR	
12	Yard Hydrants.					
	•	Total number of hydrants	NA	NA	NA	
	•	Hose Box	NA	NA	NA	
13	Pumpi	ng Arrangements.				
	•	Ground Level				
		Discharge of main Pump				
		Head of Main pump	2280 lpm	2280 lpm	MR	
		Number of main pumps	40m	40m	MR	
		 Jockey Pump out put 	Q2no.	Oino.	MR	
	21	> Jockey pump head	180 lpm	180 lpm	MR	
		Standby Pump out put	40m	40m	MR	
		Standby Pump Head	2280 lpm	2280 lpm	MR	
	Auto Starting/ NPump House Ao	Auto Starting/ Manual stoppingPump House Access	40m	40m	MR	
	•	Terrace level	Required	Provided	MR	
		Discharge of pump			.,	
		➤ Head of the pump	900 LPM	900 lpm	MR	
		➤ Power Supply	40m	40m	MR	
		Auto Starting of pump	Required	Provided	MR	
			Required	Provided	MR	
14	Captive Water Storage for fire fighting.					
	•	Underground tank capacity	50,000 ltr.	50,000 ltr.	MR	
	>	Draw-off connection	NA	NA	NA	
	>	Fire service inlet	NA	NA	NA	
	>	Access to tank	Required	Provided	MR	
	•	Overhead Tank capacity	10000 ltr	10000 ltr.	MR	
5	Exit Sig	nage.	Required	Provided	MR	
		n of Lifts.				



N/28

	Pressurization of Life CL of			
	ressurization of Lift Shaft	N/A	N/A	N/A
	Pressurization of Lift lobbyCommunication In lift Car	N/A	N/A	N/A
	Fireman's Grounding Switch	Required	Provided	MR
	• Lift Signage	NA	NA	NA
7	Charriel Charries	NA	NA	NA
3	Standby power supply	Required	Provided inverter	MR
	Refuge Area.			
	Total Area	N/A	N/A	N/A
	Location	N/A	N/A	N/A
	Fire Control Room			
	Detector System Panel Flow Switch Panel	N/A	N/A	N/A
	Flow Switch PanelPA System Panel	N/A	N/A	N/A
	Batter backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A
	Constitution D	N/A	N/A	N/A
	Special Fire Protection Systems for Protection of special Risks, if any:	Separate circuit for emergency service	Provided	MR

The fire protection systems provided in the building were tested/ checked and found some in working order at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to renew Fire Safety Certificate issued vide this department letter of even no. 239 dated 02.05.2013 under rule 35 of the Delhi Fire Service Rules 2010.

Signature of the Inspecting Officer

Name: - Rajesh Kumar

Designation:- ADO/RN

15.10.16 Dy CEA(WZ)