GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2016/ NDZ/1586

Dated: 27/10/16

FIRE SAFETY CERTIFICATE

Certified that the Paras Guest House located at 7876/6, Arakashan Road, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (01 guest rooms + reception), 1st floor (03 guest rooms), 2nd floor (02 guest rooms), 3rd floor (03 guest rooms) and terrace floor (01 store room + kitchen for staff sealed), total 12 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2012/2571 dated 18/07/12. The premises was re-inspected by the officer concerned of this department on 15/10/16 in the presence of Sh. Jahangi Alam (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 12 guest rooms only with effect from 2-7-1-6--------- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 27 16 -- at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.

2. The Manager,
Paras Guest House located at 7876/6, Arakashan Road, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INSPE	CTION REPOR	RT		
3. 4. 5. 6. 7.	INSPE Name & address of the building Type of case:- Details of previous FSC:- Fire safety directives No Date of inspection:- Name of the inspecting officer:- Name & designation of officer	CTION REPORT Paras Guest House located at 7876/6, Arakashan Road, Pahar Ganj, New Delhi Gr. + 04 Upper floors,) total 12 guest rooms Ground floor (01 guest rooms + reception), 1st floor (03 guest rooms), 2nd floor (02 guest rooms), 3rd floor (03 guest rooms), 4th floor (03 guest rooms) and terrace floor (01 store room + kitchen for staff sealed) Renewal No. F6/DFS/MS/GH/2012/2571 dated 18/07/12. N/A 15/10/16 Sh. Manoj Kumar Sharma (ADO/CC)			
δ.	From the building side:- Sh. Jahangi Alam (Manager)				
9.	Year of construction:-	2001			
	Applicant's letter No:-	Nil dated 26/0	09/2016.		
*				Old Case	
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR	
1.	Access to Building				
	1) Road width	N/A	06 mtr.	N/A	
	2) Gate width	N/A	N/A	N/A	
	3)Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Arr		kits		
	A. Number of staircases				
	1. Upper floors	01 Nos.	01 Nos.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase		3	= 1	
	1. Upper floors	0.80 mtr.	1.20 Mtr.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits				
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous	N/A	N/A	N/A	
	staircase to terrace			. 11	
	E. Wigth of corridor	N/A	N/A	N/A	
2	F. Door size	01 mtr.	01 mtr.	MR	
3.	Compartmentation	127/4	127/	1	
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	·N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
1	5) Fire Dampers	N/A	N/A	N/A	
4.	Smoke Management System		I NI/A	127/4	
	1) Basements	30 ACPH	N/A	N/A	
	2) Upper floors	12 a/c per	Natural	MR	
		THE STATE			

hour

5.	Fire Extinguishers		1			
	1) Total numbers	10	10	MR		
	2) Types	ABC & CO2	ABC & CO2	MR		
191	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel					
	1) Total number of eachfloor	01	01	MR		
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR		
	3) Nozzle diameter	05 mm	05 mm	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	N/A	N/A	N/A		
9.	Public Address System	N/A	N/A	N/A		
10.	Automatic Sprinkler System	- 1/4	- V/1	1 1/2 1		
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling					
11.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor					
	3) Hose box	N/A	N/A	N/A		
12.	Yard Hydrants					
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement					
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main	N/A	N/A	N/A		
	pump					
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump	N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual	N/A	N/A	N/A		
	stopping	-//	V.			
	2) Terrace level	-				
	a) Discharge of pump	225 LPM	225 LPM	MR		
	b) Head of pump	30 mtr.	30 mtr.	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided	MR		
14.	Captive Water Storage for Fi					
	1) Under ground tank	N/A	N/A	N/A		
	capacity					
	a) Draw-off connection	N/A	N/A	N/A		

Las

	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
×	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syster Risk, if any: ABC & CO ₂	em for Protec	tion of special	MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/GH/2015/1726 dated 31/07/2015 have been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2012/2571 dated 18/07/12 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

DO(CD)

Sehn)