GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

No. F6/DFS/MS/GH/2016/SZ/ 1615

Dated: 31 10/16

FIRE SAFETY CERTIFICATE

Nizamuddin, New Delhi, comprised of ground floor (Reception + 03 G/Rooms), first floor (05 G/Rooms), second floor (05 G/rooms), third floor (05 rooms for private use), fourth floor (03 rooms for pvt. use) & fifth floor (02 rooms-sealed by owner) was granted FSC for 13 guest rooms up to second floor by this department vide letter No. F.6/DFS/MS/GH/2013/SZ/1009 dated 03/10/2013. The premises was re-inspected by the officer concerned of this department on 22.10.2016 in the presence of Mr. Rahul (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fir for occupancy class "Residential & Lodging Building, (Guest House)" with effect from 31 for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 31/10/16 at New Delhi by

Vipin Kental Chief Fire Officer Ph.: 011-23412225

Copy to: -

- 1. M/s S. Pal Palace Guest House, 32-A, Nangli Rajapur, East Nizamuddin, New Delhi -110013
- 2. The Joint Commissioner of Police (Lic.), 1st Floor, PS Defence Colony, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety and means of escape facilities shall be maintained in good working condition at all time. Any lapse rendering the fire safety or means of evacuation facilities non-functional shall be the responsibility of the management.
- 2. Building Sanctioning authority may verify any deviation with regard to construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null & void.
- 3. The staff shall be trained for operating fire fighting system and mock evacuation drill be conducted at regular interval and record be maintained.
- 4. The basement shall be used strictly as per the provisions of Building Bye Laws.
- 5. The Owner/Occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules, 2010. The form is available on www.dfs.delhigovt.nic.in.
- 6. The Owner/Occupier shall apply for renewal of this Fire Safety Certificate to the Director in the form 'J' [sub rule (1) of rule 37] along with copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in.

NIO

		4 110		766	
A	INSPECTI			3	
1	Name & Address of the Building			est House at 32-A,	
7		Nangli Rajapur, East Nizamuddin, New Delhi-13			
2	Type of Occupancy			dging, Group-A (Guest	House)
3	Building Comprised of	Ground plus five upper floors			
4	Type of Case	Renewal			
5	Details of Previous NOC	F.6/DFS	S/MS/GH	/2013/SZ/1009 dated 03/	/10/2013
. 6	Fire Safety Directives Letter No	Nil			
7	Date of Inspection	22.10.2016			
8	Name of the Inspecting Officers	ADO R.N. Singh			
9	Name & Designation of Officers	Mr. Rahul (Manager)			
	from the building side				
10	Year of construction	2005 Ground floor (Rec.+ 03 G/Rooms), 1 st Floor (05 G/Rooms) 2 nd Floor (05 G/Rooms), 3 rd & 4 th floor (05 & 03 rooms for private use) and fifth floor (02 rooms-sealed by owner)			
11	Applicant letter No.	Nil Dt. 1	Nil Outdo	or Diary no. 10136 dated	d 40.10.2016
S. No	Minimum standards on Fire Prevention	Old NOC		Provided at Site	Remarks
	and Fire Safety U/R 33		.2010		MR/NMI
		Requirement			
1	Access to Building.				
	Road width.	6 Mtr		6 Mts.	MR
	Gate width	N/A	1	N/A	N/A
	Width of internal road	N/A		N/A	N/A
2	Number, width, type and arrangements o	f exits.			
72	a. Number of Staircase				
	 Upper floors 	One		One	MR
	Basement floor	N/A		N/A	N/A
	b. Width of Staircase			-	2 8
	Upper floors.	1 m		1 m	MR
	Basement floor.	N/A		N/A	N/A
	c. Protection of exits				
	Fire check door	N/A		N/A	N/A
	Pressurization	N/A		N/A	N/A
	d. No. of continuous staircase to terrace	One		One	MR
	e. Width of corridor	N/A		N/A	N/A
	f. Door size	1 m		1.12 m (final exit)	MR
3	Compartmentation.	1 111		1.12 iii (iiidi exit)	IVIIC
	Fire check door.	N/A		N/A	N/A
	Sealing of electrical shafts.	N/A		N/A	N/A
	• Fire rating of shaft door.	N/A		N/A	N/A
	Water curtain.	N/A		N/A	N/A
	• Fire dampers.	N/A		N/A	N/A
4.	Smoke Management system.	1 11/11		14/21	14/21
т.	Basement	N/A		N/A	N/A
	Upper floors	N/A		N/A	N/A
5.	Fire Extinguishers.	14/11	***************************************	IN/A	IN/A
J.	Total numbers	06 Nac		06 Nos	MD
		06 Nos.		06 Nos.	MR
	• Types	ABC/W.Co2 ISI Marked		ABC- 05 & WCo2-01	MR
-	• ISI Marking	151 Mar	ked	Provided	MR
6.	First Aid Hose Reels.	TT -	1		
	Total numbers on each floor.	Hose Reel		01	MR
	 Length of hose-reel hose. 			30 m	MR
	Nozzle Diameter			05 mm	MR

Renewal

S. Pal Palace Guest House at 32-A, Nangli Rajapur, ND-13

7	Autom	natic Fire Detection and Alarming			
	•	Type of detectors	N/A	N/A	N/A
	•	Location of Main Panel	N/A	N/A	N/A
	•	Location of Repeater Panel	N/A	N/A	N/A
	•	Alternate source of power	N/A	N/A	N/A
		Hooter's location	N/A	N/A	N/A
8.	MOEI	FA	Required	Provided	MR
9.	Public	Address System	N/A	N/A	N/A
10.	Auton	natic Sprinkler System	· ·		
	•	Basement	N/A	N/A	N/A
		Upper floors	N/A	N/A	N/A
	•	Sprinkler above false ceiling	N/A	N/A	N/A
11.	Intern	al Hydrants.			
		Size of Riser / Down-comer	N/A	N/A	N/A
		Number of Hydrant per floor	N/A	N/A	N/A
		Hose box.	N/A	N/A	N/A
12.	Yard	Hydrants.	*		
	•	Total number of hydrants.	N/A	N/A	N/A
		Hose box.	N/A	N/A	N/A
13.		ing arrangements.	6	A A	
		ound Level			
		Discharge of main pump.	N/A	N/A	N/A
		Head of main pump.	N/A	N/A	N/A
		Number of main pumps.	N/A	N/A	N/A
		Jockey Pump output.	N/A	N/A	N/A
	A	Jockey Pump head.	N/A	N/A	N/A
	>	Standby Pump output.	N/A	N/A	N/A
	>	Standby Pump head.	N/A	N/A	N/A
	>	Auto Starting/Manual Stopping.	N/A	N/A	N/A
	>	Pump House Access	N/A	N/A	N/A
	• Te	rrace Level	(d)		
	>	Discharge of pump.	Fire Pump	225 LPM	MR
	~	Head of pump.	Required	30 m	MR
	>	Power supply.	Required	Provided (Inverter)	MR
	>	Auto starting of pump.	Required	Provided	MR
14.	Captiv	ve water storage for Fire Fighting.	1	*	
	•	Underground tank capacity.	N/A	N/A	N/A
	•	Draw-off connection.	N/A	N/A	N/A
		Fire Service Inlet.	N/A	N/A	N/A
	•	Access to tank.	N/A	N/A	N/A
		Overhead tank capacity.	2,500 Ltr.	2,500 Ltr.	MR
15.	Exit S	ignage.	Required	Provided	MR
16.		ion of Lifts.	1 1		
		Pressurization of lift shaft.	N/A	N/A	N/A
		Pressurization of lift lobby.	N/A	N/A	N/A
		Communication in lift car.	N/A	N/A	. N/A
		Fireman's switch.	N/A	N/A	N/A
		5. Lift signage.	N/A	N/A	N/A
17		by Power Supply	Required	Provided (Inverter)	MR
18.	-	e Area	required	(Interest)	
10.	Actug	Total area	N/A	N/A	N/A
		2. Location	N/A	N/A	N/A

Renewal

19.	Fire Control Room.						
	Detector System Panel.	N/A	N/A	N/A			
	Flow Switch Panel.	N/A	N/A	N/A			
	 PA system Panel. 	N/A	N/A	N/A			
	Battery backup	N/A	N/A	N/A			
	Building floor plan	N/A	N/A	N/A			
20.	Special Fire Protection System for the	Required	Provided 01 ABC	MR			
	Protection of special Risk, if any.		type fire extinguisher	*			
			near elect. panel				

The Fire Protection system provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F.6/DFS/MS/GH/2013/SZ/1009 dated 03/10/2013, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: R.N. Singh Designation: ADO

Renewal

S. Pal Palace Guest House at 32-A, Nangli Rajapur, ND-13

Div. Officer (SD)

24/0/16

368/cf. 82

dy clotses

25 10 10 10

Chochs

FT/O

mistell 14 ZE/10.