GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

No. F6/DFS/MS/GH/2016/SZ/ (6/7

Dated: 31/10/16

FIRE SAFETY CERTIFICATE

Certified that the Sun Village Inn, A-14, Ring Road, Lajpat Nagar, New Delhi, comprised of Basement, Ground, Mezzanine + 02 upper floors having 16 guest rooms & basement lying vacant was granted FSC by this department vide letter No. F.6/DFS/MS/GH/2013/281 dated 08/05/2013. The premises was re-inspected by the officer concerned of this department on 13.10.2016 in the presence of Mr. Pavitharan (Manager) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fir for occupancy class "Residential & Lodging Building" with effect from 31 10 16 for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 311016 at New Delhi by

Vipin Kental Chief Fire Officer Ph.: 011-23412225

Copy to: -

- 1. M/s Sun Village Inn, A-14, Ring Road, Lajpat Nagar, New Delhi-24
 - 2. The Joint C. P. (Lic.), First Floor, Police Station Defence Colony, New Delhi.

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety and means of escape facilities shall be maintained in good working condition at all time. Any lapse rendering the fire safety or means of evacuation facilities non-functional shall be the responsibility of the management.
- 2. Building Sanctioning authority may verify any deviation with regard to construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null & void.
- 3. The staff shall be trained for operating fire fighting system and mock evacuation drill be conducted at regular interval and record be maintained.
- 4. The basement shall be used strictly as per the provisions of Building Bye Laws.
- 5. The Owner/Occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules, 2010. The form is available on www.dfs.delhigovt.nic.in.
- 6. The Owner/Occupier shall apply for renewal of this Fire Safety Certificate to the Director in the form 'Ĵ' [sub rule (1) of rule 37] along with copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in.

		CTION REPORT				
1	Name & Address of the Building		Sun Village Inn, A-14, Ring Road,			
		Lajpat Nagar,				
2	Type of Occupancy		Residential & Lodging, Group-A (Guest House)			
3	Building Comprised of		Basements, Ground, Mezzanine + 2 upper floors			
4	Type of Case		Renewal			
5	Details of Previous NOC		F.6/DFS/MS/GH/2013/281 dated 08/05/2013			
6	Fire Safety Directives Letter No		Nil			
7	Date of Inspection		13.10.2016			
8	Name of the Inspecting Officers		ADO R.N. Singh			
9	Name & Designation of Officers from the building side	Mr. Pavitharar	Mr. Pavitharan, Manager			
10	Year of construction	guest	Basement (lying vacant) Ground (Rec., 0-guest room) Mezzanine (02 store room) 1s Floor (07 G/rooms) 2nd Floor (05 G/Rooms Total 16 Guest Rooms.			
11	Applicant letter No.	No. 3009/Joint	No. 3009/Joint C.P./Lic. (H) Dt. 26.09.2016 and Party letter no. Nil Dt. 23.09.2016			
S. No	Minimum standards on Fire Preventi		Provided at Site	Remarks		
	and Fire Safety U/R 33	17.07.2009 Requiremen		MR/NMF		
1	Access to Building.					
	Road width.	Accessible	12 Mts.	MR		
	Gate width	NA	NA	NA		
	 Width of internal road 	NA	NA	NA		
2	Number, width, type and arrangemen	its of exits.				
	a. Number of Staircase					
	Upper floors	One	Provided	MR		
	Basement floor	Two	Provided	MR		
	b. Width of Staircase		123,130	TVIIC		
	Upper floors.	1.25 m	1.34 m	MR		
	Basement floor.	1.25 m	1.34 m & .1.25 m	MR		
	c. Protection of exits	1120 111	1.3 · III & .1.23 III	IVIIC		
	Fire check door	Required	Provided	MR		
	Pressurization	NA	NA	NA		
	d. No. of continuous staircase to terr					
	e. Width of corridor	NA NA	One NA	MR		
	f. Door size	1 m	1.25 m (Final exit)	NA		
3	Compartmentation.	1 111	1.23 iii (Filiai exit)	MR		
	• Fire check door.	Required	Provided	MR		
	 Sealing of electrical shafts. 	NA	NA			
	 Fire rating of shaft door. 	NA	NA NA	NA		
	Water curtain.	NA	NA NA	NA		
		NA	NA NA	NA		
4.	• Fire dampers. Smoke Management system.	11/1	INA	NA		
7.	Basement	NA	F-1	27.4		
	Upper floors	NA NA	Exhaust Fan provided	NA		
5.	Fire Extinguishers.	INA	NA	NA		
J.	Total numbers	D . 11 5	00 M	100		
		Portable Fire	08 Nos.	MR		
	• Types	Extinguishers	ABC- 04 & Co2-04	MR		
(ISI Marking First Aid III. Parallel III. Pa	ISI Marked	Provided	MR		
6.	First Aid Hose Reels.	1.2				
	Total numbers on each floor.	Hose Reels	One	MR		
	• Length of hose-reel hose.		30 Mts.	MR		
	Nozzle Diameter	9	5 mm	MR		

H/22

	Automatic Fire Detection and Alarm Type of detectors		::	
	Type of acacetors	NA	NA	NA
	• Location of Main Panel	NA	NA	NA
	 Location of Repeater Panel 	NA	NA	NA
	Alternate source of power location MOEF Hooter's location	NA	NA	NA
-8.	MOEF Tooter's location	NA	NA	NA NA
8: 9.		Reguired	Provided	
10.	Public Address System	NA	NA	MR
10.				NA
	• Basement	Required	Provided	110
	 Upper floors 	NA	NA	MR
	Sprinkler above false ceiling	NA	NA	NA
11.	Internal Hydrants.		IVA	NA
	 Size of Riser / Down-comer 	NA	NIA	
	 Number of Hydrant per floor 	NA	NA	NA
	Hose box.	NA	NA	NA
12.	Yard Hydrants.	1411	NA	NA
	 Total number of hydrants. 	NIA		
	Hose box.	NA	NA	NA
13.	Pumping arrangements.	NA	NA	NA
	Ground Level		S2E -	
	bisenarge of main pump.	NA	NA	NA
	of mani pump.	NA	NA	NA
	main pullips.	NA	NA	NA
	a dinpoutput.	NA	NA	NA
	rockey rump mead.	NA	NA	NA
	tump output.	NA	NA	NA
	starraby i unip ficau.	NA	NA	NA
	Tato Starting/Ivialitial Stopping	NA	NA	NA
	Pump House Access	NA	NA	NA
	Terrace Level			11/1
	Discharge of pump.	Boosting Pur	np 450 LPM	MR
	Head of pump.	NA	40 Mtr	NA
	Power supply.	Required	Provided (DG Set)	
1.4	Auto starting of pump.	NIA	Provided (BO Set)	MR
14.	Captive water storage for Fire Fighting.		Trovided	NA
	 Underground tank capacity. 	NA	40,000 Ltr	DIA
	 Draw-off connection. 	NA	NA NA	NA
	 Fire Service Inlet. 	NA	NA	NA
	 Access to tank. 	NA	NA	NA
	 Overhead tank capacity. 	5,000 Ltr.	*	NA
5.	Exit Signage.	Required	10,000 Ltr ·	MR
6.	Provision of Lifts.	required	Provided	MR
	 Pressurization of lift shaft. 	NA	NIA	
	 Pressurization of lift lobby. 	NA	NA	NA
	• Communication in lift car.	NA	NA	NA
	• Fireman's switch.	NA	NA	NA
	• 5. Lift signage.	NA NA	NA	NA
7	Standby Power Supply		NA	NA
3.	Refuge Area	Required	Provided (DG Set)	MR
	Total area	1274	•	
	• 2. Location	NA	NA	NA
	2. Location	NA	NA	NA

Sun Village Inn, A-14, Ring Road, Lajpat Nagar

19.	Fire Control Room.					
	•	Detector System Panel.	NA	NA	NA	
			NA	NA	NA	
			NA	NA	NA	
		Battery backup	NA ·	NA	NA	
		Building floor plan	NA	NA	NA	
20.		l Fire Protection System for the	NA	NA	NA	
	Protec	ction of special Risk, if any.				

The Fire Protection system provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F.6/DFS/MS/GH/2013/281 dated 08/05/2013 renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name: R.N. Singh Designation: ADO

Renewal

Sun Village Inn, A-14, Ring Road, Lajpat Nagar

Div. Officer (SD)

by coc(S2)

Cher Fire Office

354/CAS2 00/00/16/21/16/0(54) 24/4

m.sell

FTM