GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2016/ 1641

Dated :--- 08.11.2016

FIRE SAFETY CERTIFICATE

Certified that the Everest Palace Guest House located at 8244-A,Gali No.6,Multani Dhand, Pahar Ganj, New Delhi-110055.comprised of Ground + 4 Upper Floors, ground floor – reception + 01 guest room 1st floor to 4th floor 02 guest rooms at each floor total 09 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2013/07 dated 05.03.2013. The premises was re-inspected by the officer concerned of this department on 14.10.2016 in the presence of Mr. Pawan Katyal and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules. 2010 and that the premises is fit for occupancy of class Residential Group –A-1' for total 09 guest rooms only as above with effect from –38.11.2014.

——for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. mentioned below.

(Vipin Kental) Chief Fire Officer Delhi Fire Service Ph: - 011-23412225

Copy to:-

1. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi

The Licensee,
 Everest Palace Guest House,
 8244-A,Gali No.6,Multani Dh.

8244-A, Gali No.6, Multani Dhand, Pahar Ganj, New Delhi-110055.

Condition:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. The means of escape shall be kept unobstructed / unlocked & remain available for speedy evacuation of occupants in case of an emergency.
- 3. The means of escape shall be kept unobstructed / unlocked & remain available for speedy evacuation of occupants in case of an emergency.
- 4. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 5. The trained fire fighting staff should be available round the clock.
- 6. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 7. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 8. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

14-19

	INSPECTION REPORT							
	1.N	fame & address of the building:-		e Guest House,824				
				i Dhand,Pahar Gan	J,New Delni-			
			110055.		i 4			
	2.	Type of occupancy:-		Group A-1 Ground	+ 4 upper			
				floors.(09 guest rooms)				
			-ground floor – reception ,+ 01 guest room, 1 st floor to 4 th floor 02 guest rooms at each floor.					
					t 100ms at each 1100r.			
		Type of case:-		/MS/GH/2013/07 d	/07 dated			
	4.	Details of previous FSC:-	05/03/2013.	/W15/011/2015/07 C				
	_	Fire anfaty dimentiyon No.						
		Fire safety directives No	14/10/16					
		Date of inspection:		ıkh Singh				
	7. Name of the inspecting officer: D.O. Gurmukh Singh							
		8. Name & designation of officer From the building side:- Mr. Pawan Katyal.						
		From the building side:- Year of construction:-	2002.	Laty at.				
		-,		N0.2400/Joint C.P./Lic. (H) dated 07/09/16				
	10.	10. Applicant's letter No:- N0.2400/Joint C.P./Lic. (H) dated 07/09/16 Old Case						
S.N	Jo.	Minimum Standards on fire	Requirement/	Provided at site	Remarks			
D.1	10.	Prevention and fire safety	Existing fire		MR/NMR			
		U/R 33	safety					
		0/10/33	arrangements					
1.		Access to Building	2					
		1) Road width	N/A	6 mtr.	N/A			
		2) Gate width	N/A	N/A	N/A			
		3)Width of internal road	N/A	N/A	N/A			
2.		Number, Width Type & Arran	125 20		- 2			
		A. Number of staircases						
		1. Upper floors	01 No.	01 No.	MR			
		2. Basements	N/A	N/A	N/A			
		B. Width of staircase						
	, a 2	1. Upper floors	80 cms.	100 to 102 cms	MR			
		2. Basements	N/A	N/A	N/A			
		C. Protection of exits						
		1. Fire check door	N/A	N/A	N/A			
	1	2. Pressurization	N/A	N/A	N/A			
	2	D. No. of continuous	N/A	N/A	N/A			
		staircase to terrace	14/17	11/12				
342		E. Width of corridor	N/A	N/A	N/A			
		F. Door size	1.0 mtr.	1.0 mtr.	MR			
2			1.0 IIII.	1.0 11111.	17110			
3.	i i	Compartmentation	27/1	NT/A	DI/A			

N/A

N/A

N/A N/A

1) Fire check door

4) Water curtain

2) Sealing of electrical shafts

3) Fire rating of shaft door

N/A

N/A

N/A N/A N/A

N/A

N/A

N/A

	-	1
/		,

	5) Fire Dampers	N/A	N/A	N/A			
4.	Smoke Management System	IN/A	IN/A	IN/A			
т.		30 ACPH	N/A	N/A			
	2) Upper floors	12 ACPH	Natural	MR			
5.	Fire Extinguishers	12 ACITI	Ivaturar	IVIK			
J.	1) Total numbers	10 Nos.	10 Nos.	MR			
		ABC & CO2	ABC &CO2	MR			
	0) TOT 11		Provided	MR			
		Required	Tiovided	IVIIC			
6.	First-Aid Hose Reel	0.1					
		01 no.	01 no.	MR			
	floor	20	20	1			
		30 mtr.	30 mtr.	MR			
7		5 mm.	5 mm.	MR			
7.	Automatic Fire Detection & Alarming System						
		N/A	N/A	N/A			
	1	N/A	N/A	N/A			
	1	N/A	N/A	N/A			
		N/A	N/A	N/A			
)		N/A	N/A	N/A			
3.		N/A	N/A	N/A			
9.	Public Address System /	Required	Provided	MR			
1.0	Interconi						
10.	Automatic Sprinkler System						
		N/A	N/A	N/A			
		N/A	N/A	N/A			
		N/A	N/A	N/A			
	ceiling						
11.	Internal Hydrants						
		N/A	N/A	N/A			
	1	N/A	N/A	N/A			
	floor						
		N/A	N/A	N/A			
12.	Yard Hydrants	5					
		N/A	N/A	N/A			
		N/A	N/A	N/A			
13.	Pumping Arrangement						
	1) Ground level	N/A	N/A	N/A			
	a) Discharge of main pump	N/A	N/A	N/A			
	b) Head of main pump	N/A	N/A	N/A			
	c) Number of main pump	N/A	N/A	N/A			
	d) Jockey pump out put	N/A	N/A	N/A			
	e) Jockey pump head	N/A	N/A	N/A			
	f) Stand by pump output	N/A	N/A	N/A			
	g) Stand by pump head	N/A	N/A	N/A			
	h) Auto starting/Manual	N/A	N/A	N/A			
	stopping						
	2) Terrace level						

-	T	b) Head of pump	30	Mtr.	30 I	Mtr.	MR
		c) Power supply	Rec		Provided		MR
		d) Auto starting of pump	Required		Provided		MR
14.	d) Title states of Fig. 1.						
14.		1) Under ground tank capacity		N/A		N/A	N/A
	a) Draw-off connection			N/A		N/A	N/A
		b) Fire service inlet		N/A		N/A	N/A
		c) Access to tank		N/A		N/A	N/A
		d) Over head tank capacity		2,500 ltr	S.	2,500 ltrs.	MR
15.		Exit Signage.		Required	1	Provided	MR
16.							
	a) Pressurization of lift shaft			N/A		N/A	N/A
	b) Pressurization of lift lobby		N/A		N/A	N/A	
		c) Communication in lift car d) Fireman's switch		N/A		N/A	N/A
	1			N/A		N/A	N/A
	1	e) Lift signage		N/A		N/A	N/A
17.		tand by Power Supply		Required		Provided	MR
$\frac{17.}{18.}$				N/A		N/A	N/A
		Total area location		N/A		N/A	N/A
19.		Fire Control Room		N/A		N/A	N/A
	7	a) Detector system panel		N/A		N/A	N/A
		b) Flow switch panel		N/A		N/A	N/A
	NAME OF TAXABLE PARTY.	c) PA system panel		N/A		N/A	N/A
	1	d) Battery backup		N/A		N/A	N/A
		e) Building floor plan		N/A		N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:					N/A	

The fire protection system provided in the guest house were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/MS/DFS/GH/2013/07 dated 05/03/2013, renewal under Rule 35 of the Delhi Fire Service rules

2010, is recommended

Gurmukh Singh Divisional Officer

Dy CRO(HOZ)

CFI. M.

M. SCELL BITTO.

3/11/16/8/11