## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI **HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001**

No. F6/DFS/MS/Bangut 2016/ W2 /1792

Dated: 16/12/16

## FIRE SAFETY CERTIFICATE

Certified that the Apsara Grand Banquet Halls at A-1 /20-B, Paschim Vihar, Rohtak Road, New Delhi-110063 comprised of Basement, Ground & Two Upper Floor only owned/occupied by Apsara Grand Banquet Halls, has already been issued NOC / FSC by this department vide letter No. F6/DFS/MS/School/2013/444 dated 14.06.2013. The premises was re-inspected by the officer concerned of this department on 28.11.2016 in the presence of Sh. Sandeep Walia (Owner) and observed that Fire prevention and fire safety arrangements provided in the premises, found in good working condition. The premises have therefore, deemed complied with the Fire Prevention and Fire Safety Requirements in accordance with rule 33 of the Delhi Fire Service Rule 2010 and that a period of three years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS rules, 2010.

Issued on 6 12 116 at New Delhi by.

Alg. 0/c

Chief Fire Officer.

Copy to :-

1. Sh. Sandeep Walia, Apsara Grand Banquet Halls, A-1/20-B, Paschim Vihar, Rohtak Road, New Delhi-63.

## Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. Use of Basement shall be strictly as per Building By-Laws 1983.
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from available WWW.dfs.Delhigovt.nic.in
- 8. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

1110

## **INSPECTION REPORT**

1. Name & address of the building: Apsara Grand Banquet Halls

A-1/20-B, Paschim Vihar, Rohtak Road,

Plot Area = 326 M<sup>2</sup>

Covered Area=326 M<sup>2</sup>

Basement + Ground +
Two Upper Floors

New Delhi-63.

2. Type of Occupancy : Assembly

3. Type of Case : <u>Renewal</u>

4. Details of previous NOC : Letter No <u>F6/DFS/MS/2013/WZ/1240 dated 27/11/2013</u>

5. Fire Safety directives Letter No.: F.6/DFS/MS/2013/2004 dated 13.08.2013

6. Date of inspection : <u>28.11.2013</u>

7. Name of the Inspecting Officer: A.K. Jaiswal

8. Name and designation of Officer

from the building side : Sh. Sandeep Walia

9. Year of Construction : 2004

**10.** Applicant's letter No. : Nil dated 08.11.2016

S	Minim	um standards on fire	BBL/	Provi	ded at	Remarks MR/N	MR
No		tion and fire safety U/R 33	Requirements	site		remains wife with	
1.		of building	1 1				
	•	Road width	6 mtr	6 mtr		MR	
		Gate width	5 mtr	5 mtr		MR	
	•	Width of internal road	NA	NA		NA	
2.	Numbe	er, width, Type & Arrangeme	ents of exits				
		Number of staircases					
	•	Upper floors	2	2		MR	
	●	Basements	2	2		MR	
	· b.	Width of staircases					
	•	Upper floors	1.50 mtr	1.50	mtr	MR	
			V				
	•	Basements	1.50 mtr	1.50	mtr	MR	
	c.	Protection of exits					
		E A					_
	. •	Fire check door	Required		Provided	d	MR
	87						
	•	Pressurization	Required		Provided	d	MR
	,		4		1		NAD
	50	No of continuous staircase	1		1		MR
		to terrace	NA		NA		NA
	e.	Width Of Corridor	IVA	IVA			IVA
	f.	Door Size	2.00 mtr x 2 on ea	ch floor	2.00 mtr	x 2 on each floor	MR



14/17

			. //7				
3.	Compartmentation						
	• Fire check door	Required	Provided	MR			
	Sealing of electrical shafts	Required	Provided	MR			
	Fire Rating of shaft door	Required	Provided	MR			
	Water Curtain	NA	NA	NA	,		
	Fire Dampers	NA	NA	NA			
<del>1</del> .	Smoke managements System						
	Basements	30 a/c per hour	Exhaust fan	MR			
	• Upper floors	12 a/c per hour	Open to sky	MR			
5.	Fire Extinguishers						
	Total numbers	10	15	MR			
	• Types	ABC/Co2/Foam	Provided	MR			
	IS marking	ISI marked	Provided	MR			
, ),	First – Aid Hose Reels						
	Total numbers on each floor	1	1	MR			
	Length of hose reel hose	30 Mtr.	30 Mtr.	MR			
	Nozzle diameter	5 mm	5 mm	MR	2		
7.	Automatic fire detection and alarmi	ng system					
	Type of detector	Smoke	Provided	MR			
	Location of Main Panel	GF	Provided	MR			
	Location of Repeater Panel	GF	Provided	MR			
	Alternate source of power	Required	Provided	MR			
	Hooters' Location	GF	Provided	MR			
	MOEFA	Required	Provided	MR			
	Public Address System	NR	NR	NR			
0.	Automatic Sprinkler System						
	Basements	Required	Provided	MR			
	Upper Floor	Not Required	Not Provided	Not App	olicable		
	Sprinkler above false ceiling	Required (Only Basement)	Provided	MR			



N/18.

11.	Inte	rnal Hydrants						
e a		Size of riser/down-comer	100 mm	100 mm	MR			
	1.			Ser Ser				
	•	Number of hydrants per floor	1	1	MR	-		
			1	1	MR			
		Hose Box						
12.	Yard	l Hydrants						
		Total number of hydrants	NA	NA	NA			
	•	Hose Box	NA	NA	NA			
13.	Pum	ping Arrangements			· ·			
	• Gr	ound Level / Over Head	O.H. Tank					
	• Dis	scharge of main pump	2280 Lpm.	2280 Lpm.	MR			
	➤ He	ad of main pump	60 MH	60 MH	MR			
	> Nu	mber of main pumps	2	2	MR			
	> Joc	key pump out put	180 Lpm.	180 Lpm.	MR			
	> Joc	k <mark>ey pu</mark> mp head	60 MH	60 MH	MR			
7	Star	ndby Pump out put	2280 LPM	2280 LPM	NR			
7	Star	ndby Pump Head	60 MH	60 MH	NR			
2	Aut	o Staring/Manual stopping	Required	Provided	MR			
>	Pun	np House Access	Required	Provided	MR			
•	Terr	ace level		*				
>	> Disc	harge of pump	450 LPM	450 LPM	MR.			
>	Head	d of the pump	40 MH	40 MH	MR			
>	Pow	er supply	Required	Provided	MR			
>	Auto	starting of pump	Required	Provided	MR			
14.	Captiv	e water Storage for fire fighting	ng					
		Under Crown 1 T 1 C				**		
	<i>D</i>	Under Ground Tank Cap. Draw of connection	D					
*	<b>A</b>	Fire service inlet	Required	Provided	MR			
		Access to tank	Required	Provided	MR	3		
			Required	Provided	MR			
		Overhead Tank capacity	10,000 Ltr.	60,000 Ltr.*	MR			
			ARI					
			MA					

12)79

15	Exit Signage	Required	Provided	MR			
16.	Provision of Lifts						
10,	> Pressurization of Lift Shaft_	Required	Provided	MR			
	> Pressurization of lift lobby	Required	Provided	MR			
	Communication in lift Car	Required	Provided	MR			
	Fireman's Grounding Switch	Required	Provided	MR			
	➤ Lift Signage	Required	Provided	MR			
17.	Standby power supply	Required	Provided	MR			
18.	Refuge Area						
10.	> Total area	NA	NA	NA			
	> Location	NA	NA	NA			
19.	Fire control room						
17:	Detector system panel	NA	NA	NA			
	> Flow Switch Panel	NA	NA	NA			
	> PA System Panel	NA	NA	NA			
	> Battery backup	NA	NA	NA			
	> Building Floor Plans	NA	NA	NA			
20.	Special Fire Protection Systems for Protection of special Risks, if any;	NA	NA	NA			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter No. F6/DFS/MS/2013/WZ/1240 dated 27/11/2013 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

\*Note:- Management has provided 60,000 lts capacity Over Head Tank in place of 50,000 lts Under Ground Tank and 10,000 lts Over Head Tank. All the Pumps are installed on Terrace level.

Signature of the Inspecting Officer Name A-K. JATSWAL Designation A.D.O. (JW).)