GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6 / DFS / MS / 2016 / 1786

Dated: 6/12/2016

FIRE SAFETY CERTIFICATE

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.Delhigovt.nic.in

(Atul Garg) Chief Fire Officer Ph:-011-23414250

Copy to: -

1. The Director, Education, Government of N.C.T of Delhi. Old Sectt. Delhi - 54.

2. The Principal, Rao Mahar Chand Saraswati Vidya Mandir, Guru Nanak Nagar, Delhi-42.

INSPECTION REPORT

1. Name & address of the building

: Rao Mahar Chand Saraswati Vidya Mandir, Guru Nanak Nagar,

Delhi-42.

2. Type of Occupancy : Educational (G+01 Floors)

3. Type of Case : Renewal

Details of previous NOC 4.

 $: F6/DFS/MS/School/2013/WZ/898 - Dated: 10/09/2013(Ground \ Floor \ only)$

Fire Safety directives letter No 5.

: Director of Education Circular dated 01.03.2011

Date of inspection

: 30/11/2016

7. Name of the Inspecting Officers : ADO (RN)

Name and designation of officers

from the building side

: Mrs. Renu Vashistha (Principal)

9. Year of Construction

: 1994/2014

10. Applicant's letter No.

: SVM/Bh/11/2016-17/75 Dated-15/11/2016

lot Ai	rea-4 Acres Covered Area:1800 sq.yard	class rooms	-24 nos	students = 756nos	
	Minimum Standards on fire prevention and fire safety U/R 33	Circular of Director of Education	Provided at site	Remarks MI/NMR	
1	Access to building				
	Road width	6m	6m	MR	
	Gate width .	4.5m	4.8m	MR	
	Width of internal road	NA	NA	VI	
	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases				
	Upper Floors	02	02	MR	
	Basements	NA	: NA	NA.	
	b. Width of staircases				
	Upper Floors	1.50m	1.50m each	MR	
	Basements	NA	NA	V.1	
	c. Protection of exits				
	Fire check door	. NA	NA	NI	
	Pressurization	NA	NA	V	
	d. No. of continuous staircases to terrace	NA	NA	V /	
	e. Width of Corridor	NA	NA	NI	
	f. Door Size	1 m	1.12 m	\12	

MP

3	Compartmentation.				
	Fire check door	NA	NA	NA	
	 Sealing of electrical shafts 	NA	NA	NV	
	• Fire Rating of shaft door	NA	NA	NA	
	Water Curtain	NA	NA	NA	
	• Fire Dampers	NA	NA	VI	
	Smoke Management System.				
	Basements	30 a/c per hour	NA	NI	
	• Upper floors	12 a/c per hour	Natural Ventilated	MR	
	Fire Extinguishers				
	Total numbers	07nos	14nos	MR	
	• Types	ABC/CO2	ABC—14	MR	
	ISI marking	ISI Marked	Yes	MR	
	First-Aid Hose Reels.				
	Total numbers on each floor	NA	NA	NI	
274	Length of hose reel hose	NA	NA	V 1	
	Nozzle diameter	NA	NA	// /	
7	Automatic fire detection and alarming system.				
	Type of detectors	NA	NA	NA	
	Location of Main Panel	NA	NA	NA	
	 Location of Repeater Panel 	NA	NA	VA	
	Alternate source of power	NA	NA	VA	
	 Hooters' Location 	NA	NA	NV.	
8	MOEFA	NA	NA	. 1	
)	Public Address System.	NA	NA	NA	
10	Automatic Sprinkler System.				
	Basement	NA	NA	NA	
	Upper Floor	NA	NA	NA	
	Sprinkler above false ceiling	NA	NA	NA	



12/12

1 1	Internal Hydrants					
	Size of riser/down-comer	NA	NA	V		
	Number of hydrants per floor	NA	NΛ	7:7		
	Hose Box	NA	NA	NI.		
2	Yard Hydrants.					
	Total number of hydrants	NA	NA	N.		
	Hose Box	NA	NA	NA		
3	Pumping Arrangements.					
	Ground Level					
	Discharge of main Pump	N/A	N/A	V _I .A		
	➤ Head of Main pump					
	Number of main pumps	N/A	N/A	V, 1		
	Jockey Pump out put	N/A	N/A	VA		
	Jockey pump head	N/A	N/A	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		
	➤ Standby Pump out put	N/A	N/A	VγA		
	> Standby Pump Head	N/A	N/A	ν, Δ		
	Auto Starting/ Manual stoppingPump House Access .	N/A	N/A	N/A		
	Terrace level	N/A	N/A	V, A		
	Discharge of pump			.,		
	Head of the pump	NA	NA	V		
	➤ Power Supply	NA	NA	V V		
	Auto Starting of pump	N/A	NA	\\\ \\\\ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\		
		N/A	NA · · · ·	N, A		
4	Captive Water Storage for fire fighting.					
	Underground tank capacity	NA	NA	N.V		
	> Draw-off connection	NA	NA	V,		
	➤ Fire service inlet	NA	NA	VA		
	> Access to tank	NA	NA	V 1		
	Overhead Tank capacity	NA,	NA	N/		
5	Exit Signage.	N/A	N/A	_/ A		

1

12/12

16	Provision of Lifts.			4.
	Pressurization of Lift Shaft	N/A	N/A	V.1
	Pressurization of Lift lobby	N/A	N/A	V. A
	Communication In lift CarFireman's Grounding Switch	N/A	N/A	V, A
	• Lift Signage	N/A	N/A	V/A
7	C. II	N/A	N/A	\/\ \
	Standby power supply	N/A	N/A	V. 1
8	Refuge Area.			
	> Total Area	N/A	N/A	V.A
`	Location	N/A	N/A	\/ \/ \
)	Fire Control Room			
	Detector System Panel	N/A	N/A	N/A
	Flow Switch PanelPA System Panel	N/A	N/A	N/A
	Batter backup	N/A	N/A	Vi A
	Building Floor Plans	N/A	N/A	V/ \
	Carrie I I'm D	N/A	N/A	7,1
	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	ν, Α

Accordingly, the fire protection systems provided in the building were tested/ checked random; and found in working condition at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevent on and fire safety required as stipulated in Director of Education Circular dated 17.01.2005 the FSC issted vide letter of even no 898 dated 10.09.2013 renewal under rule 35 of the Delhi Fire Service Rules, 2010 is recommended

> Signature of the Inspecting Office Name: - Rajesh Kumar

Designation:- ADO/RN

Jour signature P/ //