GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2016/ MD2/1811

Dated: 22 / 11 / 16

FIRE SAFETY CERTIFICATE

Certified that the Ahuja Residency located at 3, Sunder Nagar, New Delhi comprised of Basement (Storage), Ground floor (08 guest room + reception), Mezzanine floor (04 guest rooms), 1st floor (08 guest rooms), 2nd floor (02 guest rooms) and Barsati floor (02 guest rooms) total 24 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2013/NDZ/1338 dated 24/12/13. The premises was re-inspected by the officer concerned of this department on 01/12/16 in the presence of Sh. Avinash (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 24 guest rooms only with effect from 22-111-16-------- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 22 41-16---at New Delhi by.

491/2

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter No. 2623/Joint C.P./Lic. (H) dated 16/09/2016.
- 2. The Manager, Ahuja Residency located at 3, Sunder Nagar, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

- H122

INSPECTION	REPORT
------------	--------

1. Name & address of the building

Ahuja Residency located at 3, Sunder
Nagar, New Delhi
Basement (Storage), Ground floor (08 guest
room + reception), Mezzanine floor (04 guest

room + reception), Mezzanine floor (04 guest rooms), 1st floor (08 guest rooms), 2nd floor (02 guest rooms) and Barsati floor (02 guest rooms)

total 24 guest rooms

3. Type of case:- Renewal

4. Details of previous FSC:- No. F6/DFS/MS/GH/2013/NDZ/1338 dated 24/12/13.

5. Fire safety directives No.N/A
Date of inspection:-

6. Date of inspection:- 01/12/167. Name of the inspecting officer:- Sh. Man

8. Name & designation of officer

From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Sh. Manoj Kumar Sharma (ADO/CC)

Sh. Avinash (Manager) 1981

2623/Joint C.P./Lic. (H) dated 16/09/2016.

S.No.	Minimum Standards on fire Requirement/ Provided at site Remarks				
	Prevention and fire safety	Existing fire	Provided at site		
	U/R 33	safety		MR/NMR	
		arrangements		•	
1.	Access to Building	- January Children	1		
1	1) Road width	N/A	12 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
×	3) Width of internal road	N/A	N/A	N/A	
	Number, Width Type & Ar	rangement of E	vits	IN/A	
	A. Number of staircases	1 (4 -	11103		
	1. Upper floors	02 Nos.	02 Nos.	MR	
	2. Basements	01 Nos.	01 Nos.	MR	
	B. Width of staircase		011105.	IVIIC	
	1. Upper floors	0.80 mtr.	1.04 mtr. & 0.80 Mtr.	MR	
	2. Basements	0.80 mtr.	1.04 Mtr.	MR	
	C. Protection of exits	4		TVIIC	
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
-	D. No. of continuous staircase to terrace	01	01	MR	
	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	01 mtr.	01 mtr.	MR	
	Compartmentation		or mu.	IVIIC	
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
	Smoke Management System	•		1.071	
	1) Basements	30 ACPH	Provided	MR	
	2) Upper floors	12 a/c per hour		MR	

- M23-

5.	Fire Extinguishers			
	1) Total numbers	10	12	MD
	2) Types	ABC & CO2		MR
	3) ISI marking	Required	Provided Provided	MR
6.	First-Aid Hose Reel	required	TTOVIGEG	MR
	1) Total number of eachfloor	Required	Provided	1.00
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR
	3) Nozzle diameter	05 mm	05 mm	MR
7.	Automatic Fire Detection &	Alexaning Care	05 mm	MR
-,	1) Type of detectors			
	2) Location of main panel	N/A N/A	N/A	N/A
	3) Location of repeater panel	N/A	N/A	N/A
	4) Alternate source of power	N/A N/A	N/A	N/A
	5) Hooter's Location		N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.		N/A	Provided	N/A
10.	Public Address System	N/A	N/A	N/A
10.	Automatic Sprinkler System 1) Basement			-
		N/A	N/A	N/A
	2) Upper floors	N/A	N/A	N/A
	3) Sprinkler above false	N/A	N/A	N/A
11	ceiling			
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A	N/A	N/A
	2) Number of hydrants per	N/A	N/A	N/A
	floor			1011
10	3) Hose box	N/A	N/A	N/A
12.	Yard Hydrants			1 - 11 - 1
	1) Total number of hydrants	N/A	N/A	N/A
	2) Hose box	N/A	N/A	N/A
3.	Pumping Arrangement			14/21
	1) Ground level	N/A	N/A	N/A
	a) Discharge of main	N/A	N/A	N/A N/A
	pump		1771	IN/A
	b) Head of main pump	N/A	N/A	N/A
	c) Number of main pump	N/A	N/A	
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
	f) Stand by pump output	N/A	N/A	N/A
	g) Stand by pump head	N/A	N/A	N/A
	h) Auto starting/Manual	N/A	N/A	N/A
	stopping	14/11	IN/A	N/A
	2) Terrace level		**************************************	
	a) Discharge of pump	450 LPM	450 I DM) (D
	b) Head of pump	30 mtr.	450 LPM	MR
	c) Power supply		30 mtr.	MR
	d) Auto starting of pump		Provided	MR
	Captive Water Storage for Fir	Required	Provided	MR
			77/	
	capacity	N/A	N/A	N/A
		NIA		
	a) Diaw-oil connection	N/A	N/A	N/A

-11/24-

	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
•	d) Over head tank capacity	5,000 ltr.	5,000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	1		1,111
_	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
1	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
1,0	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risk, if any:			NA

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2013/NDZ/1338 dated 24/12/13 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

Messe

DO(CD)

16 Rolls Dy CRO

6/17/16 (RO(XDZ) 1)

FTM.

M-SOUT 8/12