GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS : DELHI FIRE SERVICE : NEW DELHI – 110001

No.F6/DFS/MS/EH/2016/ NOZ/1809

Dated: 22/12/16-

FIRE SAFETY CERTIFICATE

Certified that the M/S Darzi Bar (A Unit of Radioactive Hospitality Pvt. Ltd.) located at H-55, H-89, 1st & 2nd floor, Cannaught Place, New Delhi building comprised of Ground + 2 Upper Floors and Restaurant is running at 1st floor & 2nd floor only owned /occupied by M/S Darzi Bar (A Unit of Radioactive Hospitality Pvt. Ltd.), has complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Delhi Fire Service on 02/12/2016 in the presence of Sh. Abhishk (Partner) and that the building / premises, is fit for occupancy class Assembly Building Group D, Restaurant is running at 1st floor & 2nd floor only with effect from 2-1/2-1/6-for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

Copy to:-

1. The Medical Officer of Health, NDMC, Palika Kendre, New Delhi.

The Manager,
 M/S Darzi Bar (A Unit of Radioactive Hospitality Pvt. Ltd.)
 H-55, H-89, 1st & 2nd floor, Cannaught Place, New Delhi.

Condition for the validity of fire safety certificate

1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.

2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.

5. This fire safety certificate may not be treated in any case for regularization of

unauthorized construction, if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in

7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in

case of an emergency.

8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT 1. Name & address of the building:- M/S Darzi Bar (A Unit of Radioactive Hospitality Pvt. Ltd.) H-55, H-89, 1st & 2nd floor, Cannaught Place, New Delhi. 2. Type of occupancy:-Group - D Assembly Building Gr. + 2 upper floor (Restaurant at 1st floor & 2nd floor only) 3. Type of case:-New Case 4. Details of previous FSC:-N/A 5. Fire safety directives No.-N/A 6. Date of inspection:-02/12/16 7. Name of the inspecting officer:-Sh. Sunil Chaudhary Dy. CFO/NDZ, Sh. G.S. Chauhan DO/CD & Sh. Manoj Kumar Sharma ADO/CC

8. Name & designation of officer From the building side:-

From the building side:9. Year of construction:-

10. Applicant's letter No:-

Sh. Abhishk (Partner)

Pre. 1983

Nil dated 03/11/16.

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement BBL / NBC Part - VI	Provided at site	Remarks MR/NMR	
1.	Access to Building		1 - 11-		
	1) Road width	09 mtr.	18 mtr.	MR	
	2) Gate width	N/A	N/A	N/A	
15	3) Width of internal road	N/A	N/A	N/A	
2.	Number, Width Type & Ar	rangement of F	Exits	IVA	
	A. Number of staircases			× .	
	1. Upper floors	02 Nos.	02 Nos.	MR	
	2. Basements	N/A	N/A	N/A	
	B. Width of staircase			14/14	
	1. Upper floors	0.80 & 1.5 mtr.	1.50 mtr. & 0.90 mtr.	MR	
	2. Basements	N/A	N/A	N/A	
	C. Protection of exits		1011	IVA	
	1. Fire check door	N/A	N/A	N/A	
	2. Pressurization	N/A	N/A	N/A	
	D. No. of continuous staircase to terrace	N/A	N/A	N/A	
1	E. Width of corridor	N/A	N/A	N/A	
	F. Door size	1X2.mtr & 1 mtr.	1X2.mtr & 1 mtr.	MR	
	Compartmentation				
	1) Fire check door	N/A	N/A	N/A	
	2) Sealing of electrical shafts	N/A	N/A	N/A	
	3) Fire rating of shaft door	N/A	N/A	N/A	
	4) Water curtain	N/A	N/A	N/A	
	5) Fire Dampers	N/A	N/A	N/A	
	Smoke Management System				
	1) Basements	N/A	N/A	N/A	
	2) Upper floors	12 a/c per		MR	

5.	Fire Extinguishers	· · · · · · · · · · · · · · · · · · ·	1			
	1) Total numbers	05 Nos.	07 Nos.	MR		
	2) Types	ABC & CO2	ABC & CO2	MR		
	3) ISI marking	ISI	Provided	MR		
6.	First-Aid Hose Reel					
	1) Total number	01	01	MR		
	2) Length of hose reel hose	30 m	30 m	MR		
	3) Nozzle diameter	5 mm	5 mm	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	N/A	N/A	N/A		
10.	Automatic Sprinkler System					
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling		`	4		
11.	Internal Hydrants	,				
	1) Size of riser/down-comer	100 mm	100 mm	MR		
	2) Number of hydrants per	01	01	MR		
	floor					
	3) Hose box	01	01	MR		
12.	Yard Hydrants		Tari			
	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement	-				
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main	N/A	N/A	N/A		
	pump	77/4	NT/A	DI/A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump	N/A	N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	g) Stand by pump head	N/A N/A	N/A N/A	N/A N/A		
	h) Auto starting/Manual stopping	IN/A	IN/A	IN/A		
	2) Terrace level	 				
		450 LPM	450 LPM	MR		
	a) Discharge of pumpb) Head of pump	30 mtr.	30 mtr.	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided	MR		
	d) Auto starting of pump	Required	Fiovided	IVIIX		
14.	Captive Water Storage for Fi	re Fighting				
17.	1) Under ground tank	N/A	N/A	N/A		
	capacity	1 1/1 1	1.1/1.1	14/11		
	capacity			4		

	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	10,000 ltrs.	10,000 ltrs.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.		•	
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste Risk, if any:	m for Protecti	on of special	N/A

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/2016/2380 dated 06/10/2016 have been rectified.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules, grant of fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 / is recommended please.

Signature of the Inspecting Officer Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name :- Sh. Sunil Chaudhary Designation: - DCFO (NDZ)

Name :- G.S Chauhan

Designation: - DO (CD)

Name: - M.K. Sharma

Designation: - ADO (CC)