FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI

HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE, NEW DELHI

No. FG | DF3 | MS 2016 1829

Dated: 23. 12. 2016

FIRE SAFETY CERTIFICATE

Certified that the **Delhi Metro Rail Corporation** located at **Moti Nagar Metro Station** (Except PD area) comprised of Ground, Concourse and Platform was issued FSC vide letter no. **F.6/DFS/MS/2014/WZ/134 dated 30/01/2014.** The premises was re inspected by the officer concerned of this department on **05-12-2016** in the presence of **Mr Kumar Waibhav** (AM/Fire) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the building / premises is fit for the occupancy class "Assembly" Group D Sub Division D – 7 with effect from **23.12.2016**. for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 23:12.2016. at New Delhi by.

(Atur Garg)

Chief Fire Officer,

Qelhi Fire Service.

Copy to:

1. Mr Kumar Waibhay (AM/Fire), DMRC, Metro Bhawan, Fire Brigade Lane, Barakhamba Road, New Delhi – 110001.

Following fire safety directives must be adhered to:-

1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.

2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.

3. The trained staff should be available round the clock.

4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.

5. The basement shall be used as per building bye laws 1983.

6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.

7. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

9. All the exit/passage must not be kept under lock and key & kept free from any obstruction.

INSPECTION REPORT

1. Name & address of the building: Moti Nagar Metro Station (Except PD area)

2. Type of Occupancy : Assembly

3. Type of Case : Renewal (Ground + Concourse + Platform)

4. Details of previous NOC : F.6/DFS/MS/2014/WZ/134 dated 30/01/2014

5. Fire Safety directives Letter No.: F6/DFS/MS/BP/2004/2282 dated 01-10-2004

6. Date of inspection : 05/12/2016

7. Name of the Inspecting Officer: Udai Vir Singh ADO (WP)

8. Name and designation of Officer

from the building side : Mr Kumar Waibhav (AM/Fire)

9. Year of Construction : 2005

10. Applicant's letter No. : DMRC/O&M/Fire/NOC/L-3/2016/50 dated 23-11-16

S No	Minimum standards on fire prevention and fire safety U/R 33	NBC Requirements	Provided at site	Remarks MR/NMR				
1.	Access of building							
	Road width	On main road	Provided	MR				
	Gate width	5m	On main road	MR				
	• Width of internal road	NA	NA	NA				
2.	Number, width, Type & Arrangem	ents of exits						
	a. Number of staircases							
	• Upper floors	2	Provided	MR				
	Basements	NA	NA	NA				
	b. Width of staircases							
	Upper floors	1.5 mtr	2x460 cm each plat	MR being old				
			form	case				
	 Basements 	NA	NA	NA				
	c. Protection of exits							
	Fire check door	NA	NA	NA				
	 Pressurization 	NA	NA	NA				
	d. No of continuous	NA	NA	NA				
	staircase to terrace	Old Case	Old Case	Old Case				
	e. Width Of Corridor	2 mtr	2 mtr provided	MR				
2	f. Door Size	2 11111	2 mii provided	IVIIX				
3.	Compartmentation	D 1						
	Fire check door	Required	Provided	MR				
	 Sealing of electrical shafts 	Required	Provided	MR				
	 Fire Rating of shaft door 	Required	Provided	MR				
	 Water Curtain 	NA	NA	NA				
	• Fire Dampers	NA	NA	NA				
4.	Smoke managements System							
	• Basements	NA	NA	NA				
	• Upper floors	NA	NA	NA				
5.	Fire Extinguishers							
	 Total numbers 	35	28 CO2, 7 WCO2	MR				
	 Types 	CO2 & WCO2	Provided	MR				
-	• IS marking	Required	Provided	MR				

7.	Autor	Type of detectors		noke		Provided		MR
		Location of Main Panel		equired		Provided		MR
		Location of Repeater		equired		Provided		MR
1		Panel		equired		Provided		MR
	•	Alternate source of power						
	•	Hooters' Location	Required			Provided		MR
8.	MOE	FA	Required			Provided		MR
9.	Public	Address System	Re	equired		Provided		MR
10.	Automatic Sprinkler System							
	•	Basements	N	4		NA		NA
	•	Upper Floor	N	Λ		NA		NA
	•	Sprinkler above false	NA			NA		NA
		ceiling						
11.	Internal Hydrants							
	•	Size of riser/down- comer		50mm		Provided		MR
	0	Number of hydrants per	3			Provided		MR
		floor	R	equired		Provided		MR
		Hose Box						
12.	2. Yard Hydrants							
		Total number of hydrants		2		Provided		MR
		Hose Box		Required		Provided		MR
13.	Pumpi	ng Arrangements		required		110 / 1000		TVIIC
	Ground Level All the pumps are connected with generator also, O							
	. 1		water storage tank and overhead pumps of same					
	l sak	is boiled on the second of the second				ided in place of		
	•	Discharge of main pump		1800 lpm		Provided		MR
	>	Head of main pump		60m		Provided	10	MR
	>	Number of main pumps		1		Provided		MR
	>	Jockey pump out put		180 lpm		Provided		MR
	1	Jockey pump head		60m		Provided		MR
	7	Standby Pump out put		1800 lpm		Provided		MR
	>	Standby Pump Head	. 90	60m		Provided	1	MR
	A A	Auto Staring/Manual stopping Pump House Access	ıg	Required		Provided		MR
		Terrace level		Required		Provided		MR
	>	Discharge of pump		NA		2X1800 lpm,		NA
		Head of the pump		7.7.1		1X180 lpm		
		Power supply		NA		60m each		NA
		Auto starting of pump		NA	-	Provided		NA
14.		e water Storage for fire fighting	no	NA		NA		NA
A 7,	Captiv	Under ground tank capacity	ng	50000 ltrs		Provided		MR
		Draw of connection		Required		Provided		MR
	A	Fire service inlet		Required		Provided		MR
		Access to tank		Required		Provided		MR
	•	Overhead Tank capacity		NA		50000ltrs		MR
15	Exit Si	gnage		Required		Provided		MR
16.		on of Lifts		*				
	>	Pressurization of Lift Shaft		NA		NA		NA
		Pressurization of lift lobby		NA		NA		NA
	>	Communication in lift Car		Required		Provided		MR
	A	Fireman's Grounding Switch	i	Required		Provided		MR
		Lift Signage		Required		Provided		MR
17.	Standb	y power supply		Required		Provided		MR

9	Refuge Area			
	Total area	NA	NA	NA
	> Location	NA	NA	NA
19.	Fire control room			
	Detector system panel	Required	Provided	MR
	Flow Switch Panel	NA	NA	NA
	> PA System Panel	Required	Provided	MR
	Battery backup	Required	Provided	MR
	Building Floor Plans	NA	NA	NA
20.	Special Fire Protection Systems for	CO2 flooding	Provided	MR
	Protection of special Risks, if any;	for ASS, HT,		
		LT panel		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F.6/DFS/MS/2014/WZ/134 dated 30/01/2014 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name Udai Vir Singh

Name

Designation ADO (WP)

Designation

Dolla Junder 2/10/16