GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2016/ M02 (82)

Dated: 23 12/16

FIRE SAFETY CERTIFICATE

Certified that the K. K. Guest House located at 3438, Dariba Pan, Panar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (04 guest rooms + reception + 01 store room), 1st floor (05 guest rooms + 01 store room), 2nd floor (06 guest rooms + 01 store room) and 3rd floor (02 staff rooms) total 15 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2013/NDZ/1245 dated 28/11/13. The premises was re-inspected by the officer concerned of this department on 15/12/16 in the presence of Sh. Gulshan Kumar (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 15 guest rooms only with effect from -2-3-1-1-1-6 for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued 23 1-10416-at New Delhi by.

(Vipin Kental)
Chief Fire Officer
Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 2677/Joint C.P./Lic (H) dated 19/09/16.
- The Manager,
 K. K. Guest House located at 3438, Dariba Pan, Panar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

		INSPECTION REPORT

1. Name & address of the building K. K. Guest House located at 3438, Dariba

Pan, Panar Ganj, New Delhi

Gr. + 03 Upper floors (total 15 Guest rooms) Ground floor (04 guest rooms + reception + 01 store room), 1st floor (05 guest rooms + 01 store room), 2nd floor (06 guest rooms + 01 store room) and 3rd floor (02 staff rooms)

3. Type of case:-

4. Details of previous FSC:-

Renewal

No. F6/DFS/MS/GH/2013/NDZ/1245 dated

28/11/13. N/A

5. Fire safety directives No.-

6. Date of inspection:-

15/12/16

7. Name of the inspecting officer:-8. Name & designation of officer

Sh. Manoj Kumar Sharma (ADO/CC)

From the building side:-

9. Year of construction:-10. Applicant's letter No:-

Sh. Gulshan Kumar (Manager) 2001

2677/Joint C.P./Lic. (H) dated 19/09/2016.

C 3.1				Old Case				
S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement/ Existing fire safety arrangements	Provided at site	Remarks MR/NMR				
1.	Access to Building	arrangements						
	1) Road width	N/A	06 mtr.	N/A				
	2) Gate width	N/A	N/A	N/A				
	3)Width of internal road	N/A	N/A	N/A				
2.	Number, Width Type & Ar	11/11						
	A. Number of staircases		0					
	1. Upper floors	01 Nos.	01 Nos.	MR				
	2. Basements	N/A	N/A	N/A				
	B. Width of staircase			2				
	1. Upper floors	0.80 mtr.	0.80 Mtr.	MR				
	2. Basements	N/A	N/A	N/A				
	C. Protection of exits							
	1. Fire check door	N/A	N/A	N/A				
	2. Pressurization	N/A	N/A	N/A				
	D. No. of continuous	01	01	MR				
	staircase to terrace		*	у в				
	E. Width of corridor	1.25 mtr.	1.50 mtr.	MR				
	F. Door size	01 mtr.	01 mtr.	MR				
3.	Compartmentation							
	1) Fire check door	N/A	N/A	N/A				
	2) Sealing of electrical shafts	N/A	N/A	N/A				
-	3) Fire rating of shaft door	N/A	N/A	N/A				
	4) Water curtain	N/A	N/A	N/A				
	5) Fire Dampers	N/A	N/A	N/A				
4.	Smoke Management System							
	1) Basements	30 ACPH	N/A	N/A				
	2) Upper floors	12 ACPH	Natural	MR				
5.	Fire Extinguishers							
	1) Total numbers	10	10	MR				
	2) Types	ABC & CO2	ABC & CO2	MR				
	3) ISI marking	Required	Provided	MR				

First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter Automatic Fire Detection & A 1) Type of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per 1) Hose box Yard Hydrants	01 30 mtr. 05 mm Alarming Sys N/A	01 30 mtr. 05 mm stem N/A N/A N/A N/A N/A Provided Provided N/A N/A N/A N/A N/A N/A N/A N/	MR MR MR N/A
2) Length of hose reel hose 3) Nozzle diameter Automatic Fire Detection & All Type of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per Toor 3) Hose box	05 mm Alarming Sys N/A N/A N/A N/A N/A N/A NR NR NR N/A N/A N/A N/A N/A N/A N/A	05 mm Stem N/A N/A N/A N/A N/A Provided Provided N/A N/A N/A N/A N/A N/A N/A	MR MR N/A N/A N/A N/A N/A N/A N/A MR MR MR N/A N/A N/A N/A N/A N/A
Automatic Fire Detection & Automatic Solution of main panel Automatic Solution MOEFA Public Address System Automatic Sprinkler System Basement Dupper floors Solution Sprinkler above false Seciling Internal Hydrants Solution Size of riser/down-comer Number of hydrants per Gloor Solution Hose box	05 mm Alarming Sys N/A N/A N/A N/A N/A N/A NR NR NR N/A N/A N/A N/A N/A N/A N/A	05 mm Stem N/A N/A N/A N/A N/A Provided Provided N/A N/A N/A N/A N/A N/A N/A	N/A
Automatic Fire Detection & Automatic Fire Detection & Automatic Fire Detection & Automatic Fire Detection & Detection of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false 2) Sprinkler above false 3) Sprinkler above false 3) Size of riser/down-comer 2) Number of hydrants per 3) Hose box	N/A	N/A N/A N/A N/A N/A N/A N/A Provided Provided N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A N/A MR MR MR N/A N/A N/A N/A N/A
1) Type of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per Toor 3) Hose box	N/A N/A N/A N/A N/A NR NR NR N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A Provided Provided N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A MR MR MR N/A N/A N/A N/A N/A
2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per Cloor 3) Hose box	N/A N/A N/A NR NR N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A Provided Provided N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A MR MR MR N/A N/A N/A N/A N/A
3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box	N/A N/A NR NR N/A N/A N/A N/A N/A	N/A N/A N/A Provided Provided N/A N/A N/A N/A N/A	N/A N/A N/A N/A MR MR N/A N/A N/A N/A N/A
4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per Cloor 3) Hose box	N/A N/A NR NR N/A N/A N/A N/A N/A	N/A N/A Provided Provided N/A N/A N/A N/A N/A	N/A N/A MR MR N/A N/A N/A N/A N/A N/A
MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per Iloor 3) Hose box	N/A NR NR N/A N/A N/A N/A N/A	N/A Provided Provided N/A N/A N/A N/A N/A	N/A MR MR N/A N/A N/A N/A N/A
MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box	NR NR N/A N/A N/A N/A N/A	Provided Provided N/A N/A N/A N/A N/A	MR MR N/A N/A N/A N/A N/A
Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false reiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per Toor 3) Hose box	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A
Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box	N/A N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A
1) Basement 2) Upper floors 3) Sprinkler above false ceiling (Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box	N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A
2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box	N/A N/A N/A	N/A N/A N/A N/A	N/A N/A N/A N/A
3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per Iloor 3) Hose box	N/A N/A N/A	N/A N/A N/A	N/A N/A N/A
Internal Hydrants Size of riser/down-comer Number of hydrants per Toor Hose box	N/A N/A	N/A N/A	N/A N/A
Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per 1000r 3) Hose box	N/A	N/A	N/A
1) Size of riser/down-comer 2) Number of hydrants per cloor 3) Hose box	N/A	N/A	N/A
2) Number of hydrants per loor 3) Hose box	N/A	N/A	N/A
loor B) Hose box	TOOL TOOLS AND TO		
	N/A	NI/A	
		I IN/ A	N/A
laiu fivurants		11/12	1472
Total number of hydrants	N/A	N/A	N/A
			N/A
			1,111
	N/A	N/A	N/A
			N/A
	1 11 1	1771	17/11
b) Head of main pump	N/A	N/A	N/A
c) Number of main pump			N/A
2) Terrace level			
	220 LPM	220 LPM	MR
	+		MR
			MR
	-		MR
	1		
1) Under ground tank	N/A	N/A	N/A
	27/4		
			N/A
,			N/A
		N/A	N/A
	2500 ltr.	5000 ltr.	MR
	Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump b) Head of pump c) Power supply d) Auto starting of pump Captive Water Storage for Fi 1) Under ground tank capacity a) Draw-off connection b) Fire service inlet c) Access to tank	Pumping Arrangement 1) Ground level N/A a) Discharge of main pump b) Head of main pump N/A c) Number of main pump N/A d) Jockey pump out put N/A e) Jockey pump head N/A f) Stand by pump output N/A g) Stand by pump head N/A h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump 220 LPM b) Head of pump 30 mtr. c) Power supply Required d) Auto starting of pump Required Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A b) Fire service inlet N/A c) Access to tank d) Over head tank 2500 ltr.	Pumping Arrangement 1) Ground level N/A N/A a) Discharge of main pump N/A N/A b) Head of main pump N/A N/A c) Number of main pump N/A N/A d) Jockey pump out put N/A N/A e) Jockey pump head N/A N/A f) Stand by pump output N/A N/A g) Stand by pump head N/A N/A h) Auto starting/Manual stopping 2) Terrace level a) Discharge of pump 220 LPM 220 LPM b) Head of pump 30 mtr. 30 mtr. c) Power supply Required Provided d) Auto starting of pump Required Provided Captive Water Storage for Fire Fighting 1) Under ground tank capacity a) Draw-off connection N/A N/A b) Fire service inlet N/A N/A c) Access to tank N/A N/A d) Over head tank 2500 ltr. 5000 ltr.

17/2/-

_	E '4 Cianaga	Required	Provided	MR
5.	Exit Signage. Provision of Lifts.			
16.	a) Pressurization of lift	N/A	N/A	N/A
	shaft b) Pressurization of lift	N/A	N/A	N/A
	c) Communication in	N/A	N/A	N/A
	lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	N/A	N/A	N/A
	Refuge Area Total area location	N/A	N/A	N/A
	C tral Doom	N/A	N/A	N/A
19.	a) Detector system	N/A	N/A	N/A
	panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Sy Risk, if any: ABC, Co ₂	stem for Prote	ection of special	MR

The fire protection systems provided in the building were randomly tested, checked

and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2013/NDZ/1245 dated 28/11/13 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)