GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2016/ MOZ/1824

Dated: 23 12/16

FIRE SAFETY CERTIFICATE

Certified that the Rishi Guest House located at 76-76A (Municipal No. 7764-7765), Ram Nagar, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (04 guest rooms + reception), 1st floor to 3rd floor (08 guest rooms at each floor), total 28 **FSC** granted by this department rooms was No.F6/DFS/MS/GH/2013/NDZ/1217 dated 21/11/13. The premises was re-inspected by the officer concerned of this department on 10/12/16 in the presence of Sh. Shiv Kumar (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 28 guest rooms only with effect from -2-3-++2-1-6---- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -23/12/16-at New Delhi by.

K23/12

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 3689/Joint C.P. /Lic. (H) dated 21/10/16.
- 2. The Manager, Rishi Guest House at 76-76A (Municipal No. 7764-7765), Ram Nagar, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

IN	JCI	DE	CT	ION	P	EPC	RT	
11	ICI			VIV	1/			

1. Name & address of the building Rishi Guest House located at 76-76A

(Municipal No. 7764-7765), Ram Nagar,

Pahar Ganj, New Delhi.

Gr. + 03 Upper floors (total 28 Guest rooms) Ground floor (04 guest rooms + reception), 1st floor to 3rd floor (08 guest rooms at each floor).

3. Type of case:-

4. Details of previous FSC:-No. F6/DFS/MS/GH/2013/NDZ/1217 dated

21/11/13.

5. Fire safety directives No.-

N/A

6. Date of inspection:-

10//12/16

7. Name of the inspecting officer:-

Sh. Manoj Kumar Sharma (ADO/CC)

8. Name & designation of officer

From the building side:-

Sh. Shiv Kumar (Manager) 1986

9. Year of construction:-

10. Applicant's letter No:-

3689/Joint C.P. /Lic. (H) dated 21/10/16.

Old Case

S.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks		
3.1 (0.	Prevention and fire safety	Existing fire		MR/NMR		
	U/R 33	safety				
		arrangements	40			
1.	Access to Building					
	1) Road width	N/A	05 mtr.	N/A		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arr	angement of Ex	kits			
	A. Number of staircases	•				
	1. Upper floors	01 Nos.	01 Nos.	MR		
	2. Basements	N/A	N/A	N/A		
	B. Width of staircase					
	1. Upper floors	0.80 mtr.	1.0 Mtr.	MR		
	2. Basements	N/A	N/A	N/A		
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	01	01	MR		
	staircase to terrace					
	E. Width of corridor	1.20 mtr.	1.25 mtr.	N/A		
¥I	F. Door size	01 mtr.	01 mtr.	MR		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
	4) Water curtain	N/A	N/A	N/A		
	5) Fire Dampers	N/A	N/A	N/A		
4.	Smoke Management System					
	1) Basements	30 ACPH	N/A	N/A		
	2) Upper floors	12 a/c per	Natural	MR		
		hour				

1	1	0
1	1	1

5.	Fire Extinguishers					
	1) Total numbers	06	08	MR		
	2) Types	ABC & CO2	ABC & CO2	MR		
	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel					
	1) Total number of eachfloor	01	01	MR		
	2) Length of hose reel hose	30 mtr.	30 mtr.	MR		
	3) Nozzle diameter	05 mm	05 mm	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	N/A	N/A	N/A		
10.	Automatic Sprinkler System					
10.	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
	ceiling	17/15				
11.	Internal Hydrants					
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor	1 1/11	1 1/11	1 11 1		
	3) Hose box	N/A	N/A	N/A		
12.	Yard Hydrants	11/12	12.022			
14.	1) Total number of hydrants	N/A	N/A	N/A		
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement					
15.	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main	N/A	N/A	N/A		
	pump	11/12	1 1/1 1	A 11/2 A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump		N/A	N/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A	N/A		
	f) Stand by pump output	N/A	N/A	N/A		
		N/A	N/A	N/A		
	g) Stand by pump head h) Auto starting/Manual	N/A	N/A	N/A		
	stopping	1 1/1/1	14/17	1 1/2 2		
	2) Terrace level	+				
	a) Discharge of pump	450 LPM	450 LPM	MR		
		30 mtr.	30 mtr.	MR		
	* * *	Required	Provided Provided	MR		
	11 1		Provided	MR		
	d) Auto starting of pump	Required	FIOVIDED	IVII		

m

14.	Captive Water Storage for	Fire Fighting		
	1) Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	5000 ltr.	5000 ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			1711
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
1.77	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	· N/A
20.	Special Fire Protection Systel Risk, if any: ABC, Co ₂	m for Protect	ion of special	MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2013/NDZ/1217 dated 21/11/13 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

DO(eD)

434500