GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2017/ ND2/42

FIRE SAFETY CERTIFICATE

Certified that the Only Suites (A Unit of Alankar Merchandise Pvt. Ltd.) located at 61/36, Nova Hospital, New Rohtak Road, New Delhi-110005 comprised of Basement, Stilt, Ground + 3 Upper Floors, Basement - storage, stilt - reception + office + parking, Ground floor - restaurant & 1st to 3rd floor 06 guest rooms at each floor total 18 rooms granted **FSC** by this department No.F6/DFS/MS/GH/2013/NDZ/240 dated 18.02.2014. The premises was re-inspected by the officer concerned of this department on 23/12/16 in the presence of Mr. Suman Singh found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy of class Residential Group -A-1' for total 18 guest rooms only unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010. mentioned below.

471

(Vipin Kental) Chief Fire Officer Delhi Fire Service Ph: - 011-23412225

Copy to:-

1

1. The Joint. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi

The Licensee,
 Only Suites (A Unit of Alankar Merchandise Pvt. Ltd.),
 61/36,Opp. Nova Hospital,New Rohtak Road,New Delhi-110005.

Condition:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. The means of escape shall be kept unobstructed / unlocked & remain available for speedy evacuation of occupants in case of an emergency.
- 3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 4. The trained fire fighting staff should be available round the clock.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

	INS	PECTION REPO	RT			
1.]	Name & address of the building		(A Unit of Alanka	r Merchandise		
	o was established the communication of the communic		1/36,Opp. Nova Ho			
			id,New Delhi-1100			
2.	Type of occupancy:-		Group A-1 Basem			
	T	,Ground	Group II I Busen	10111,51111		
		S CONTROL CONTROL	Floors.(18 guest roo	ms) Basement		
		 storage, stilt - 	- reception + office +	parking, Ground		
		floor – restau	rant & 1 st to 3 rd floor 0	6 guest rooms at		
3	Type of case:-	each floor . Renewal				
	Details of previous FSC:-		/MS/GH/2014/ND	7/240 datad		
	Details of previous 1 ge	18/02/2014.	/1V15/011/2014/1VD	Z/240 dated		
5.	Fire safety directives No	N/A				
	Date of inspection:-	23/12/16				
	Name of the inspecting officer		ıkh Singh			
	Name & designation of officer					
	From the building side:-	Mr. Suman	Singh.			
9.	Year of construction:-	2012-13	C			
10.	Applicant's letter No:-	3952/Joint.	C.P.Lic (H) Dated	15/11/16		
2				Old Case		
S.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks		
	Prevention and fire safety	Existing fire		MR/NMR		
	U/R 33	safety				
		measures				
•	Access to Building					
	1) Road width	N/A	9 Mtr.	MR		
	2) Gate width	N/A	N/A	N/A		
	3)Width of internal road	N/A	N/A	N/A		
2.	Number, Width Type & Arran	ngement of Exits				
	A. Number of staircases			-		
	1. Upper floors	02 Nos.	02 Nos.	MR		
	2. Basements	02 Nos.	02 Nos.	MR		
	B. Width of staircase					
	1. Upper floors	150 cms.	150 cms. & 90	MR		
			cms. (iron)			
	2. Basements	150 cms.	150 cms. & 115	MR		
			cms.			
	C. Protection of exits					
	1. Fire check door	N/A	N/A	N/A		
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	N/A	N/A	N/A		
	staircase to terrace					
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1 mtr.	1 mtr.	MR		
3.	Compartmentation					
	1) Fire check door	N/A	N/A	N/A		
	-/			- 11		

N/A

N/A N/A

N/A

N/A

N/A

2) Sealing of electrical shafts

3) Fire rating of shaft door
4) Water curtain

N/A

N/A

N/A

1	5) Fire Dampers	N/A	N/A	
4.	Smoke Management Syste	em	IN/A	NA
	1) Basements	30 ACPH	T	
-	2) Upper floors	12 ACPH	Exhaus	
5.	Fire Extinguishers		Natural	MR
	1) Total numbers	12Nos.	10	
	2) Types	ABC & CO2	12 no.	MR
	3) ISI marking	Required	TIDO CC	CO2 MR
6.	First-Aid Hose Reel	required	Provide	d MR
	1)Total number at each	01 no.	0.1	
	floor	01 110.	01 no.	MR
	2) Length of hose reel hose	30 mtr.	20	
7	3) Nozzle diameter	-	30 mtr.	MR
7.	Automatic Fire Detection &	Alarming System	5 mm.	MR
	- J PO OI detections	N/A		
	2) Location of main panel	NI/A	N/A	N/A
-11	3) Location of repeater pane	1 N/A	N/A	N/A
	4) Alternate source of nower	N/A	N/A	N/A
	3) Hooter's Location	N/A	N/A	N/A
8.	MOEFA	Required	N/A	N/A
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	required	Provided	MR
	1) Basement	Required		
	2) Upper floors	N/A	Provided	MR
	3) Sprinkler above false	N/A	N/A	N/A
	ceiling	IN/A	N/A	N/A
11.	Internal Hydrants			
	1) Size of riser/down-comer	N/A		
	2) Number of hydrants per	N/A	100 mm.	N/A
	Hoor	IN/A	01 no.	N/A
	3) Hose box	N/A		д 8
12.	Yard Hydrants	IN/A	01 no.	N/A
	1) Total number of hydrants	N/A		
	2) Hose box		N/A	N/A
3.	Pumping Arrangement	N/A	N/A	N/A
	1) Ground level	NT/A		
	a) Discharge of main	N/A	N/A	N/A
	pump	N/A	N/A	N/A
	b) Head of main pump	27/4		2 1/11
	c) Number of main pump	N/A	N/A	N/A
	d) Jockey pump out put	N/A	N/A	N/A
	e) Jockey pump head	N/A	N/A	N/A
t	f) Stand by pump output	N/A	N/A	N/A
-	- Juliu of pump output	N/A	N/A	N/A
-		N/A	N/A	N/A
	otta i i gi ivialiual	N/A	N/A	N/A N/A
	stopping 2) Terrace level	н		IN/A
-	a) Digat			
	a) Discharge of pump	450 LPM	450 LPM	MR

-N/7-

	b) Head of pump	30 Mtr.	30 Mtr.	MR
	c) Power supply	Required	Provided	MR
	d) Auto starting of pump	Required	Provided	MR
4.	Captive Water Storage for Fire			
17.	Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	10,000 ltrs.	10,000 ltrs.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.	•		
10.	a) Pressurization of lift	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	Required	Provided	MR
	d) Fireman's switch	Required	Provided	MR
	e) Lift signage	Required	Provided	MR
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Systemany:	em for Protection	of special Risk, if	N/A

The fire protection system provided in the guest house were tested, checked at

random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS/MS/GH/2013/NDZ/240 dated 18/02/2014, renewal under Rule 35 of the Delhi Fire Service rules 2010, is recommended.

Gurmukh Singh Divisional Officer

Dycho(xxx)

F. p. m.scel

m-scell 2/1

1 1 mb for sign. fol.