GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

Fax No. 011-23412593, Ph. 011-23412225

No. F6/DFS/MS/GH/2017/SZ/ 04

Dated: 2.3./.1./1.7.

FIRE SAFETY CERTIFICATE

Certified that the G.R.D. Inn located at H-20/B, Kalkaji, New Delhi, comprised of Basement, Ground + 03 upper floors having 15 guest rooms was granted FSC by this department vide letter No. F.6/DFS/MS/GH/2013/310 dated 15/05/2013. The premises was reinspected by the officer concerned of this department on 06.01.2017 in the presence of Ms. Pinki (Manager) of the guest house and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Residential Lodging Building, Group-A" as above with effect from 23 1 17 for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 23 | 1 | 7 at New Delhi by

(Vipin Kental) Chief Fire Officer

Copy to: -

1. The Joint Commissioner of Police (Lic.), 1st Floor, PS Defence Colony, New Delhi.

2. M/s G.R.D. Inn at H-20/B, Kalkaji, New Delhi-110019

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety and means of escape facilities shall be maintained in good working condition at all time. Any lapse rendering the fire safety or means of evacuation facilities non-functional shall be the responsibility of the management.
- 2. Building Sanctioning authority may verify any deviation with regard to construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null & void.
- 3. The staff shall be trained for operating fire fighting system and mock evacuation drill be conducted at regular interval and record be maintained.
- 4. The basement shall be used strictly as per the provisions of Building Bye Laws.
- 5. The Owner/Occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules, 2010. The form is available on www.dfs.delhigovt.nic.in.
- 6. The Owner/Occupier shall apply for renewal of this Fire Safety Certificate to the Director in the form 'J' [sub rule (1) of rule 37] along with copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in.

		ON REPORT		
1	Name & Address of the Building	G.R.D. Inn loca	ted at H-20/B, Kalkaji, N	lew Delhi
2	Type of Occupancy	Residential & Lodging, Group-A (Guest House)		
3	Building Comprised of	Basement, Ground + 03 upper floors		
4	Type of Case	Renewal		
5	Details of Previous NOC	F.6/DFS/MS/GH/2013/310 Dated 15/05/2013		
6	Fire Safety Directives Letter No	Nil		
7	Date of Inspection	06.01.2017		
8	Name of the Inspecting Officers	ADO R.N. Sing	h	
9	Name & Designation of Officers	Ms. Pinki (Man		
	from the building side			
10	Year of construction	2009 Basement (Small office & Vacant), Ground Floor (Reception, lounge, waiting hall & kitchen), First Floor to third floor (05 G/rooms on each floor) Total15 guest rooms		
11	Applicant letter No.	4294 Joint C.P./Lic. (H) Dated 07/1		12/2016
S. No	Minimum standards on Fire Prevention and Fire Safety U/R 33	Old NOC Dt. 22/04/2010 Requirement	Provided at Site	Remarks MR/NMR
1	Access to Building.			
	Road width	Accessible	12 mtr.	MR
	Gate width	NA	NA	NA
	Width of internal road	NA	NA	NA
2	Number, width, type & arrangement of exits.			
	a. Number of Staircase			
	Upper floors	One	One	MR
	Basement floor	Two	Two	MR
	b. Width of Staircase			
	Upper floors	1.25 m	1.25 m	MR
	Basement floor	1.25 m	1.25 m each	MR
	c. Protection of exits	1.40 111	1.25 11 0001	IVIIC
	Fire check door	NA	NA	NA
	Pressurization	NA	NA	NA
				MR
	d. No. of continuous staircase to terrace	One	One	
	e. Width of corridor	NA	NA	MR
2	f. Door size	1 m	1.55 m (final exit)	MR
3	Compartmentation.	NIA.	TATA	LDIA
	• Fire check door.	NA	NA	NA
	Sealing of electrical shafts.	NA	NA	NA
	 Fire rating of shaft door. 	NA	NA	NA
	Water curtain	NA	NA	NA
	Fire dampers.	NA	NA	NA
4.	Smoke Management system.			
	Basement	30 ACPH	Exhaust Fans	MR
	Upper floors	12 ACPH	Exhaust Fans	MR
5.	Fire Extinguishers.			
	Total numbers	Portable Fire	12 Nos.	MR
	• Types	Extinguishers	ABC-10, W.Co2-02	MR
	ISI Marking	ISI marked	Yes	MR
6.	First Aid Hose Reels.			
	 Total numbers on each floor. 	Hose Reel	One	MR
	 Length of hose-reel hose. 		30 m	MR
	Nozzle Diameter		05 mm	MR

Renewal

M/s G.R.D. Inn at H-20/B, Kalkaji, New Delhi-110019

13	.3	
March 1	M	į.
	Mil	2

7	Automatic fire detection & alarming system.	Dagwined	Smoke	MR
	Type of detectors	Required	Ground floor	NA
	Location of Main Panel	NA	NA	NA
	Location of Repeater Panel	NA	Provided	MR
	Alternate source of power	Required	Each floor	NA
	Hooter's location	NA		MR
8.	MOEFA	Required	Provided	NA
9.	Public Address System	NA	Provided	INA
10.	Automatic Sprinkler System		D 11-1	MR
	 Basement 	Required	Provided	NA
	 Upper floors 	NA	NA	NA NA
	Sprinkler above false ceiling	NA	NA	INA
11.	Internal Hydrants.		1.00	MD
	 Size of Riser/Down-comer 	Required	100 mm	MR
	 Number of Hydrant per floor 	NA	NA	NA
	Hose box.	NA	NA	NA
12.	Yard Hydrants.			1 27.1
	Total number of hydrants.	NA	NA	NA
	Hose box.	NA	NA	NA
13.	Pumping arrangements.			
	a) Ground Level			
	Discharge of main pump.	NA	NA	NA
	Head of main pump.	NA	NA	NA
	Number of main pumps.	NA	NA	NA
	> Jockey Pump output.	NA	NA	NA
	Jockey Pump head.	NA	NA	NA
	> Standby Pump output.	NA	NA	NA
	Standby Pump head.	NA	NA	NA
	Auto Starting/Manual Stopping.	NA	NA	NA
	> Pump House Access	NA	NA	NA
	A.	INA	1471	1111
	b) Terrace Level	Required	450 LPM & 180 LPM	MR
	Discharge of pump.	Required	40 Mtr	MR
	> Head of pump.		Provided	MR
	Power supply.	Required	Provided	MR
	> Auto starting of pump.	Required	Provided	IVIIX
14.	Captive water storage for Fire Fighting.		, DIA	NA
	 Underground tank capacity. 	NA	NA	NA NA
	 Draw-off connection. 	NA	NA	MR
	 Fire Service Inlet. 	Required	Provided	
	 Access to tank. 	Required	Provided	MR
	 Overhead tank capacity. 	5,000 Ltr.	5,000 Ltr	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	Pressurization of lift shaft.	NA	NA	NA
17	Pressurization of lift lobby.	NA	NA	NA
	• Communication in lift car.	NA	NA	NA
	• Fireman's switch.	Required	Provided	MR
		NA	NA	NA
	Lift signage. St. II. Programmer.	Required	Provided	MR
17	Standby Power Supply	Required	11011000	
18.	Refuge Area	NIA	NA	NA
	Total area	NA	NA NA	NA
	 Location 	NA	n at H-20/B, Kalkaji, New I	

Renewal



19.	Fire Control Room.			
	Detector System Panel.	NA	NA	NA
	Flow Switch Panel.	NA	NA	NA
	PA system Panel.	NA	NA	NA
	Battery backup	NA	NA	NA
*	Building floor plan	NA	NA	NA
20.	Special Fire Protection System for the	NA	NA	NA
	Protection of special Risk, if any.		19	

The Fire protection systems provided in the building were randomly checked/ tested and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, Fire Safety Certificate issued vide letter No. F6/DFS/MS/GH/2013/310 dated 15.05.2013, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name : R.N. Singh

Designation: ADO

Renewal

M/s G.R.D. Inn at H-20/B, Kalkaji, New Delhi-110019

Div. Officer (SD)

Dy (Po(52)

12(1

CFO Sps

MSCELL

ETM

W 13/1