GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. F-6/DFS/MS/ FH / 2017/WZ / 81

Dated: / 9 / 0 / /2017

FIRE SAFETY CERTIFICATE

Certified that <u>Guru Kirpa Farms</u>, <u>Palla Bakhtawarpur Road</u>, <u>Delhi-110036</u> comprised of <u>Ground + one upper floor</u> is owned / occupied by that <u>Guru Kirpa Farms</u> was issued fire safety certificate vide Letter No.<u>F.6/DFS/MS/FH/ 2013/405 dated 31/05/2013</u> have complied with the fire prevention and fire safety Requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officers concerned of fire service on <u>16/12/2016</u> in the presence of <u>Sh. Radhey Shyam Gosain (Owner)</u> and that the building / premises is fit for occupancy <u>Class Sub Div. D-5 Assembly Building</u> with effect from <u>/ ? / o / / 2017</u> for a period of <u>three years</u> in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Conditions for the validity of Fire Safety Certificate:

- 1. Means of escape shall not be kept locked or bolted from outside and shall be easily open able by occupants in case of an emergency.
- 2. All employees shall be acquainted with the use and maintenance of all the fire fighting installation/equipments.
- 3. The fire suppression / protection arrangements provided in the guest house are to minimize losses, if maintained in good working condition. These systems cannot give any guarantee that there will be no fire or losses in the event of one.
- 4. Any loss of life and property due to non-functional of fire safety arrangements and other installations shall be the responsibility of the licensee.
- 5. This report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on **WWW.dfs.Delhigovt.nic.in**

Issued on $\frac{19 / of / (7)}{2}$ at New Delhi by

(Atul Garg) Chief Fire Officer Ph: 011-23414250

Copy to:

- 1. Guru Kirpa Farms, Palla Bakhtawarpur Road, G. T. K. Road, Delhi-110036
- 2. Office Of the Asstt. Commissioner NDMC, Narela Zone, Narela Delhi-110040.

INSPECTION REPORT

Gr. + one upper floor

1. Name & address of the building: Guru Kirpa Farms, Palla Bakhtawarpur Road,

Delhi-110036.

2. Type of Occupancy Assembly Place

3. Type of Case : Renewal

4. Details of previous NOC : Letter No.F.6/DFS/MS/FH/2013/405 dated 31/05/2013

5. Fire Safety directives letter No : NBC Part IV

6. Date of inspection : 16/12/2016

7. Name of the Inspecting Officers: ADO (BW)

8. Name and designation of officers

from the building side : Sh. Radhey Shyam Gosain (Owner)

9. Year of Construction : 1996

10. Applicant's letter No. O.D dated 10/11/2016 : Nil

Plot Area: 2.5 Acres Covered Area: 400 sq yard

S. No.	Minimum Standards on fire prevention and fire safety U/R 33 Access to building	NBC Requirement	Provided at site	Remarks MR/NMR
	Road width	*		
	Gate width	9.0 mtr	9.0 mtr	MR
	 Width of internal road 	5.0 mtr	6.0 mtr	MR
		6.0 mtr	6.0 mtr	MR
	Number, Width, Type & Arrangement	of Exits		3
	a. Number of staircases	N.A	37.4	
	• Unner Floor		N.A	N.A
	• Upper Floors	01	01	MR
	Basements A Wilth Control	N.A	N.A	N.A
	b. Width of staircases	N.A	N.A	. N.A
	 Upper Floors 	1.25 mtr	1.25 mtr	MR
	Basements	N.A	N. A.	Being Old Case
	c. Protection of exits	IV.A	N.A	N.A
		N.A	N.A	N.A
	 Fire check door 		OHA 122	IV.A
	 Pressurization 	N.A	N.A	N.A
		N.A	N.A	N.A
e.	No. of continuous staircases to terrace	N.A	N.A	N.A
g.	Width of Corridor			IV.A
		N.A	N.A	N.A
h.	Door Size	105		
		1.25 mtr	1.25 mtr	MR

NIR

Guru Kirpa Farms, Palla Bakhtawarpur Road, Delhi-110036

	Compartmentation.		N.A	N.A
	• Fire check door	N.A	N.A N.A	N.A
	 Sealing of electrical shafts 	N.A		N.A
	 Fire Rating of shaft door 	N.A	N.A	
	Water Curtain	N.A	N.A	N.A
		N.A	N.A	N.A
	• Fire Dampers			
ŀ	Smoke Management System.	30 a/c per hour	N.A	N.A
	• Basements	12 a/c per hour	Natural ventilation	MR
	• Upper floors	12 dre per neur	11000	
5	Fire Extinguishers	16 ADC	16	MR
	Total numbers	16 ABC	ABC	MR
	• Types		Yes	MR
	IS marking	ISI marked	Yes	IVIIC
6	First-Aid Hose Reels.			
	Total numbers on each floor	One	Provided	MR
			Provided	MR
	• Length of hose reel hose	30 m	Provided	MR
	Nozzle diameter	5 mm		
7	Automatic fire detection and alarming	system.	N.A	N.A
	Type of detectors	N.A	N.A	N.A
	 Location of Main Panel 	N.A		N.A
	 Location of Repeater Panel 	N.A	N.A	
	Alternate source of power	N.A	N.A	N.A
	Hooters' Location	N.A	N.A	N.A
0	MOEFA	Required	Provided	MR
8		N.A	N.A	N.A
9	Public Address System.	1 1.17	*	
10	Automatic Sprinkler System.		e dal Trans	D.T. A
	Basement	N.A	N.A	N.A N.A
	Upper Floor	N.A	N.A	
	 Sprinkler above false ceiling 	N.A	N.A	N.A
11	Internal Hydrants		D +1 1	MR
	Size of riser/down-comer	100 mm	Provided	MR
	 Number of hydrants per floor 	01	Provided	MR
		Required	Provided	1 1 1 1 1

pholom

		Yard Hydrants.	21.4	N.A	N.A
+	•	Total number of hydrants	N.A		N.A
		Hose Box	N.A	N.A	N.A
3	Pumpi	ng Arrangements.			7.T. A
+	·	Ground Level	N.A	N.A	N.A
		Discharge of main Pump	N.A	N.A	N.A
		> Head of Main pump	N.A	N.A	N.A
			N.A	N.A	N.A
			N.A	N.A	N.A
		> Jockey Pump out put	N.A	N.A	N.A
		> Jockey pump head	N.A	N.A	N.A
		> Standby Pump out put	N.A	N.A	N.A
		Standby Pump HeadAuto Starting/ Manual	N.A	N.A	N.A
		stopping	N.A	N.A	N.A
		> Pump House Access	N.A	N.A	N.A
	•	Terrace level	900 LPM	900 LPM	MR
		> Discharge of pump	40 M	40 M	MR
		> Head of the pump	N.A	N.A	N.A
		> Power Supply	N.A	N.A	N.A
		> Auto Starting of pump			
14	Capt	ive Water Storage for fire fighting		27.4	N.A
	•	Underground tank capacity	N.A	N.A	4
	>	22	N.A	N.A	N.A
	>	Fire service inlet	N.A	N.A	N.A
			N.A	N.A	N.A
		Overhead Tank capacity	10,000 ltr	15,000 ltrs	MR
15	Fv:4	Signage.	Required	Provided	MR
					^
16	Pro	vision of Lifts.	N.A	N.A	N.A
	•	Pressurization of Lift Shaft	N.A	N.A	N.A
	•	Pressurization of Lift lobby	N.A	N.A	N.A
	•	Communication In lift Car		N.A	N.A
	•	Fireman's Grounding Switch	N.A		N.A
	•	Lift Signage	N.A	N.A	
17	Sta	ndby power supply	Required	125 KVA	MR
1.7	200				

Ale Some

		N.A
N.A	N.A	IN.A
N A	N.A	N.A
11.71		
N.A	N.A	N.A
N A	N.A	N.A
102 14 10	N. A.	N.A
N.A	N.A	N.A
N.A	N.A	N.A
	DI A	N.A
N.A	N.A	
N.A	N.A	N.A
	N.A	N.A N.A N.A N.A N.A N.A N.A N.A N.A N.A

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of the fire prevention and fire safety measures as required under the rules the NOC issued vide letter no Letter No. F.6/DFS/MS/FH/ 2013/405 dated 31/05/2013. Renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended

Signature of the Inspecting Officer

Name

Designation

Signature of the Inspecting Officer Name

Designation