## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

NO. F6/DFS/MS/2017 / W2 / 1 58
FIRE SAFETY CERTIFICATE

Dated: 24/0/ /2018

Certified that Multistoried houses at sector -A-9, pocket-1, Narela Delhi-40 comprised of Four blocks, Basement + S + Eleven upper floors, owned/occupied by that Multistoried houses have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer of Fire Service on 05/11/2016 in the presence Sh. A K Pandey A.E (Elect.) & A. K. Singal A.E(Civil) and the building/premises is fit for occupancy Class Residential Building "Group A-4" with effect from 24 / 0/ /2018 for a period of Five years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rule, 2010.

- 1. Means of escape shall not be kept locked or bolted from outside and shall be easily open able by guests in an event of emergency.
- 2. All employees shall be acquainted with the use and maintenance of all the fire fighting installation/equipments.
- 3. The fire suppression / protection arrangements provided in the guest house are to minimize losses, if maintained in good working condition. These systems cannot give any guarantee that there will be no fire or losses in the event of one.
- 4. The basement shall be used strictly as per the provision of building bye laws.
- 5. Any loss of life and property due to non-functional of fire safety arrangements and other installations shall be the responsibility of the licensee.
- 6. This report may not in any way be treated as regularization of unauthorized construction, if
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 8. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form available WWW.dfs.Delhigovt.nic.in

(Atul Garg) Chief Fire Officer Ph: 011-23414250

Copy to:-

- 1. The Executive Engineer, Northern Division-3, DDA, Kingsway Camp, Mukherjee Nagar, New Delhi-110009
- 2. The AE (Elrct.)Multistoried houses at sector, A-9, pocket-1, Narela Delhi-40

## INSPECTION REPORT

Four blocks B+S+11 floors

1. Name & address of the building: Multistoried houses at sector-A-9, pocket-1, Narela Delhi-40

2. Type of Occupancy

: Residential Building "Group A-4"

3. Type of Case

: New Case

4. Details of previous NOC

: Nil

5. Fire Safety directives letter No : Letter No.F.6/DFS/MS/2010/2304 dated 08/05/2010

6. Date of inspection

: 05/11/2016

7. Name of the Inspecting Officers: DO(NW) & ADO (BW)

8. Name and designation of officers

from the building side

: Sh. A K Pandey A.E (Elect.) & A. K. Singal A.E(Civil)

9. Year of Construction

: 2014

10. Applicant's letter No.

dated 06/10/2016 : F.38(72)AE(P)/ND-3/DDA/1558

Plot Area:26446.36 m2

Covered Area Basement:18425 m2 + Upper floor-45780 m2

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR
1	Access to building	¥		
	Road width	18 mtr	18 mtr	MR
	Gate width	4.5 mtr	06 mtr	MR
	Width of internal road	06 mtr	06 mtr	MR
2	Number, Width, Type & Arrangement o	f Exits		3
	a. Number of staircases	Required	Provided	MR
	Upper Floors	03 in each block	03 in each block Provided	MR
	Basements	03 in each block Ramp-02	03 in each block Ramp-02 Provided	MR
	b. Width of staircases	N/A	N/A	N/A
		1.50 mtr each	3 X 1.5 mtr each Block Provided	MR
	<ul><li>Upper Floors</li><li>Basements</li></ul>	Ramp-2 X 4.0 mtr S/C-1.50 mtr each	3 X 1.5 mtr each Block & 2 X6.0 mtr Ramps Provided	MR
	c. Protection of exits	N/A	N/A	N/A
	Fire check door	Required	Provided	MR
	Pressurization	Required	Provided	MR
	e. No. of continuous staircases to terrace	1 in each block	2 in each block	MR
	g. Width of Corridor	N/A	N/A	N/A
	h. Door Size	1.00 mtr	1.00 mtr	MR

3	Compartmentation.	_			
	Fire check door	Required	Provided	MR	
	Sealing of electrical shafts	Required	Provided	MR	
	Fire Rating of shaft door	N/A	N/A	N/A	
	Water Curtain	N/A	N/A	N/A	
	Fire Dampers	N/A	N/A	N/A	
4	Smoke Management System.				
	Basements	30 a/c per hour	Provided	MR	
	Upper floors	12 a/c per hour	Natural	MR	
5	Fire Extinguishers				
	Total numbers	One @ 300 m2	157 157	MR	
	• Types		ABC CO2	MD	
	IS marking	ISI marked	ABC CO2	MR	
			Yes	MR	
5	First-Aid Hose Reels.				
	Total numbers on each floor	02 in each floor	Provided	MR	
	<ul> <li>Length of hose reel hose</li> </ul>	each block 30 m	Provided	MR	
	Nozzle diameter	5 mm	Provided	MR	
7	Automatic fire detection and alarming system.				
	Type of detectors	Required	Provided	MR	
	Location of Main Panel	Required	Provided on gr. floor	MR	
	Location of Repeater Panel	N/A	N/A	N/A	
	Alternate source of power	Required	Provided	MR	
	Hooters' Location	Each floor	Provided	MR	
	MOEFA	Required	Provided	MR	
)	Public Address System.	Required	Provided	MR	
0	Automatic Sprinkler System.				
	Basement	Required	Provided	MR	
	Upper Floor	N/A	N/A	N/A	
	<ul> <li>Sprinkler above false ceiling</li> </ul>	N/A	N/A	N/A	
1	Internal Hydrants				
	Size of riser/down-comer 100mm	02 in each blk on	Provided	MR	
	Number of hydrants per floor	each floor 02 in each blk on	Provided		
	Hose Box	each floor	he see to it specture mit	MR	
		02 in each blk on each floor	Provided	MR	

12	Yard Hydrants.				
	Total number of hydrants	N/A	N/A	N/A	
	Hose Box	N/A	N/A	N/A	
13	Pumping Arrangements.			1175	
	Ground Level	N/A	N/A	N/A	
	Discharge of main Pump	1620 LPM	1620 LPM Provided	MR	
	Head of Main pump	70 M	70 M Provided	MR	
	Number of main pumps	02	02	MR	
	Jockey Pump out put	180 LPM	180 LPM Provided	MR	
	Jockey pump head	70 M	70 M Provided	MR	
	Standby Pump out put	1620 LPM	1620 LPM Provided	MR	
	Standby Pump Head	70 M	70 M Provided	MR	
	<ul><li>Auto Starting/ Manual stopping</li></ul>	Required	Provided	MR	
	Pump House Access	Required	Provided	MR	
	Terrace level	N/A	N/A	N/A	
	Discharge of pump	N/A	N/A	N/A	
	Head of the pump	N/A	N/A	N/A	
	Power Supply	N/A	N/A	N/A	
	Auto Starting of pump	N/A	N/A	N/A	
(	Captive Water Storage for fire fighting.				
	<ul> <li>Underground tank capacity</li> </ul>	75,000 ltrs	1,00,000 ltrs	MR	
	Draw-off connection	Required	Provided Provided	- 2	
	Fire service inlet	Required		MR	
	Access to tank	•	Provided	MR	
	Overhead Tank capacity	Required	Provided	MR	
F	Exit Signage.	20,000 ltrs	40,000 ltrs Provided	MR	
	Provision of Lifts.	Required	Provided	MR	
+	Pressurization of Lift Shaft	Paguina 1			
		Required N/A	Provided	MR	
	• Pressurization of Lift lobby		N/A	N/A	
	• Communication In lift Car	Required	Provided	MR	
'	Fireman's Grounding Switch	Required	Provided	MR	
-	• Lift Signage	Required	Provided	MR	
St	andby power supply	Required	Provided	MR	

N-24

Multistoried houses at sector-A-9, pocket-1, Narela Delhi-40.

18	Refuge Area.			
	Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19	Fire Control Room			
	Detector System Panel	Required	Provided	MR
	Flow Switch Panel	Required	Provided	MR
	PA System Panel	Required	Provided	MR
	Batter backup	Required	Provided	MR
	Building Floor Plans	Required	Provided	MR
20	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/ issue shortcomings as noted at serial numbers...nil......

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name

Name

Designation

Designation

ADORD P

SSmyh