## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CONNAUGHT PLACE NEW DELHI-110001.

No. F.6/DFS/MS/2017/SZ / 13 a

Dated: 2/2/17

## FIRE SAFETY CERTIFICATE

Certified that the Plot No.-19, District Centre, Janak Puri, New Delhi-110058, comprised of basement, ground plus four upper floors owned/ occupied by M/s Inox Leisure ltd. & Superior Films Pvt. Ltd. Earlier known as Satyam Cinema was issued NOC by this department vide letter no. F.6/MS/DFS/Cinema/2004/1166 dated 01.6.2004 was re-inspected by the officers concerned of this department on 02.12.2016 in the presence of Sh. Sanjay Kumar (Asst. Facility Manager) and found that the owner have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/ premises is fit for occupancy class Mixed occupancy (Assembly & Business) w.e.f. the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule-38 of the Delhi Fire Service Rules, 2010 printed overleaf.

Issued on 2 12 12017 at New Delhi.

(VIPIN KENTAL) CHIEF FIRE OFFICER

Copy to:-

- The Manager, Supperior Films Pvt. Ltd., Mall Area, Plot No.-19, District Centre, Janak Puri, New Delhi-110058.
- 2. The District Magistrate (West), Govt. of NCT of Delhi, Old Middle School Complex, Rampura, New Delhi-110035.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. The means of escape arrangements shall be kept unlocked & unobstructed for speedy evacuation of occupants in case of an emergency.
- 3. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 4. The trained staff should be available round the clock.
- 5. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 6. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 7. Basement shall be used as per the building bye laws.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 9. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in the Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry.

	INSPECTION	REPORT	72				
	1 Name & address of the building: Plot No19	, District Centre, Jan	nak Puri, New De	lhi-110058.			
	2. Type of Occupancy : Group D (A	: Group D (Assembly Building)					
	J. Type of case	Renewal					
	T. Details of The vious 1.00	F.6/MS/DFS/Cinema/2004/1166 dated 01.6.2004 F.6/MS/DFS/BP/2002/Cinema/992 dated 24.06.2002					
	5. The Surety and the						
	O. Bate of inspection	uggal					
	1	Chattopadily dy & 11	.5.0.0.0				
	8. Name and designation of officers From the building side : Sh. Sanjay Kumar (Asst. Facility Manager)						
	9. Year of Construction : 2002						
		ated 26.08.2016					
~	Minimum Standards on fire prevention and fire	NBC/ BBL	Provided at	Remarks			
S. No.	safety U/R 33	Requirement	site	MR/NMR			
1.	Access to building			*			
*/	1100000 to 1 ===== g			) (D			
7	Road width	Accessible (09 mtrs) 06 mtrs	12 mtrs Directly accessible	MR MR			
	Gate width	06 mtrs	from road	MR			
	<ul> <li>Width of internal road</li> </ul>	00 mus	06 mtrs	IVIIX			
2.	Number, Width, Type & Arrangement of Exits						
4.	Trumper, traces, type or transferment of			-			
	a. Number of staircases	0.132	0421 2	MD			
	Upper Floors	04 No.'s	04 No.'s	MR			
	Basements	01 No.+ 01 Ramp	01 No.+ 01 Ramp	MR			
	b. Width of staircases		Kamp				
	Upper Floor	02 mtrs	2.07, 2.12, 2.07	MR			
	Basements	02 mus	& 2.04 mtrs	1711			
	Basements	02 mtrs	S/Case 2.03 &	MR			
			Ramp 4.5 mtrs				
	c. Protection of exits	*		N/D			
	Fire check door	Required	Provided	MR			
	Pressurization	Required	Provided	MR			
	d. No. of continuous staircases to	Required	One	MR			
	terrace	150 cms	Opening in	MR			
	e. Width of Corridor		hall				
	f. Door Size	150 cms	150 cms	MR			
	1. Door size		V				
3.	Compartmentation		3 2				
	71 1 1 1	Required	Provided	MR			
	<ul><li>Fire check door</li><li>Sealing of electrical shafts</li></ul>	Required	Sealed	MR			
	<ul> <li>Sealing of electrical sharts</li> <li>Fire Rating of shaft door</li> </ul>	<u> </u>	N/A	N/A			
	Water Curtain	N/A		12 200 200 200 200			
	• Fire Dampers	N/A	Provided	N/A			
	•	Required	Provided	MR			
4.	Smoke Management System						
	Pagamanto	Air change PH	Provided	MR			
	• Basements	G					
		2		N. C.			
	Upper floors	12 Air change	Natural	MR			
		PH	Ventilation				
5.	Fire Extinguishers		D 11 1	MR			
	Total numbers	50 No.'s	Provided				
	• Types	ABC/CO <sub>2</sub> /WCO <sub>2</sub> ISI marked	Provided	MR			
	IS marking	151 marked	ISI marked	MR			
6.	First-Aid Hose Reels						
	1.0	03	Provided	MR			
	Total numbers on ground floor	30 mtrs	Provided	MR			
	<ul> <li>Length of hose reel hose</li> </ul>	-					

/.	Automatic fire detection and alarming system					
	Type of detectors	Smoke & Heat	Provided	MR		
	<ul> <li>Location of Main Panel</li> </ul>	Required	G. Floor	MR		
	<ul> <li>Location of Repeater Panel</li> </ul>	N/A	N/A	N/A		
	Alternate source of power	Required	Provided	MR		
	Hooters' Location	Required	Provided Near exit	MR		
8.	MOEFA	Required	Provided	MR		
9.	Public Address System	Required	Provided	MR		
10.	Automatic Sprinkler System					
	Basement	Required	Provided	MD		
	Ground Floor	Required	Provided	MR MR		
	<ul> <li>Sprinkler above false ceiling</li> </ul>	Required	Provided			
11.	Internal Hydrants	Required	Trovided	MR		
	<ul> <li>Size of riser/down-comer</li> </ul>	150 mm	Provided	MR		
	<ul> <li>Number of hydrants</li> </ul>	03 No.'s	Provided	MR		
	Hose Box	03 No.'s	Provided	MR		
12.	Yard Hydrants					
	Total number of hydrants	Two	Provided	MR		
12	Hose Box	Two	Provided	MR		
13.	Pumping Arrangements					
	<ul> <li>Ground Level</li> <li>Discharge of main Pump</li> </ul>					
	<ul><li>Discharge of main Pump</li><li>Head of Main pump</li></ul>	2850 LPM	Provided	MR		
	Number of main pumps	60 mtrs	Provided	MR		
	> Jockey Pump out put	One	Provided	MR		
	> Jockey pump head	180 LPM	Provided	MR		
		60 mtrs	Provided	MR		
	Standby Pump out put	2850 LPM	Provided	MR		
	<ul><li>Standby Pump Head</li><li>Water Curtain Pump</li></ul>	60 mtrs	Provided	MR		
	> Auto Starting/Manual Stopping	Required	Provided			
	Trate Starting Manual Stopping	-		MR		
	, D , Y	Required N/A	Provided Provided	MR		
	<ul><li>Pump House Access</li><li>Terrace level</li></ul>	IVA	riovided	N/A		
	Discharge of pump	N/A	DI/A	27/4		
	<ul><li>Head of the pump</li></ul>	N/A	N/A	N/A		
	Power Supply	N/A	N/A N/A	N/A		
	➤ Auto Starting of pump	N/A	N/A	N/A N/A		
14.	Captive Water Storage for fire fighting					
5	Underground tank capacity	100000 Ltrs	Provided	MR		
"	<ul><li>Draw-off connection</li><li>Fire service inlet</li></ul>	Required	Provided	MR		
	Access to tank	Required	Provided	MR		
	Overhead Tank capacity	Required	Provided	MR		
		10000 ltrs	45000 ltrs Provided	MR		
15.	Exit Signage.	Required	Provided	MR		
16.	Provision of Lifts.					
10.	Pressurization of Lift Shaft	N/A	DT/A	77/4		
	<ul> <li>Pressurization of Lift Shalt</li> <li>Pressurization of Lift lobby</li> </ul>		N/A	N/A		
	Communication In lift Car	N/A	N/A	N/A		
	Fireman's Grounding Switch	Required	Provided	MR		
	• Lift Signage	Required	Provided	MR		
	2000	Required	Provided	MR		
	LOS PROPERTO DE LA CONTRACTOR DE LA CONT	Required	Provided	MP		

18.	Refuge Area.			
	> Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19.	Fire Control Room			
	Detector System Panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA System Panel	N/A	N/A	N/A
	<ul><li>Battery backup</li><li>Building Floor Plans</li></ul>	N/A	N/A	N/A
		N/A	N/A	N/A
20.	Special Fire Protection System for Protection of special Risks, if any:	Manual CO <sub>2</sub> Fire Fighting System for LT, HT Panel Modular type DCP for AVH's	Provided	MR

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the Fire Safety Certificate issued vide letter number F.6/MS/DFS/Cinema/2004/1166 dated 01.6.2004 renewal under rule 37 of the Delhi Fire Service Rules 2010 is recommended.

Note:- Satyam Cineplex (Audi 1-4) common basement, Partial Ground floor, first floor, second floor, third floor and fourth floor in the mall area has already been issued FSC vide letter no. F6/DFS.MS/cinema/2014/SZ/624 dated 21.05.2014.

Signature of Inspecting Officer

Name: - M.K. Chatto adhyay Designation: - Divisional Officer Signature of Inspecting Officer

Name: - Sandeep Duggal

Designation:- Asstt. Divisional Officer

Dy. C.F.O.(South Zone)

CFO(\$7) m.s cen 4/19/1

F.T. lother is put up prosignature please

crocszo m.scen 4/2