GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI – 110001

No.F6/DFS/MS/2017/ School/ MO2/194

Dated: 10/2/17

FIRE SAFETY CERTIFICATE

Certified that the N.P Sec. School located at Havlock Square, Gole Market, New Delhi comprises of Ground + 02 Upper floor was granted FSC by this department vide letter No. F6/DFS/MS/School/2014/NDZ/64 dated 16/01/2014. The premises was re-inspected by the officer concerned of this department on 02-02-2017 in the presence of Sh. Sajjan Kumar (Fire Officer) and found that the said school building have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy of class Group B "Educational Building" Sub-Div. B-I with effect from 4-0-12-1-2017 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 on the conditions printed below.

Issued on . l.o.l.21.1.7..... at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

P/r Me

Copy to:-

- The Principal,
 N.P Sec. School,
 Havlock Square, Gole Market, New Delhi.
- 2. Director of Education, Govt. of NCT, Delhi.
- 3. Sh. Sajjan Kumar, Fire Officer, Fire Department, NDMC, Palika Kendra, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided there in shall be maintained in good working condition at all time. The owner / occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six months prior to its expiry".

-14/8-

	<u>I</u>	NSPECTION RE	PORT					
	1. Name & address of the b	Name & address of the building:- N.P Sec. School at Havlock Square, Gole						
		Market,	New Delhi .					
	2. Type of occupancy:-	Education	onal Building, Gr.	+ 2 Upper flo				
	3. Type of case:-	Educational Building, Gr. + 2 Upper floo Renewal						
	4. Details of previous FSC:- F6/DFS/MS/School/2014/NI							
	16/01/2014.							
	6. Date of inspection:-	N/A						
	7 Name of the inspection:	NI OI A						
	Name of the inspecting officer:- Sh. Manoj Kumar Sharma (ADO/CC)							
	From the building side:-	cer						
	9. Year of construction:-	Sh. Sajjar	Kumar (Fire Off	ficer)				
	10. Applicant's letter No:-	Old	2 4 2					
S.No	D. Minimum Standards on fire	Nil dated	02/01/2017					
0.110	Standards on the		Provided at sit	te Remarks				
	Prevention and fire safety U/R 33	Existing fire		MR/NMF				
	U/K 33	safety		1 100 200 00000000000000000000000000000				
1.	Access to Building	arrangements						
	1) Road width							
		Accessable	09 mtr.	MR				
	2) Gate width	04 mtr.	04 mtr.	MR				
	3) Width of internal road	NA	NA	NA				
2.	Number, Width Type & Arra	angement of Exit	S	11/1				
	A. Number of staircases							
	1. Upper floors	02	02	MR				
	2. Basements	NA	NA NA					
	B. Width of staircase	1	IVA	NA				
	1. Upper floors	1.5 mtr.	1.20 & 1.12 mtr.	1.00				
	2. Basements	NA NA	NA 1.12 mtr.	MR				
	C. Protection of exits	1111	IVA	NA				
	1. Fire check door	N/A	NI/A					
	2. Pressurization	N/A	N/A	N/A				
	D. No. of continuous	01	N/A	N/A				
	staircase to terrace	01	01	MR				
	E. Width of corridor	2						
	F. Door size	2 mtr.	2 mtr.	MR				
	Compartmentation	1 mtr.	1 mtr	MR				
			e e " ;					
	1) Fire check door	N/A	N/A	N/A				
	2) Sealing of electrical shafts	N/A	N/A	N/A				
	3) Fire rating of shaft door	N/A	N/A	N/A				
	4) Water curtain	N/A	N/A	N/A				
	5) Fire Dampers	N/A	N/A	N/A				
	Smoke Management System							
	1) Basements	30 ACPH	N/A	N/A				
	2) Upper floors	12 ACPH	Natural					
	Fire Extinguishers	and the same of th	1,acarar	MR				
	1) Total numbers	16 Nos.	20 Nos.	MD				
	2) Types	ABC & CO2	ABC, CO2	MR				
	3) ISI marking	Required		MR				
	First-Aid Hose Reel	required	Provided	MR				
	1)Total number of each	02	02					
	floor	02	02	MR				
	2) Length of hose reel hose	30 mt=	20					
	3) Nozzle diameter	30 mtr. 05 mm	30 mtr. 05 mm	MR				
	- , A : VEELV MIGHTURE	113 10110	() 5	MR				

	Automatic Fire Detection & 1) Type of detectors	Alarming System				
		N/A				
	2) Location of main panel		N/A	N/A		
	3) Location of repeater pane	N/A	N/A	N/A		
	4) Alternate source of power	el N/A	N/A	N/A		
	5) Hooter's Location		N/A	N/A		
8.	MOEFA	N/A	N/A	N/A		
9.	Public Address System	N/A	N/A	N/A		
10.	Automatic Sprintle G	N/A	Provided	N/A		
10.	Automatic Sprinkler System 1) Basement		*			
		N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false ceiling	N/A	N/A	N/A		
11.	Internal Hydrants					
	1) Size of riser/down-comer	100 mm	100			
	2) Number of hydrants per	02No. each floor	100 mm	MR		
	floor	021\0. each 1100	o. outli	MR		
	3) Hose box	02Na 2221 C	floor			
	,	02No. each floor		MR		
12.	Yard Hydrants		floor			
	1) Total number of hard					
	2) Hose box	N/A	N/A	N/A		
13.	Pumping Arrangement	N/A	N/A	N/A		
	1) Ground level					
	a) Discharge of main	N/A	N/A	N/A		
	pump			14/11		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main	N/A	N/A	N/A		
	pump			IN/A		
	d) Jockey pump out put	N/A	N/A	N/A		
	e) Jockey pump head	N/A	N/A			
	f) Stand by pump	N/A	N/A	N/A		
	output		IVA	N/A		
	g) Stand by pump head	N/A	N/A	27/1		
	h) Auto starting/Manual	N/A	N/A	N/A		
	stopping	14/21	IN/A	N/A		
	2) Terrace level		3 6 28			
	a) Discharge of pump	150 & 220 I D. 5	450.0.00			
	b) Head of pump	450 & 220 LPM 40 mtr.	450 & 220 LPN			
	c) Power supply		40 mtr.	MR		
	d) Auto starting of	Required	Provided	MR		
	pump	Required	Provided	MR		
4.	Captive Water Storage for Eins	Ei alati				
	Captive Water Storage for Fire Fighting 1) Under ground tank N/A					
	broand tank	N/A	N/A	N/A		
}	capacity	1 7 1				
F	1) 7:	N/A	N/A	N/A		
+) 1	N/A	N/A	N/A		
-		Required	Provided	MR		
	d) Over head tank	5,000 ltr.	5,000 ltr.	MR		
	capacity		,	14117		
	Exit Signage.	Required	Provided	MR		
	Provision of Lifts.		- 10 11dCd	IVIK		
) B	AT/A				
	a) Pressurization of life N			1		
	a) Pressurization of lift shaft	N/A	N/A	N/A		

11/9-

no

- W110 -

	lobby				
	c) Communication in lift car	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
	e) Lift signage	N/A	N/A	N/A	
17.	Stand by Power Supply	N/A	N/A	N/A	
18.	Refuge Area	N/A	N/A	N/A	
	Total area location	N/A	N/A	N/A	
19.	Fire Control Room	N/A	N/A	N/A	
	a) Detector system panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A	
20.	Special Fire Protection System for Protection of special Risk, if any: DCP, CO ₂				

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/School/2014/NDZ/64 dated 16/01/14 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name:- M.K. Sharma Designation:- A. D.O. (CC)

0 ... 0 (1)(57)

DYC60 (402)

(. F.

FIM.

m.scell

1/2

F.T. letter is put up f

M. SCEU WAZ

messe

220 cfo AD2 7/21 17/9/2