## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/EH/2017/ NO2/236

Dated: 20/02/17

## FIRE SAFETY CERTIFICATE

Connaught Place New Delhi comprised of Basement, Ground, Mezzanine + 2 Upper Floor, restaurant running at ground & mezzanine floor, basement room for store, was granted FSC by this department vide letter No.F6/DFS/MS/GH/2014/NDZ/145 dated 30/01/14 The premises was re-inspected by the officer concerned of this department on 08/02/17 in the presence of Mr. Ankur Aggarwal and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises fit for occupancy class Assembly Building Group D (Restaurant) with effect from \( \subseteq \frac{1}{2} \subseteq

Issued -- 2010217---at New Delhi by.

(Vipin Kehtal) Chief Fire Officer Delhi Fire Service Ph. 011-23412225

- Copy to:- (1) Medical Officer of Health, New Delhi Municipal Council, Palika Kendra, New Delhi.
  - (2) Barracks Restaurant (A unit of Lido Dinner) at M-38, Connaught Place New Delhi.

## Conditions:

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (!) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

INSPECTION REPORT

1. Name & address of the building:- Barracks Restaurant (A unit of Lido Dinner)

at M-38, Connaught Place New Delhi.

2. Type of occupancy:- Group – D Assembly Building

Basement, Gr., Mezz. + 2 Upper Floors.

3. Type of case:- Renewal

4. Details of previous NOC:- No: F6/DFS/MS/GH/2014/NDZ/145 dated

N/A

30/01/14.

5. Fire safety directives No.-

6. Date of inspection: 08/02/17

7. Name of the inspecting officer:- Dy.CFO Sunil Chowdhary & D.O.

Gurmukh Singh

8. Name & designation of officer From the building side:-

9. Year of construction:-

10. Applicant's letter No:-

Mr. Ankur Aggrawal.

Old building

Nil- dated 18/01/17

S.No.	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement Existing	Provided at site	Remarks MR/NMR
1.	Access to Building		1	
	1) Road width	6 mtr.	12 mtr.	MR
	2) Gate width	N/A	N/A	N/A
	3)Width of internal road	N/A	N/A	N/A
2.	Number, Width Type & Arra	angement of E	xits	
4.	A. Number of staircases			
	1. Upper floors	2 Nos.	2 Nos.	MR
	2. Basements	1 No.	1 No.	MR
	B. Width of staircase	<u> </u>		
	1. Upper floors	1.50 mtr.	1.45 mtr. &	MR (old
			1.15 mtr.	building)
	2. Basements	1 mtr.	1 mtr.	MR
	C. Protection of exits			NT/A
	1. Fire check door	N/A	N/A	N/A
	2. Pressurization	N/A	N/A	N/A
	D. No. of continuous	N/A	N/A	N/A
	staircase to terrace		7711	DT/A
	E. Width of corridor	N/A	N/A	N/A
	F. Door size	1.2 mtr.	1.2 mtr.	MR (old case)
3.	Compartmentation			
	1) Fire check door	N/A	N/A	N/A
	2) Sealing of electrical shafts	N/A	N/A	N/A
	3) Fire rating of shaft door	N/A	N/A	N/A
	4) Water curtain	N/A	N/A	N/A
	5) Fire Dampers	N/A	N/A	N/A
4.	Smoke Management System	1		1100
	1) Basements	30 a/c per hour	Mechanical	MR

X1-12

	12 ole per	Natural	10
2) Upper floors			
Fire Extinguishers			
	10 Nos.	The state of the s	MR
	ABC & CO2	ABC & CO2	MR
	Required	Provided	MR
First-Aid Hose Reel			
1) Total number of each	Required	01 no.	MR
	30 m	30 m	MR
3) Nozzle diameter	5 mm	5 mm	MR
Automatic Fire Detection &	Alarming Syste	em	
	N/A	N/A	N/A
	N/A	N/A	N/A
		N/A	N/A
			N/A
/	~		N/A
			MR
	- Millians		N/A
		1772	
	Required	Provided	MR
			MR
			N/A
	IVA	14/71	1771
	NI/A	N/A	N/A
			N/A
	IN/A	IVA	IVA
	NI/A	NI/A	N/A
	IN/sA	IN/A	IN/A
	DT/A	NI/A	NT/A
			N/A
	N/A	N/A	N/A
			1
			N/A
	N/A	N/A	N/A
	N/A	N/A	N/A
		N/A	N/A
	N/A	N/A	N/A
e) Jockey pump head	N/A	N/A	N/A
of sockey parties fleat			
	t N/A	N/A	I N/A
f) Stand by pump output		N/A N/A	N/A N/A
f) Stand by pump output g) Stand by pump head h) Auto starting/Manual	N/A	N/A N/A N/A	N/A N/A N/A
f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping	N/A	N/A	N/A
f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping 2) Terrace level	N/A N/A	N/A N/A	N/A N/A
f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping	N/A	N/A N/A	N/A N/A
	floor (2nd floor)  2) Length of hose reel hose  3) Nozzle diameter  Automatic Fire Detection &  1) Type of detectors  2) Location of main panel  3) Location of repeater panel  4) Alternate source of power  5) Hooter's Location  MOEFA  Public Address System  Automatic Sprinkler System  1) Basement  2) Upper floors  3) Sprinkler above false ceiling  Internal Hydrants  1) Size of riser/down-comer  2) Number of hydrants per floor  3) Hose box  Yard Hydrants  1) Total number of hydrants  2) Hose box  Pumping Arrangement  1) Ground level  a) Discharge of main pump  b) Head of main pump  c) Number of main pump	Fire Extinguishers  1) Total numbers  2) Types  ABC & CO2  3) ISI marking  Required  First-Aid Hose Reel  1) Total number of each floor (2 <sup>nd</sup> floor)  2) Length of hose reel hose  3) Nozzle diameter  Automatic Fire Detection & Alarming System  1) Type of detectors  2) Location of main panel  3) Location of repeater panel  4) Alternate source of power  5) Hooter's Location  MOEFA  Required  Public Address System  Automatic Sprinkler System  1) Basement  2) Upper floors  3) Sprinkler above false ceiling  Internal Hydrants  1) Size of riser/down-comer  2) Number of hydrants per floor  3) Hose box  N/A  Yard Hydrants  1) Total number of hydrants  1) Total number of hydrants  1) Ground level  A) Discharge of main pump  b) Head of main pump  c) Number of main pump  N/A	Fire Extinguishers   10 Nos.   10 Nos.   2) Types   ABC & CO2   ABC & CO2

M-13

c) Power supply	Required	Provided	MR
d) Auto starting of pump	Required	Provided	MR
Captive Water Storage for F	ire Fighting		
1) Under ground tank	N/A	N/A	N/A
capacity			DT/A
			N/A
			N/A
c) Access to tank			N/A
	5,000 Ltrs.	5,000 Ltrs.	MR
capacity		D 11.1	MD
Exit Signage.	Required	Provided	MR
Provision of Lifts.			7
a) Pressurization of lift	N/A	N/A	N/A
shaft	т.	4	27/4
b) Pressurization of lift	N/A	N/A	N/A
lobby		DT/A	NI/A
	N/A	N/A	N/A
	27/4	DI/A	N/A
			N/A N/A
	and the second s		
Stand by Power Supply			MR
Refuge Area	N/A	N/A	N/A
Total area location	N/A	N/A	N/A
Total aloa location			
Fire Control Room	N/A	N/A	N/A
	N/A	N/A	N/A
	N/A	N/A	N/A
	1877 1178 1178 1178	N/A	N/A
		N/A	N/A
Dattery Oderkap		1.	
e) Building floor plan	N/A	N/A	N/A
	tom for Droto	ption of special	N/A
Special Fire Protection Sys	tem for Frote	tion of special	11/11
	d) Auto starting of pump  Captive Water Storage for F  1) Under ground tank capacity a) Draw-off connection b) Fire service inlet c) Access to tank d) Over head tank capacity  Exit Signage.  Provision of Lifts. a) Pressurization of lift shaft b) Pressurization of lift lobby c) Communication in lift car d) Fireman's switch e) Lift signage  Stand by Power Supply  Refuge Area  Total area location  Fire Control Room a) Detector system panel b) Flow switch panel c) PA system panel d) Battery backup  e) Building floor plan	d) Auto starting of pump Required  Captive Water Storage for Fire Fighting  1) Under ground tank capacity  a) Draw-off connection N/A  b) Fire service inlet N/A  c) Access to tank N/A  d) Over head tank capacity  Exit Signage. Required  Provision of Lifts.  a) Pressurization of lift shaft  b) Pressurization of lift lobby  c) Communication in lift car  d) Fireman's switch N/A  e) Lift signage N/A  Stand by Power Supply Required  Refuge Area N/A  Total area location N/A  Fire Control Room N/A  a) Detector system panel  b) Flow switch panel N/A  c) PA system panel N/A  d) Battery backup N/A  e) Building floor plan N/A	d) Auto starting of pump Required Provided  Captive Water Storage for Fire Fighting  1) Under ground tank capacity  a) Draw-off connection N/A N/A  b) Fire service inlet N/A N/A  c) Access to tank N/A N/A  d) Over head tank capacity  Exit Signage. Required Provided  Provision of Lifts.  a) Pressurization of lift shaft  b) Pressurization of lift lobby  c) Communication in lift car  d) Fireman's switch N/A N/A  e) Lift signage N/A N/A  Stand by Power Supply Required Provided  Refuge Area N/A N/A  Total area location N/A N/A  Fire Control Room N/A N/A  a) Detector system panel  b) Flow switch panel N/A N/A  c) PA system panel N/A N/A  N/A N/A  N/A N/A  N/A  N/A  N/

The common fire protection system provided and extended in the restaurant were tested, checked at random and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter No. F6/DFS MS/GH/2014/NDZ/145 dated 30/01/14, renewal under rule35 of the Delhi Fire Service rules 2010, is recommended.

Dy. C.F.O Sunil Chowdhary Gurmukh Singh Divisional Officer