FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI

HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F-6/DFS/MS/2017/ School (128) 7

Dated: 62/03/2017

FIRE SAFETY CERTIFICATE

Issued on . 6.4.63././..... at New Delhi by.

Chief Fire Officer
Delhi Fire Service

Copy to:

The Principal, D.A.V. Public School, Tarun Enclave, Pitampura Delhi.110034.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

1. Name and address of the building:- D.A.V. Public School Located at Tarun Enclave, Pitampura Delhi.110034

2. Type of Occupancy

: Educational (Ground Floor only)

3. Type of Case

: New

4. Details of previous NOC

: NIL

5. Fire Safety directives Letter No.: DOE Circular no.3298-3398 dated 01-03-2011

6. Date of inspection

: 13-02-2017

7. Name of the Inspecting Officer: Udai vir singh, ADO (WP)

No. of Students=735 No. of class rooms=15 Plot area=2410sqm

Covered area=892sqm

8. Name and designation of Officer

: Mr Pardeep Kumar (Admin. Officer)

9. Year of Construction

from the building side

: 2005

10. Applicant's letter No.

: DAVPS/PE/SS/2017 Dated-23/01/17

0		. DAVI 5/FE/55/	25/01	/ 1 /
S No	Minimum standards on fire prevention and fire safety U/R 33	Cr.No.3298- 3398 dated 1-3- 11	Provided at site	Remarks MR/NMR
1.	Access of building		J.	
2.	 Road width Gate width Width of internal road Number, width, Type & Arrang	Accessible Accessible NA ements of exits	9mAccessible 245cmProvided NA	MR MR NA
	 a. Number of staircases Upper floors Basements b. Width of staircases Upper floors Basements c. Protection of exits Fire check door Pressurization d. No of continuous staircase to terrace e. Width Of Corridor f. Door Size 	NA N	NA	NA NA NA NA NA NA NA NA NA MR NA MR

	3.	Compartmentation				NIA			
		Fire check door		NA		NA			
		Sealing of electrical				NA		NA	
		shafts		NA		NA		NA	
		• Fire Rating of shaft door		NA		NA		NA	
		Water Curtain		NA		NA			
-		 Fire Dampers 	-	NA		NA NA		NA	
	4.	Smoke managements System	1	- 12 2		INA		NA	
		Basements		NA		NA		271	
-	-	• Upper floors		NA		NA		NA	
	5.	Fire Extinguishers				1474		NA	
		• Total numbers		04 nos.		13 provided		MD	
		 Types 		ABC & CO ₂		Provided		MR	
-		IS marking		ISI marked		Provided		MR	
6).	First – Aid Hose Reels				TTOVIUCU		MR	
		• Total numbers on each	1	NA		NA		27	
		floor		VA		NA		NA	
		 Length of hose reel 	1	VA		NA		NA	
		hose				INA		NA	
-		 Nozzle diameter 							
7.	F	Automatic fire detection and a	larm	ing system				<u> </u>	
		• Type of detectors		NA	1	NA	127		
		 Location of Main Panel 		NA		NA.		A	
		 Location of Repeater Pa 	anel	NA		NA NA	N		
		 Alternate source of pow 	er	NA		NA	N.		
		 Hooters' Location 		NA		NA	N.	and the second s	
8.		IOEFA		NA			N.		
9.	P	ublic Address System		NA		NA : 1 :	N ₂		
10.	A	utomatic Sprinkler System		IVA	p	rovided	NA.	4	
		• Basements		NA	1	ГА			
		 Upper Floor 	1	NA		A	NA		
		 Sprinkler above false 	-	NA		A	NA		
E .		ceiling		11/21	IN	A	NA	1	
11.	Int	ternal Hydrants:							
		• Size of riser/down-	NA		1) T				
		comer	NA		N.		NA		
		• Number of hydrants per	NA		N		NA		
		floor	1 11 1		N	P	NA		
1.0		 Hose Box 							
12.	Yan	rd Hydrants							
		 Total number of hydrants Hose Box NA 		NT 4			T		
				N	INA	NA		NA	
				NT.		NA			
			- 14 4	141	INA		NA		
								4 X	
		A-							
		6					10		



1	3. Pumi	oing Arrangements:				
		Ground Level				
		Discharge of main	NA	NA	27.4	
		pump	NA	NA NA	NA	
	>	Head of main pump	NA	NA NA	NA	
	>				NA	
	>		NA	NA	NA	
	>		NA	NA	NA	
	>		NA	NA	NA	
	>		NA	NA	NA	
	>	Auto Staring/Manual		NA	NA	
	>	stopping Pump House Access	NA	NA	NA	
	•	Terrace level	NA	NIA		
	>	Discharge of pump	NA	NA	NA	
	>	Head of the pump	NA	NA NA	NA	
	>	Power supply	NA	NA	NA	
	>	Auto starting of pump		NA	NA	
14	. Captiv	ve water Storage for fire fi	ghting:			
	•	Under ground tank	NA	NA	NA	
		capacity				
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Draw off connection	NA	NA	NA	
	>	Fire service inlet	NA	NA	NA	
		Access to tank	NA	NA	NA	
	•	Overhead Tank capacity	NA	NA	NA	
15	Exit Si	onage	NA	2 **		
16.	Provisi	on of Lifts	NA	NA	NA	
		Pressurization of Lift	NA	DIA	27.1	
		Shaft	334 (336)	NA	NA	
		Pressurization of lift	NA	NA	NA	
	D	lobby	NA	NA	NA	
		Communication in lift Car	NA	NA	NA	
		1				
		Fireman's Grounding Switch	NA	NA	NA	
	1	Lift Signage				
17.		y power supply	NA	NTA .		
18.	Refuge		INA	NA	NA	
		Total area	NA	DT A		
		Location	NA	NA	NA	
19.		ntrol room	IVA	NA	NA	
		D	NA	NA	DT A	
	>]		NA		NA	
		0.40	NA	NA NA	NA	
		D-44 - 1 1	NA	NA NA	NA	
) '11' D1 D1	NA	NA NA	NA	
20.		rat ra	NA NA	NA .	NA	
	Systems	for Protection of	11/1	NA	NA	
	special F	Risks, if any;			4	
		2			1	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/issue shortcomings as noted at serial numbers

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name Uda VIV Signature

Designation ADO/WP

Name

Designation