## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/Ind./2017/West/ 313

# Dated: 3 / 3 /2017

#### FIRE SAFETY CERTIFICATE

Certified that the Plot No. 10-A located at Shivaji Marg, Moti Nagar, New Delhi-110015 comprised of Basement, Ground Floor, First Floor & 2<sup>nd</sup> Floor only owned / occupied by Surinder Gugnani, has already been issued Fire Safety Certificate by this department vide letter No. F5(J)/DFS/08/684 dated 12.11.2008. The premises / Building was re-inspected by the officer concerned of Fire Service on 20.02.2017 in the presence of Mr. Dalip (CareTaker) and observed that all the fire prevention and fire safety arrangements provided in the premises found in good working condition. The premises have therefore deemed complied with rule 33 of the Delhi Fire Service Rules, 2010 and that the building / premises is fit for occupancy class **Industrial** with effect from 3 / 2017 for a period of three years in accordance with Rule 36 unless renewed under Rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010.

Issued on 3/3/7 at New Delhi by.

(ATUL GARG) CHIEF FIRE OFFICER.

Copy to :-

1. Surinder Gugnani, Plot No. 10-A, Shivaji Marg, Moti Nagar, New Delhi-110015.

2. Commissioner, NDMC Civic Centre, Minto Road, New Delhi.

## Conditions for the validity of Fire Safety Certificate:

1. All the fire safety arrangement provided their in shall be maintained in good working conditions at all times.

2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

4. Any deviation with regard to the construction etc. shall be verified by the concerned building sanctioning agency.

5. The basement shall be used strictly as per the provision of building bye laws.

6. Building sanctioning authority may verify any deviation with regard to the construction in the building, However, the fire safety recommendations issued by this department vide letter no. F6/DFS/MS/BP/2001/188 dated 25/01/2001 along with the approved plans shows only ground and two floors, whereas the building has a basement also. The use, constructional features, dimensions and legality may be checked at your level.

7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on

WWW.dfs.Delhigovt.nic.in

8. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".

## **INSPECTION REPORT**

1. Name & address of the building: Plot No. 10-A, Shivaji Marg, Moti Nagar,

New Delhi-110015.

2. Type of Occupancy : Industrial Plot Area – 1710 m<sup>2</sup>

3. Type of Case : Renewal (B., G.F., 1<sup>st</sup> Floor & 2<sup>nd</sup> Floor)

4. Details of previous NOC : No.F5(J)/DFS/08/684 dated 12.11.2008

5. Fire Safety directives Letter No.:F6/DFS/MS/BP/2001/188dated 25.01.2001 / NBC

6. Date of inspection : 20/02/2017

7. Name of the Inspecting Officer: A. K.-Jaiswal

8. Name and designation of Officer

from the building side : Mr. Dalip (CareTaker)

9. Year of Construction : 2006-07

**10.** Applicant's letter No. : SG/FB17/0901

S	Minimum standards on fire	BBL / NBC	Provided at	Remarks			
No	prevention and fire safety U/R 33	Requirements	site	MR/NMR			
1.	Access of building						
	<ul> <li>Road width</li> </ul>	6 mtr	6 mtr	MR			
	• Gate width	5 mtr	5 mtr	MR			
	<ul> <li>Width of internal road</li> </ul>	ŅA	NA	NA			
2.	Number, width, Type & Arrangements of exits						
	a. Number of staircases						
	<ul> <li>Upper floors</li> </ul>	2	2	MR			
	• Basements	2	2 2 stairs & 1 Ramp				
	b. Width of staircases	2					
	• Upper floors	1.25 mtr	1.50 mtr X 1 1.30 mtr x 1	MR			
	<ul> <li>Basements</li> </ul>	1.25 mtr	1.50 mtr X 1 1.30 mtr x 1 3.50 mtr x 1(Ramp	MR			
	c. Protection of exits						
	. • Fire check door	Required Provided		MR			
	<ul> <li>Pressurization</li> </ul>	N/A N/A		N/A			
	d. No of continuous staircase to terrace	1	1	MR			
	e. Width Of Corridor	N/A	N/A	N/A			
	f. Door Size	1.20 mtr.	1.20 mtr	MR			
3.	Compartmentation						
	<ul> <li>Fire check door</li> </ul>	Required	Provided	MR			
	<ul> <li>Sealing of electrical shafts</li> </ul>	Required	Provided	MR			
	Fire Rating of shaft door	N/A	N/A	N/A			
	Water Curtain	N/A	N/A	N/A			
	Fire Dampers	N/A	N/A	N/A			
4.	Smoke managements System						
	Basements	Required	Provided	MR			
	<ul> <li>Upper floors</li> </ul>	N/A	N/A	N/A			
5.	Fire Extinguishers						
	Total numbers	15	25	MR			
	• Types	ISI marked DCP/CO <sub>2</sub> /WC	Provided O <sub>2</sub>	MR			

6.	First – Aid Hose Reels					
	Total numbers on	1 at each floor	1 at each floor	MR		
	each floor					
	<ul> <li>Length of hose reel</li> </ul>	30Mtr.	30 mtr	MR		
	hose					
	<ul> <li>Nozzle diameter</li> </ul>	5mm.	5 mm	MR		
7. Automatic fire detection and alarming system						
	Type of detector	Smoke	Smoke	MR		
	<ul> <li>Location of Main Panel</li> </ul>	Ground Floor	Ground Floor	MR		
	Location of Repeater     Panel	Alternate Floor	Alternate Floor	MR		
	Alternate source of power supply	Required	Provided	MR		
	Hooters' Location	Ground Floor	Ground Floor	MR		
0	MOEFA	Required	Provided	MR		
8. 9.		Required	Provided	MR		
10.	Public Address System Automatic Sprinkler System	neganea				
10.	Basements	Required	Provided	MR		
	Upper Floor	Required	Provided	MR		
	• Sprinkler above false	N/A	N/A	N/A		
	ceiling					
11.	Internal Hydrants					
11.	Size of riser/down-	150 mm	150 mm	MR		
	comer	N.				
	Number of hydrants	1	1	MR		
	per floor					
	Hose Box	1	1	MR		
12	TIOSC DOX					
12.	Yard Hydrants  Total number of	Required	Provided	MR		
	hydrants	,,equiled				
	Hose Box	Required	Provided	MR		
13.	Pumping Arrangements					
	• Ground Level					
	Discharge of main pump	1620 LPM	1620 LPM	MR		
	Head of main pump	60 MH	60 MH	MR		
	Number of main pumps	1	1	MR		
	> Jockey pump out put	180 LPM	180 LPM	MR		
	<ul><li>Jockey pump head</li></ul>	60 MH	60 MH	MR		
	> Standby Pump out put	1620 LPM	1620 LPM	MR		
	Standby Pump Head	60 MH	60 MH	MR		
	> Auto Staring/Manual	Required	Provided	MR		
	stopping		\			
	Pump House Access	Required	Provided	MR		
	Terrace level					
	Discharge of pump	450 LPM	450 LPM	MR		
	> Head of the pump	40 MH	40 MH	MR		
	> Power supply	Required	Provided	MR		
	> Auto starting of pump	Required	Provided	MR		
14.	Captive water Storage for fire	fighting				
	Underground tank     capacity	50,000 lts.	50,000 ltr	MR		
	> Draw of connection	Required	Provided	MR		
	Fire service inlet	Required	Provided	MR		
	> Access to tank	Required	Provided	MR		
		20,000 ltr	20,000 ltr	MR		

- 4	N/8					
15	Exit Signage	Required	Provided	M/R		
16.	Provision of Lifts					
	<ul><li>Pressurization of Lift Shaft</li></ul>	N/A	N/A	N/A		
	<ul><li>Pressurization of lift lobby</li></ul>	N/A	N/A	N/A		
	Communication in lift Car	N/A	N/A	N/A		
	<ul><li>Fireman's Grounding Switch</li></ul>	N/A	N/A	N/A		
	> Lift Signage	N/A	N/A	N/A		
17.	Standby power supply	required	Provided	MR		
18.	Refuge Area	N/A	N/A			
	> Total area	N/A	N/A	N/A		
	> Location	N/A	N/A	N/A		
19.	Fire control room					
	Detector system panel	N/A	N/A	N/A		
	> Flow Switch Panel	N/A	N/A	N/A		
	> PA System Panel	N/A	N/A	N/A		
	Battery backup	N/A	N/A	N/A		
7	Building Floor Plans	N/A	N/A	N/A		
20.	Special Fire Protection	N/A	N/A	N/A		

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the NOC issued vide letter **No.** No.F5(J)/DFS/08/684 dated 12.11.2008 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

D. 0/(w) //w W/ )

DycFo(coZ) )

29/2

Systems for Protection of special Risks, if any;

Signature of the Inspecting Officer

Name : Ashok Kumar Jaiswal

Designation: A.D.O. (Jwala Puri)

FT Pls

F.J. let

is fut up for &

Signature pl