GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No. F6/DFs/Au/school/20/7/318

Dated: 66/03/12

FIRE SAFETY CERTIFICATE

Issued on 06 103/17 at New Delhi by

(Vipin Kental) Chief Fire Officer

To,

The Manager Rosemary Public School, A 118/5, 6 & 7, Dilshad Garden, (Near G.T.B Red Light), Delhi -110095

Copy:-

The Dy. Director of Education, B–Block, Yamuna Vihar, Delhi-110053

CONDITIONS

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate of the Director in Form `J` [sub rule (1) of rule (37)] along with a copy of this Certificate, Six Months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building : Rosemary Public School, A 118/5, 6 & 7, Dilshad

Garden, (Near G.T.B Red Light), Delhi -110095.

2. Building is comprised of : Ground plus three upper floor only

3. Type of Occupancy : Educational

4. Type of Case : Renewal

5. Details of Previous NOC letter : F-6/DFS/MS/School/2014/NDZ/88 Dt. 21/01/14

6. Fire Safety directive letter No : NBC Part-IV

7. Date of Inspection : 21/02/2017

8. Name of the Inspecting officers : ADO Vijay Bahadur

9. Name and designation of Officer:

from the building side : Mr. Guru Pratap Laumas (Manager)

10. Year of Construction : 1995

11. Applicant's letter No : Letter No. RPS/JAN-17-18 Dated- 17/01/2017

S.NO.	Minimum Standards on fire prevention and fire safety U/R33	NBC Part-IV Requirement	Provided at Site	Remarks MR/NMR		
A CONTRACTOR OF THE CONTRACTOR	Access to building					
	Road width Gate width Width of internal road	06mtr.	06mtr.	MR		
		N/A	N/A	N/A		
		N/A	NA	N/A		
2	Number, Width, Type and Arrangement of Exits					
Benny-graph or species annual description and defende of	a. Number of Staircases					
	Upper Floor	01Nos.	02Nos.	MR		
	Basement	N/A	N/A.	N/A		
	B. Width of Staircases					
	Upper Floor	1.50 mtr.	0.90 mtr & 0.80 mtr.	MR		
	 Basement 	WA	N/A	N/A		
	Protection of exits Fire check door Pressurization	N/A	N/A	N/A		
		N/A	N/A	N/A		
	d. No. of continuous staircases to terrace	01 Nos.	01 Nos.	MR		
	e. Width of Corridor	1.50mtr.	1.50mtr.	MR		
	f. Door Size	01mir.	01mtr.	MR		
3	Compartmentation.					
	Fire check door	N/A	N/A	N/A		
	 Sealing of electrical shafts 	N/A	N/A	N/A		
	 Fire rating of shaft door 	N/A	N/A	N/A		
	Water curtain	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		

4	Smoke Management System.	er recorded to the contract of		and an effective province to stability high year stable to the last province of the agriculture participations.		
The Market of the Section Sect	Basement	N/A	A L. F. R.	Section (Contraction of Contraction		
	Upper floor	N/A	N/A	N/A		
5.	Fire Extinguishers	14/14	N/A	N/A		
The second free con-	Total numbers	08 nos.	00	% @ 2 ⁵⁰		
have perchanted in the say have no replaced in the	• types	ABC /CO ₂	08 nos.	MR		
	IS marking	ISI marked	ABC /CO ₂	MR		
6	First-aid-Hose Reels	l ioi markeo	ISI marked	MR		
Tipe	The state of the s					
	Length of hose reel hose	01 No.	01 No.	MR		
	Nozzle diameter	30mtr.	30mtr.	MR		
	and for all the property on some and the property and the property of the prop	05mm	05mm	MR		
7	Automatic fire detection and alarming system.					
	 Type of detectors 	N/A	N/A	N/A		
	 Location of main panel 	N/A	N/A	N/A		
	 Location of repeater panel 	N/A	N/A	N/A		
	 Alternate source of power 	N/A	N/A	N/A		
	Hooter's location	N/A	N/A	N/A		
8	MOEFA	N/A	N/A	N/A		
9	Public address System.	Required	Provided	MR		
10	Automatic Sprinkler System.	and the second s	and a constant and the second constant and the second seco	TO ACCUSE AND A SECURITY AS AS A SECURITY ASSAULT ASSA		
	Basement	N/A	N/A	N/A		
	 upper floor 	N/A	N/A	N/A		
and in the second of the second or the second of the secon	 sprinkler above false ceiling 	N/A	N/A	N/A		
11	Internal Hydrants					
Personal Villes	size of riser/down-comer	NA	N/A	N/A		
er o demokratik de kalendare e elektronek eginek eginek eginek	Number of hydrants per floor	N/A	N/A	N/A		
	Hose Box	N/A	N/A	N/A		
12	Yard Hydrants.					
	 Total number of hydrants 	N/A	N/A	N/A		
	Hose Box	NA	N/A	N/A		
13	Pumping Arrangements.					
	Ground Level	erikkan kali beli na pianori musek kan kali selakeun meninaben katike jir oda arum na bababai mala a usekulun	erte på mantilen er und er til er flette erte med mantilette men med sydnes det dysk egen gest det er detterfolgen ende en en afterdeten.	tt med vertred et de tradection des vertregen de partiet partiet peter en det plijd in die stade til de stett de		
	Discharge of main Pump	N/A	N/A	N/A		
	> Head of Main Pump	N/A	N/A	N/A		
and the second second	Number of main pumps	N/A	N/A	N/A		
	Jockey pump out put	N/A	N/A	N/A		
	Jockey pump head	N/A	N/A	N/A		
	Standby pump out put	N/A	N/A	N/A		
	➢ Standby pump Head	N/A	N/A	N/A		
	 Auto Starting /Manual stopping 	N/A	N/A	N/A		
	➤ Pump House Access	N/A	MA	N/A		
	Terrace Level	Required	Provided	The same of the sa		
	Discharge of pump	450 Lpm.	NAME AND ADDRESS OF THE PROPERTY OF THE PROPER	MR		
	> Head of the Pump	40 M	450 Lpm. 40 M	MR		
	> Power supply	Required		MR		
	> Auto Starting of pump	Required	Electricity Provided	MR		

14	Captive Water Storage for Fire Fighting.	N/A	N/A	N/A		
	Underground tank capacity	N/A	N/A	N/A		
	> Draw-off connection	N/A	N/A	N/A		
	> Fire service inlet	N/A	N/A	N/A		
	> Access to tank	N/A	N/A	N/A		
	Overhead Tank capacity	10,000 Ltr.	10,000 Ltr.	MR		
15	Exit Signage.	Required	Provided	MR		
16	Provision of Lifts.					
	Pressurization of Lift Shaft	N/A	N/A	N/A		
	Pressurization of Lift lobby	N/A	N/A	N/A		
	Communication in lift car	N/A	N/A	N/A		
	Firemen's grounding switch	N/A	N/A	N/A		
	Lift Signage	N/A	N/A	N/A		
17	Standby power supply	N/A	N/A	N/A		
18	Refuge Area.					
	Total area	N/A	N/A	N/A		
	Location	N/A	N/A	N/A		
19	Fire Control Room					
	Detector system panel	N/A	N/A	N/A		
	Flow switch panel	N/A	N/A	N/A		
	PA system panel	N/A	N/A	N/A		
	Battery backup	N/A	N/A	N/A		
	Building Floor Plans	N/A	N/A	N/A		
20	Special Fire Protection systems for protection of special Risks, if any:	N/A	N/A	N/A		

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

Keeping in view the deemed compliance of the minimum standards on fire prevention and fire safety required under the NBC, it is recommended to issue Fire Safety Certificate.

Signature of the Inspecting Officer

Name

:- V. B. Yadav

Designation

:- A.D.O (T.Pur)