GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI-110001

No. F6/DFS/MS/Business/SZ/2017/338

Dated: 8/3/17

FIRE SAFETY CERTIFICATE

(Vipin Kental)
Chief Fire Officer
Tel: 011-23412225

Copy to:-

- 1. The Authorized Signatory, Excel Infotec Limited, 910, Ansal Bhawan, 16 K. G. Marg, New Delhi-110001
- 2. The Executive Engineer (Bldg.), Building Department, South MCD, Civic Center, Minto Road, New Delhi-110002.

Conditions for the validity of fire safety certificate:

- 1. All the means of escape/entry/exit shall be kept free from any obstruction.
- 2. All the fire safety arrangements provided therein shall be maintained in good working condition at all time as seen during inspection. Any loss of life or property due to non-functional fire safety measures shall be at the responsibility of the management.
- 3. All the staff members must know the correct method of operation of firefighting system.
- 4. The owner/ occupier shall submit a declaration every year in Form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in.
- 5. This fire safety certificate may not in any way be treated as regularization of unauthorized construction, if any.
- 6. "The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry."

INSPECTION REPORT

1. Name& address of the building: Excel Infotech Limited, 3 LSC, Pamposh Enclave, G.K.-I, New Delhi-110048

: Class-E "Business" Type of Occupancy

: Renewal 3. Type of Case

: No. F6/MS/DFS/2005/HR/2506/Com/HV/592 dated 26/10/2005 4. Details of Previous NOC

5. Fire Safety directives letter No: 12 points of 1986 Act

: 21/02/2017 Date of inspection : A. K. Malik Name of Inspecting Officer 7.

Name and designation of officers

: Mr. P. Pradhan (Executive Technical) From the building side

[2 tier Basement + GF + 4 Upper floors] : 2005 Year of Construction

10. Applicant's letter No. : Nil dated 23/01/2017, outdoor diary no. 749 dated 23/01/17 S. No. Minimum Standards on fire prevention and 12 Fire Safety Provided at site Remark							
S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Points	1 Tovided at site	MR/NMR			
•	Access to building						
	 Road width Gate width Width of internal road 	Approachable NA NA	Provided (Two sides) Boundary less building NA	MR (old case) MR MR			
2.	Number, Width, Type & Arrangement of Exits						
	a. Number of staircases						
	Upper Floors	Required	2 Nos	MR			
	Basements	Required	2 in Upper Basement 1 in Lower Basement	MR (old case)			
	b. Width of staircases	u gift	A Committee of the Comm				
	Upper Floor	Required	1.08-1.25m (Lower basement to terrace) & 0.73m (Upper basement to 4 th Floor)	MR (old case)			
	Basements	Required	1.08-1.25m & 0.73m in upper basement &1.08m in Lower Basement	MR (old case)			
	c. Protection of exits						
	Fire check door	-NA-	-NA-	-NA-			
	Pressurization	-NA-	-NA-	-NA-			
	d. No. of continuous staircases to terrace	One	One	MR			
	e. Width of Corridor f. Door Size	-NA-	-NA-	-NA-			
	f. Door Size	-NA-	1m (final exit)	-NA-			
3.	Compartmentation						
	Fire check door	Required	Provided	MR			
	 Sealing of electrical shafts 	Required	Provided	MR			
	 Fire Rating of shaft door 	-NA-	-NA-	-NA-			
	Water Curtain	-NA-	-NA-	-NA-			
	Fire Dampers	-NA-	-NA-	-NA-			
4.	Smoke Management System						
	Basements	-NA-	-NA-	-NA-			
	Upper floors	-NA-	-NA-	-NA-			
5.	Fire Extinguishers						
5.	Total numbers	Portable	60 No's	MR			
	• Types	Appliances	ABC/W. CO ₂ /CO ₂ - 10/10/10 No's	MR			
	IS marking		Yes	MR			
6.	First-Aid Hose Reels						
-	Total numbers on each floor	Required	Two	MR			
	Length of hose reel hose	Required	30m	MR			
	Nozzle diameter	Required	5mm	MR			

	CM-in Panal	Required	Ground Floor	MR _			
	Location of Main PanelLocation of Repeater Panel	-NA-	-NA-	-NA-			
	Location of Repeater FailerAlternate source of power	Required	Provided	MR			
	Hooters' Location	Required	All floors	MR			
		Required	Provided	MR			
8.	MOEFA	Required	Provided	MR			
9.	Public Address System	required					
10.	Automatic Sprinkler System	Required	Provided	MR			
	Basement Grand Floor	Required	Provided	MR			
	 Ground Floor Sprinkler above false ceiling	-NA-	-NA-	-NA-			
		-1471					
11.	Internal Hydrants	Required	100mm	MR			
	Size of riser/down-comer Size of riser/down-comer	Required	Two	MR			
	Number of hydrants per floorHose Box	Required	Two	MR			
		Required					
12.	Yard Hydrants	-NA-	-NA-	-NA-			
	Total number of hydrants	-NA-	-NA-	-NA-			
	Hose Box	-INA-					
13.	Pumping Arrangements						
	Ground Level	-NA-	900LPM	-NA-			
	Discharge of main Pump	-NA-	53m	-NA-			
	> Head of Main pump		Two	-NA-			
	Number of main pumps	-NA-	7.76	-NA-			
	> Jockey Pump out put	-NA-	-NA-	-NA-			
	> Jockey pump head	-NA-	-NA-				
	Standby Pump out put	-NA-	-NA-	-NA-			
	> Standby Pump Head	-NA-	-NA-	-NA-			
	Auto Starting/Manual Stopping	-NA-	Provided	-NA-			
	> Pump House Access	-NA-	Provided	-NA-			
	Terrace level		1 100 L DM	1.40			
	Discharge of pump	900 LPM & Jockey	900 LPM & 2 x 180 LPM	MR			
	> Head of the pump	42m	53m & 2 of 35m	MR			
	> Power Supply	Required	Provided	MR			
	> Auto Starting of pump	Required	Provided	MR			
14.	Captive Water Storage for fire fighting						
	Underground tank capacity	Required	50,000 Lts	MR			
	> Draw-off connection	Required	Provided	MR			
	Fire service inlet	Required	Provided	MR			
	> Access to tank	Required	Provided	MR			
	Overhead Tank capacity	Required	15,000 Lts.	MR			
15.	Exit Signage.	Required	Provided	MR			
16.	Provision of Lifts.						
10.	Pressurization of Lift Shaft	-NA-	-NA-	-NA-			
	Pressurization of Lift lobby	-NA-	-NA-	-NA-			
	Communication In lift Car	-NA-	Provided	-NA-			
	 Fireman's Grounding Switch 	Required	Provided	MR			
	Lift Signage	-NA-	Provided	-NA-			
17.	Standby power supply	Required	Provided	MR			
18.	Refuge Area.						
10.	> Total Area	-NA-	-NA-	-NA-			
	> Location	-NA-	-NA-	-NA-			
19.	Fire Control Room						
17.	Detector System Panel	-NA-	-NA-	-NA-			
		-NA-	-NA-	-NA-			
	 Flow Switch Panel 	1111					
	 Flow Switch Panel PA System Panel	Required	Provided	MR			

Excel Infotech Limited, 3 LSC, Pamposh Enclave, G.K.-I, New Delhi-110048

 Excel Infolecti Limited, 5 ESC, 1 and		NIA	-NA-
Building Floor Plans	-NA-	-NA-	1471
Special Fire Protection System for Protection of special Risks, if any:	-NA-	CO ₂ & DCP extinguishers are provided near LT Panel	-NA-

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules, It is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010.

Accordingly reply letter in shape of DFA is put up.

Signature of Inspecting Officer

Name: A. K. Malik

Designation: Divisional Officer

DY. CFO (SZ)

668/Chos2.

23/2/12-3368

27/2

Chossy

m.scell

FTM

27/2

Soln F.T. i's putup for sis, please.