GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, NEW DELHI-110001

No. F6/DFS/MS/SCHOOL/2017/

Dated: 2(/03/2017

FIRE SAFETY CERTIFICATE

Certified that the Govt. Sarvodaya Co-Ed. Vidyalaya (Code-1617003) located at A-2, Paschim Vihar, New Delhi-110063, comprised of Ground+1st Floor only owned / occupied by Govt. Sarvodaya, have complied with the fire prevention and fire safety of Education Circular Director accordance with requirements F6/Estate/CC/Fire/Safety/2011/3298-3398 dated 01/03/2011 and verified by the officer concerned of Fire Service on 03.03.2017 in presence of Smt. Vinita (Vice Principal) and that the building / premises is fit for occupancy class Educational (Group-B) with effect from21/03/17.....for a period of 3 (three) years in accordance with rule 36 unless renewal under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the DFS Rules, 2010 subject to conditions printed below.

Issued on _____at New Delhi by.

CHIEF FIRE OFFICER.

Copy to:-

1. Principal, Govt. Sarvodaya Co-Ed. Vidyalaya (Code-1617003), A-2, Paschim Vihar, New Delhi- 63.

Conditions for the validity of Fire Safety Certificate:-

- 1. All the fire safety arrangement provided there in shall be maintained in good working conditions at all times.
- 2. Loss of life or property due to non-functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire- fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. "The owner / Occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule37] along with a copy of this Certificate, six months prior to its expiry".
 - 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The from is available on WWW.dfs.Delhigovt.nic.in

12/12

INSPECTION REPORT

1. Name & address of the building: Govt. Sarvodaya Co-Ed. Vidyalaya

(Code-1617003), A-2, Paschim Vihar, New Delhi- 63.

2. Type of Occupancy

: Educational (G+1)

3. Type of Case

: New (As 1st floor is added on existing GF)

4. Details of previous NOC

: F6/DFS/MS/2011/2624 dated20/10/11(for GF only)

5. Fire Safety directives Letter No.: DOE Circular Dated 01/03/2011

6. Date of inspection

: 03/03/2017

7. Name of the Inspecting Officer: A. K.-Jaiswal

Plot Area – 16705 m²

8. Name and designation of Officer

from the building side : Smt. Vinita (Vice Principal)

Covered Area-4462 m²

9. Year of Construction

: GF-1984, G+1-2014

10. Applicant's letter No.: - A-2/PV/2017/377 Dated 23.01.2017

10.A	pplicant's letter No. : - A-2/PV	72017/3// Dated 23.0	1.201/	Damanlag				
S	Minimum standards on fire	DOE. Circ.	Provided at	Remarks MR/NMR				
No	prevention and fire safety	Dated	site	IVIR/INIVIR				
	U/R 33	01/03/2011						
	21 111	Requirements						
1.	Access of building	Accessible	6 mtr	MR				
	Road width	Accessible	4.5 mtr	MR				
	• Gate width	N/A	N/A	N/A				
	Width of internal road		1.7/					
2.	Number, width, Type & Arran	gements of exits						
	a. Number of staircases	2	4	MR				
	Upper floors		N/A	N/A				
	Basements	No basement	IN/A	14/7				
	b. Width of staircases	4.50	1.50 mtr x 4	MR				
	Upper floors	1.50 mtr.		NATIONAL TO THE RESERVE TO THE RESER				
	Basements	N/A	N/A	N/A				
	c. Protection of exits							
	Fire check door	N/A	N/A	N/A				
	 Pressurization 	N/A	N/A	N/A				
	d. No of continuous	One in each block	Provided	MR				
	staircase to terrace							
	e. Width Of Corridor	1.50 mtr.	Provided	MR				
	f. Door Size	1.00mtr X2	1.00mtr X2	MR				
3.	Compartmentation							
	Fire check door	N/A	N/A	N/A				
	Sealing of electrical	N/A	N/A	N/A				
	shafts							
	Fire Rating of shaft door	N/A	N/A	N/A				
	Water Curtain	N/A	N/A	N/A				
	• Fire Dampers	*						
4.	Smoke managements System		8					
т.	Basements	N/A	N/A	N/A				
	• Upper floors	N/A	N/A	N/A				
5	Fire Extinguishers							
5.	75 1 1	15	15	MR				
	Total numbers							
The second	• Types	ISI marked	Provided	M/R				
		ABC/CO ₂		2.45				
	 IS marking 	Required	Provided	M/R				
		100	A CONTRACTOR OF THE PARTY OF TH	The state of the s				
		AW						
		_^ 1	1 0	14 5 ALOS M				
		(N)	7 /					

6.	First – Aid Hose Reels			14 15		
	Total numbers on	N/A				
	each floor	IV/A	N/	A N/A		
				×		
	 Length of hose ree 	N/A	N/	A N/A		-
	hose			IN/A		
	 Nozzle diameter 	N/A	N/A	A N/A		
7						
7.	Automatic fire detection ar	d alarming s	ystem			
	 Type of detector 	N/A	N/A	N/A		
	 Location of Main Panel 	N/A	N/A	N/A		
	 Location of Repeate 	r N/A	N/A	D1/0		
	• Panel	N/A	N/A	N/A N/A		
	• Alternate source of	N/A				
	power	N/A	N/A	N/A		
	 Hooters' Location 	N/A	N/A	N/A		
8.	MOEFA	N/A				
9.	Public Address System	N/A N/A	N/A	N/A		
10.	Automatic Sprinkler System	IV/ A	N/A	N/A		
	• Basements	N/A	N/A			
	• Upper Floor	N/A	N/A	N/A		
	 Sprinkler above false 			N/A		
	ceiling		N/A	N/A		
11.	Internal Hydrants					
	• Size of riser/down-	N/A	N/A	B1 / 6		
	comer		IN/A	N/A		
	• Number of hydrants	N/A	N/A	N/A		
-	per floor					
	 Hose Box 	N/A	N/A	N/A		
2.	Yard Hydrants					
	• Total number of	N/A	B. / -			
	hydrants	14/74	N/A	N/A		
	 Hose Box 	N/A	N/A	N1/2		
3. F	Pumping Arrangements		IV/A	N/A		
•	Ground Level	N/A				
•	Discharge of main pump	N/A	N/A			
>	Head of main pump	N/A	N/A	NI/A		
7	Number of main pumps	N/A	N/A	N/A		
	Jockey pump out put	N/A	N/A	N/A N/A	-	
1	Jockey pump head	N/A	N/A	N/A N/A		
<u>A</u>	Standby Pump out put	N/A	N/A	N/A	- 15 m	
A	Standby Pump Head	N/A	N/A	N/A	-	
	Auto Staring/Manual stopping	N/A	N/A	N/A		
	Pump House Access	N/A				
	Terrace level	IV/A	N/A	N/A		
	Discharge of pump	N/A	1			
	Head of the pump	N/A	N/A	N/A		
> 1	Power supply	N/A N/A	N/A	N/A	*	
	A vate of the C		N/A	N/A		
		N/A	N/A	N/A		
. Ca	ptive water Storage for fire fi	ghting			100	
		N/A	Ν/Δ	N1/A		

		N/A	N/A	M/R	
15	Exit Signage	IV/ A			
16.	Provision of Lifts	NI/A	N/A	N/A	
	> Pressurization of Lift	N/A	1.7.		
	Shaft	D1 / A	N/A	N/A	
	Pressurization of lift	N/A	13773		
	lobby	DI/A	N/A	N/A	
	Communication in lift	N/A	14//		
	Car	N1/A	N/A	N/A	
	➤ Fireman's Grounding	N/A	1.4/		
	Switch	NI/A	N/A	N/A	
	Lift Signage	N/A		·	
17	Standby power supply	N/A	N/A	N/A	
17.	Standby power supply	N/A	N/A		
18.	Refuge Area	N/A	N/A	N/A	
	> Total area	N/A	N/A	N/A	
	> Location	1.47	•		
19.	Fire control room	N/A	N/A	N/A	
	Detector system panel	N/A	N/A	N/A	
	Flow Switch Panel	N/A	N/A	N/A	
	PA System Panel	N/A	N/A	N/A	
	> Battery backup	N/A	N/A	N/A	
	> Building Floor Plans	N/A	N/A	N/A	
20.	Special Fire Protection	IN/ A			
	Systems for Protection of				
	special Risks, if any;				

Note:-	General	requirements	for	schools	as	per	Director	of	Education	cırcular
_	dated 01	1/03/2011.					87			
1	Econe			Cl	ear.					
1.	Escape	routelinders in labor	atorie	e Nil						
2.	LPG cy	linders in labor	atoric	7' '~		1	MCB and E	ELCE	3	
3.	Electric	linders in laborations wiringConc	luit V	viring		1	VICE WILL			
	Electric	circuit					tha stai	rease	3	
1						of lin	HELLIC SLAI	1 Cas		
7.	Dicetife	meter board ent use as per B	BL 1	983		NA				
5.	Baseme	ent use as per D	be be	ord		Displ	aved			
6.	Emerge	ent use as per B ency telephone	no. Do	Jaiu		VIII				
7	Genera	ency telephone tor set				N11				
′ •										100

The fire protection systems provided in the building were tested, checked and found functional at the time of inspection.

Keeping in view of the substantial compliance of the minimum standards of fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

mulus glaws

Signature of the Inspecting Officer
Name : Ashok Kumar Jaiswal

Designation: A.D.O. (Jwala Puri)

10/8/17

CPO WEST 15/3/17

T. letter is fartup for sign- pl.