FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

PB DES MS GN 2017 W21 498 No.

Dated: 07/04/17

FIRE SAFETY CERTIFICATE

Certified that the J K Residency located at 2nd & 3rd Floors 120 Shakti Vihar Pitampura Delhi - 110034 in a building comprised of Basement +Stilt + Ground + 03 Upper Floor (Total 10 Rooms) (Five room at each 2nd & 3rd floor). The premises was inspected by the officers concerned of this department on 07-03-17 in the presence of Mr Ved Prakesh Zindal (Owner) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Residential Building" Group A of Sub Division - A 1 with effect from period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on at New Delhi by.

Chief Fire Officer Delhi Fire Service

Copy to: 1) Sh Ved Prakesh Zindal, J K Residency, 120 Shakti Vihar Pitampura Delhi – 110034

2) The Dy Health Officer, NDMC, Office of Dy Health Officer, Public Health Department Rohini Zone, Sector-V, Rohini, Delhi-85

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per BBL.
- 7. Rooms at terrace shall not be used for any purpose.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

INSPECTION REPORT

Name & address of the building: M/s J k Residency, Guest House Located at,
 120 Shakti Vihar Pitampura Delhi - 110034.

Type of Occupancy : Residential (Guest House) (Basement + Stilt + Ground + 3 Upper Floors) (Additional Rooms at terrace are sealed and not be used for any purpose)

3. Type of Case

: New

Basement= Storage

4. Details of previous NOC

: Nil

Stilt= Vacant of Ground= Vacant 1st Floor= Vacant

5. Fire Safety directives Letter No.: Nil

2nd & 3rd Floor=10 Rooms (5

Rooms at each floor)

6. Date of inspection

:07-03-2017

7. Name of the Inspecting Officer: Udaivir Singh ADO (WP)

8. Name and designation of Officer

from the building side

: Sh. Ved Parkash

9. Year of Construction

: -2009

10. Applicant's letter No.

: nil dated nil

S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requirements	Provided at site	Remarks MR/NMR	
1.	Access of building				
	 Road width 	18 m	18m provided	MR	
	Gate width	Accessible	On Road	MR	
	Width of internal road	NA	NA	NA	
2.	Number, width, Type & Arrangements of exits				
	a. Number of staircases) (D	
	Upper floors	02	3 Provided	MR	
	 Basements 	NA(Sealed not	NA	NA	
		in use)	Ÿ		
	b. Width of staircases			N E	
	 Upper floors 	1X1.25 mtrs &	1x130cm	MR	
	o oppor neers	1x1.5m	1X150cm&1X90cm		
	Basements	1x1.5m &1x1m	Provided	MR	
	c. Protection of exits				
	Fire check door	NA	NA	NA	
	 Pressurization 	NA	NA	NA	
	d. No of continuous	01	Provided	MR	
	staircase to terrace	1.5 mtrs	1.5m provided	MR	
	e. Width Of Corridor f. Door Size	1 mtrs	1m Provided (with door frame)	MR	



	Compartmentation			DIA	
•	Fire check door	NA	NA	NA	
	 Sealing of electrical shafts 	NA	NA	NA	
	 Fire Rating of shaft 	NA	NA	NA	
	door	NA	NA	NA	
	 Water Curtain 	NA NA	NA	NA	
	 Fire Dampers 	NA	1471		
4.	Smoke managements System	20 / 1	Provided	MR	
	• Basements	30 a/c per hour 12 a/c per hrs		NA	
	 Upper floors 	NA	NA	IVA	
5.	Fire Extinguishers			MD	
	Total numbers	08 nos.	Provided	MR	
	 Types 	ABC & CO ₂	Provided	MR	
	IS marking	ISI marked	Provided	MR	
6.	First – Aid Hose Reels				
υ.	Total numbers on each	Required	Provided	MR	
	floor • Length of hose reel	30m	Provided	MR	
	hose	5mm	Provided	MR	
	Nozzle diameter				
7.		NA	NA	NA	
	• Type of detectors			NA	
	• Location of Main	NA	NA	NA NA	
	Panel	NA	NA	,1424	
	 Location of Repeater Panel 	NA	NA	NA	
	 Alternate source of 			NIA	
	power	NA	NA	NA	
	 Hooters' Location 		D 11.1	MR	
8.	MOEFA	Required	Provided	MR	
9.	Public Address System	Required	Provided	IVIIC	
10.	Automatic Sprinkler System				
	Basements	Required	Provided	NA	
	 Upper Floor 	NA	NA NA	NA NA	
11	 Sprinkler above false ceiling 	NA	NA	11/7	
				3.7.4	
1.1	Size of riser/down-	NA	Provided	NA	
	comerNumber of hydrants	NA	Provided	NA	
	per floor	NA	Provided	NA	
	Hose Box	INA	Tiovided	73	
12		NIA	NA	NA	
	Total number of	NA	INA		
	hydrants • Hose Box	NA	NA	NA	



Pu	mping Arrangements:			NA
	Ground Level	NΑ	NA	INA
	• Discharge of main			NA
	pump	NA	NA	NA NA
	Head of main pump	NA	NA	IVA
	> Number of main			NA
	pumps > Jockey pump out put	NA	NA	NA NA
	t hand	NA	NA	NA
	11 Downer Out hill	NA	NA	NA
	~ 11 December Head	NA	NA	NA
	Standby Pump HeadAuto Staring/Manual	NA	NA	147
	stopping			NA
	> Pump House Access	NA	NA	1112
	• Terrace level			MR
	Discharge of pump	450 LPM	1X450 lpm	MR
	Head of the pump	40 mtrs	Provided	MR
	> Power supply	Required	Provided	MR
	> Auto starting of pump	Required	Provided	IVIIX
	Captive water Storage for fire fi	ighting:		NA
14.	Captive water Storage for the in	NA	NA	INA
	Under ground tank			NA
	capacity	NA	NA	NA NA
	> Draw off connection	NA	NA	NA NA
	Fire service inlet	NA	NA	MR
	> Access to tank	5000Ltrs	Provided	IVIK
	Overhead Tank	300	(5,000 Ltrs)	MR
	capacity	Required	Provided	IVIK
15	Exit Signage	1		NA
16.	Provision of Lifts Pressurization of Lift	NA	NA	INA
	1			NA
	Shaft intion of lift	NA	NA	NA
	> Pressurization of lift	1112		MR
	lobby Communication in lift	Required	Provided	IVIK
		71		MR
	Car Fireman's Grounding	Required	Provided	IVIK
		11		MR
	Switch	Required	Provided	
	➤ Lift Signage	Required	Provided	MR
17		Tedari		D.T.A.
18	. Refuge Area	NA	NA	NA
	> Total area	NA	NA	NA
	> Location	147.		374
19	Fire control room	el NA	NA	NA
	> Detector system pan	el NA NA	NA	NA
	Flow Switch Panel		NA	NA
	> PA System Panel	NA	NA	NA
	> Battery backup	NA NA	NA	NA
	> Building Floor Plan	s NA	1	



20.	Special Fire Protection Systems for Protection of special Risks, if any;	NA	NA	NA	
	, T				
	The fire protection syste	ems provided	in the building were	test checked and found fo	unctional at the
	time of inspection. Keeping in view the sub-	ostantial comp	oliance of the minim	um standards on fire prev	vention and fire
	safety required under the rules	it is recomm	ended to grant Fire	Safety Certificate under	rule 35 of the
	Delhi Fire Service Rule			as noted at ser	rial numbers
	Note				
	Signature of the Inspecting Office	cer (Signature of the Insp	acting Officer	
			orginature of the msp	ecting Officer	
	Name Way Vir high Designation ADO/WP	1	Name		
	Designation ADO/WP	Ι	Designation		
	,				
	10/0 ,	1./.	\bigcap		
	- Imu	19/3/12 m	X		
			4		
	N-180 (NZ)		10/8/17		.2
	CAO WOOD	July			
		Y			
		1	0 1. 1	the drugs	
	Ask him	AO	support 1	ocon y	41 .
	01 00	of ho	20- 22-5 3	rul as a	omelia
	long, go	V DC	011	00	
	earlier Mu	letter	to- 22-53	s M	
	date 27	lallh		15/3/17	
	date 27	1711-	160/19	18/11	
	0~	tipo	1.falft		
	0.14				
	DOM January	0/3/10			
		1 //			
	ADOLAM				
	AN CHI				1