## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE

NEW DELHI- 110 001

No. FG DFS (ans ) CHG/2017/52/484 FIRE SAFETY CERTIFICATE

0

Dated: 3 1/3/17

Issued on...31.... 2017 at New Delhi by

(Vipin Kental)
Chief Fire Officer
T.No.011-23412225

Copy to:- 1. Sh. Alok Sharma, General Manager (Fire & Safety), IGL Bhawan, Plot No.4, Community Centre, R.K.Puram, Sectror-9, New Delhi-110022.

2. Chief Architect, NDMC, Palika Kendra, New Delhi.

## Conditions for the validity of fire safety certificate are as under:-

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. The employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All fire fighting equipments shall be maintained in perfect working condition all time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate in form J, six month prior to its expiry.

1	Name & address of the 1 111		FOUNDIA V					
1	. Name & address of the building	: M/s	Indraprastl	na Gas Li	mited Retail Out	let (CN	G Pump)	
2	. Building is comprised of	als	sarojani Nag	gar, Ring	Road, New Delh	i.	1 /	
3	Type of Occupancy	: Ground floor only. : C.N.G. Filling Station.						
	Type of Case	: C.N	I.G. Filling	Station.				
	5. Details of Previous NOC  6. Fire Safety direction letter No.  7. No.F6/DFS/MS/2014/CNG/SZ/174, Dated 05.02.2014							
6	Fire Safety direction letter No	: NO.1	F5/DFS/MS	5/2014/CI	NG/SZ/174, Date	d 05.02	.2014.	
	an estion letter 140	. No.	F5/(2 A )/DE	/2000/BF	2/104, dated 23.03	3.2000,		
		No.	F6/DEC/M	S/2011/2	14, Dated 26.09.	2011,		
	la t	No.	E6/DEC/M	S/CNG/2	012/2095, Dated	07.06.2	2012 &	
7.	Date of Inspection	: 14.0	3 17	5/CNG/2(	)13/2596, Dated	27.11.20	013.	
8.	NI C.1 Y		pal (ADO)					
9.	Name and designation of Officer	· · · car	our (MDO)					
	from the building side	: Sh.	Ramesh Kı	ımar Sino	th (Fire Officer)			
	. Tear of Construction	: 201	2.	and ome	in (1 lie Officer)			
	. Applicant's letter No	: IGL	/F&S/2016	-17/17/62	2, dated 13.02.17.			
S.	No Minimum Standards on	fire	Require	ments/			narks	
	prevention and fire safety under ru		Existing Fire				R/NMR	
	33.		Protection	1		1011 (7	INIVIIX	
			System					
1	Access to building							
	Road width		Required		30m	MR		
	Gate width		N.A.		N.A.	N.A.	S1	
	Width of internal road		N.A.		N.A.	N.A.		
2	Number, Width, Type and Arrang	gemer	nt of Exits		14.7 (.	IV.A.		
	a. Number of Staircases		N.A.		N.A. N			
	Upper Floor		N.A.		N.A.	N.A.		
	Basement				N.A.	N.A.		
	B. Width of Staircases		N.A.		N.A.	N.A.		
	Upper Floor		N.A.		N.A.	N.A.		
	Basement c. Protection of exits		N.A. N.A.		N.A.	N.A.		
						N.A.		
-	Fire check door				N.A.	N.A.		
	Pressurization		N.A.		N.A.	N.A.		
	e. No. of continuous staircase	s to	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		N.A.	N.A.		
	terrace		IV.A.		N.A.	N.A.		
	g. Width of Corridor		N.A.		NI A			
	h. Door Size		1 m		N.A.	N.A.		
3	Compartmentation		1 111		1m	MR		
	Fire check door	T	N.A.		NI A			
	Sealing of electrical shafts Fire rating of shaft door				N.A.	N.A.		
					N.A.	N.A.		
	Water curtain		N.A.		N.A.	N.A.		
	Fire Dampers		N.A.		N.A.	N.A.		
			N.A.		N.A.	N.A.		
4	Smoke Management System.		2		Mar.			
	Basement		30a/c per h	our	N.A.	N.A.		
	Upper floor				N.A.	N.A.		
5.	Fire Extinguisher							
	Total numbers	20 no	S.	DCP75kg=07nos,10kg=15nos. MR				
	and the same of				.5kg=4nos.Total=26nos.  CDCP Type		1711 \	
	Types	CO <sub>2</sub> 8	& ,DCP CO <sub>2</sub> & D				MR	
	10						MR	
6	First-aid-Hose Reels.	151 m			M			
	Total numbers of each floor N.A.		NΙΛ				*	
	1 - 0 - 0 -	N.A.	N.A.		N.A.			
	Normale aliented to	N.A.		N.A.	N.A.			
		N.A.		N.A.		N.A.		

7	Automostic final late to	-1						
7	Automatic fire detection and alarming system in compressor and in filling area.							
	Type of detectors	Flame in	10	Gas & Flame in			MR	
			essor & portab ector with staff	ie			table	
	Location of main panel	ector with stall		gas detector with standard N.A.			NI A	
	Location of repeater panel Alternate source of power Hooters  N.A.  N.A.							N.A.
				N.A.			N.A.	
				N.A.			N.A.	
		Technician room			Technician room			MR
8	MOEFA	Require	Required		Provided			MR
9	Public address System.	N.A. N.A.			N.A.			N.A.
10	Automatic Sprinkler System.							
	upper floor  for  sprinkler above false ceiling		N.A.	N.A.		N.	N.A.	
			Water mist cum	0.	01No Provided		MR	
			foam trolley					
			Required					
			N.A.	N.A.		N.A.		
11	Internal Hydrants	1	*	A				
			N.A.	-	.A.		N.A.	
			N.A.		N.A.		N.A.	
4.0	Hose Box	N.A.	N	.A. N.A.		٩.		
12	Yard Hydrants.				y. 13			
			N.A.		.A.		N.A.	
10	Hose Box		N.A.	N	.A.	N.A	٩.	
13	Pumping Arrangements.							
			N.A.		N.A.		N.A.	
	<ul><li>Discharge of main Pu</li><li>Head of Main Pump</li></ul>		N.A.		A. *	N.A		
	Number of main pump		N.A.		Α.	N.A		
	Jockey pump out put		N.A.		A.	N.A		
	<ul><li>Jockey pump head</li></ul>		N.A.		A.	N.A		
	<ul><li>Standby pump out pur</li></ul>	Ctandby numan aut mut			V.A.		N.A.	
	Standby pump Head  Auto Starting (Manual		N.A.		N.A.		N.A.	
			N.A.		N.A.		N.A.	
	stopping		N.A.	N.				
	Prima House Access		N.A.		N.A.		N.A.	
	Terrace Level		N.A.	N.			N.A.	
	Discharge of pump		N.A.		N.A.		N.A.	
	Power supply		N.A.		V.A.		N.A.	
			N.A.		N.A.		N.A.	
			I V. / \.	IN.				
14	Captive Water Storage for Fig	re Fiahtir	na					
	Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity  No Smoking Signage (Hindi & Enlish)		N.A.		N.A.		N.A	
			5. 7654041 46504	N.A. N.A			N.A	
			N.A.		N.A.		N.A	
			N.A.		N.A.		N.A.	
15			N.A.		N.A.			
			Required				N.A MR	•
							IVIIX	
6	Provision of Lifts.							
	Pressurization of Lift Shaft		N.A.	A. N.A.		N.A.		
	Pressurization of Lift lobby		N.A.		N.A.	N.A.		
	Communication in lift car		N.A.		N.A. N.A.			
	Firemen's grounding switch			N.A.		N.A. N.A.		
	Lift Signage				14.71.	14.7.		

Indraprastha Gas Limited Retail Outlet (CNG Pump) at Sarojani Nagar, Ring Road, New Delhi.

17	Standby power supply	N.A.	Provided DG N.A.				
18	Refuge Area.		Set 50KVA	- Waynes			
	Total area Location	N.A.	N.A. N.A.				
19	Fire Control Room	N.A.	N.A. N.A.				
20							
	Detector system panel Flow switch panel PA system panel Batter backup Building Floor Plans  Special Fire Protection systems for protection of special Risks, if any:	N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
		N.A.	N.A.	N.A.			
		N.A.	Co <sub>2</sub> flooding syst connected throu	em N.A.			
		•	detectors provided each compressor.	in			

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules, the NOC issued vide letter No: F6/DFS/MS/2014/CNG/SZ/174, dated 05.02.2014, renewal under rule 37 of the Delhi Fire Service Rule 2010 is recommended.

Accordingly reply letter in shape of DFA is put up please.

Signature of the Inspecting Officer

Name: Vedpal

Designation: ADO

D.O. (S.D)

Pularh

15/3/12