## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2017/ M02/457

Dated: 28/03/17

## FIRE SAFETY CERTIFICATE

Certified that the Signature Palace Guest House located at 256-258, Ghee Mandi, Montola, Pahar Ganj, New Delhi comprised of Ground + 04 Upper floors, Ground floor (Reception), 1<sup>st</sup> floor to 3<sup>rd</sup> floor (05 guest rooms at each floor) and 4<sup>th</sup> floor (03 guest rooms), total 18 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2013/NDZ/1370 dated 31/12/13. The premises was re-inspected by the officer concerned of this department on 15/03/17 in the presence of Sh. Sushil (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 18 guest rooms only with effect from -28-(-33/+7--for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -28/03/17--at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- The Manager, Signature Palace Guest House at 256-258, Ghee Mandi, Montola, Pahar Ganj, New Delhi.

## Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

		7				
	Π	NSPECTION R	FPORT			
	INSPECTION REPORT  1. Name & address of the building Signature Palace Guest House located at					
		R Ghee Mand: M	re Palace Guest House located at , Ghee Mandi, Montola, Pahar			
		Gani N	lew Delhi.	ntola, Pahar		
	2. Type of occupancy:-					
	1	Gr. + 04 I	ntial, Sub Division-A	A-1		
		Ground f	loor (Reception) 1st floor	or to 2 <sup>rd</sup> floor (05		
		guest roo	loor (Reception), 1 <sup>st</sup> floor oms at each floor) and 4	th floor (03 guest		
	3. Type of case:-	rooms)		(03 guest		
	4 Details of provious EGG	Renewa	_			
	4. Details of previous FSC:-	No. F6/I	DFS/MS/GH/2013/N	NDZ/1370 date		
	5. Fire safety directives No N/A N/A					
,	6. Date of inspection:-	15/03/17				
	7. Name of the inspecting office	er:- Sh. Man	oj Kumar Sharma (	ADO/CC)		
From	8. Name & designation of office	er	`	, , , , , , , , , , , , , , , , , , , ,		
11011	the building side:-	Sh. Sushil (Manager)				
1/	9. Year of construction:-	2010				
10	0. Applicant's letter No:-	Nil dated	01/02/2017.			
S.No.	Minima			Old Case		
5.110.	Standards off file	Requirement/	Provided at site	Remarks		
	Prevention and fire safety	Existing fire safety		MR/NMR		
	U/R 33	arrangements				
1.	Access to Building					
	1) Road width	N/A	03 mtr. Approx	MR		
	2) Gate width	N/A	1.5 mtr.	N/A		
	3) Width of internal road	N/A	NI/A			
2.	Number, Width Type & Ar	rangement of l	Exits	N/A		
	A. Number of staircases					
	1. Upper floors	01 Nos.	01 Nos.	MD		
	2. Basements	N/A	N/A	MR		
	B. Width of staircase	11/11	IVA	N/A		
	1. Upper floors	0.80 mtr.	1 25	1.65		
	2. Basements	N/A	1.25 mtr.	MR		
	C. Protection of exits	IVA	N/A	N/A		
	1. Fire check door	N/A	DT/A			
	2. Pressurization	N/A	N/A	N/A		
	D. No. of continuous	01	N/A	N/A		
	staircase to terrace	01	01	MR		
	E. Width of corridor	N/A	DT/A			
	F. Door size		N/A	N/A		
3.	Compartmentation	01 mtr.	01 mtr.	01 mtr.		
	1) Fire check door	NI/A	27/1			
	2) Sealing of electrical shafts	N/A	N/A	N/A		
	3) Fire rating of shaft door	N/A	N/A	N/A		
-	4) Water curtain	N/A	N/A	N/A		
1	5) Fire Dampers	N/A	N/A	N/A		
İ		N/A	NT/A	NT/A		
		IN/A	N/A	N/A		
	Smoke Management System			N/A		
,		30 ACPH 12 ACPH		N/A		

Fire Extinguishers						
1) Total numbers	08 Nos.	08 Nos	MR			
2) Types			MR			
3) ISI marking			MR			
First-Aid Hose Reel	IVIIC					
1) Total number of eachfloor	01	01	MR			
			MR			
3) Nozzle diameter			MR			
1) Type of detectors			N/A			
2) Location of main panel			N/A			
3) Location of repeater panel			N/A			
		The second secon	N/A			
			N/A			
	200 1001 02 0320					
		ALCOHOL MANAGEMENT	MR			
Automatic Sprinkler System	required	TTOVIGEG	MR			
		N/A	NI/A			
			N/A			
			N/A			
	IVA	IN/A	N/A			
	N/A	NI/A	N/A			
			N/A N/A			
floor	IVA	IN/A	IN/A			
3) Hose box	N/A	N/A	N/A			
	11/11	14/11	IN/A			
	N/A	N/A	N/A			
2) Hose box			N/A			
Pumping Arrangement		1771	IVA			
1) Ground level	N/A	N/A	N/A			
			N/A			
		IVII	IN/A			
1	N/A	N/A	N/A			
			N/A			
	A		N/A N/A			
			N/A N/A			
			N/A			
g) Stand by pump head			N/A N/A			
	IVA	IN/A	N/A			
2) Terrace level		May .				
-/ 1 JII GOO 10 VOI	400 7 77 5	450 LPM	MR			
a) Discharge of numn	(15() I DNA					
a) Discharge of pump	450 LPM					
b) Head of pump	30 mtr.	30 mtr.	MR			
<ul><li>b) Head of pump</li><li>c) Power supply</li></ul>	30 mtr. Required	30 mtr. Provided	MR MR			
b) Head of pump	30 mtr. Required	30 mtr.	MR			
	2) Types 3) ISI marking First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter Automatic Fire Detection & 1) Type of detectors 2) Location of main panel 3) Location of repeater panel 4) Alternate source of power 5) Hooter's Location MOEFA Public Address System Automatic Sprinkler System 1) Basement 2) Upper floors 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box Vard Hydrants 1) Total number of hydrants 2) Hose box Pumping Arrangement 1) Ground level a) Discharge of main pump b) Head of main pump c) Number of main pum d) Jockey pump out put e) Jockey pump head f) Stand by pump output g) Stand by pump head h) Auto starting/Manual stopping	1) Total numbers 2) Types 3) ISI marking Required First-Aid Hose Reel 1) Total number of eachfloor 2) Length of hose reel hose 3) Nozzle diameter 05 mm  Automatic Fire Detection & Alarming Syst 1) Type of detectors N/A 2) Location of main panel N/A 3) Location of repeater panel Alternate source of power 5) Hooter's Location N/A  MOEFA Required Public Address System Automatic Sprinkler System 1) Basement N/A 2) Upper floors N/A 3) Sprinkler above false ceiling Internal Hydrants 1) Size of riser/down-comer 2) Number of hydrants per floor 3) Hose box N/A  Yard Hydrants 1) Total number of hydrants 1) Total number of hydrants 1) Ground level A) Discharge of main pump b) Head of main pump C) Number of main pump b) Head of main pump c) N/A C) Number of main pump d) Jockey pump out put e) Jockey pump head f) Stand by pump head h) Auto starting/Manual stopping	1) Total numbers			

Mis

14.	Captive Water Storage for F	ire Fighting	DI/A	N/A
	1) Under ground tank capacity	N/A	N/A	N/A
	a) Draw-off connection	N/A	N/A	N/A N/A
	b) Fire service inlet	N/A	N/A	
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank	5000 ltr.	5000 ltr.	MR
	capacity		2 11 1	MD
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.			
	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Sys Risk, if any: One ABC type felect. Panel.	tem for Proteire extinguisher	ction of special found provided near	MR

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/GH/2016/2082 dated 31/08/2016 have been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2013/NDZ/1370 dated 31/12/2013 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Designation: - ADO (CC)