## GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS, DELHI FIRE SERVICE, NEW DELHI-110001

No.F6/DFS/MS/GH/2017/472

Dated: 30103 2017

## FIRE SAFETY CERTIFICATE

Certified that the Stay Inn Guest House, 3649, Gali Ram Nath Patwa, Pahar Ganj, New Delhi-110055 comprised of Ground + 4 Upper Floors (Ground floor – Reception + 01 guest rooms + 01 office, 1<sup>st</sup> floor to 4<sup>th</sup> floor 04 guest rooms at each floor total 17 guest rooms have complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of Delhi Fire Service on 11/02/17 in the presence of Mr. Vinod Gupta that the premises is fit for occupancy of class Residential Group-A for total 17 guest rooms only as above with effect from 20103 12017 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010 mentioned below.

Issued on ... 30 03. ... 2017.... at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service Ph-011-23412225

- Copy to: (1) The Joint Commissioner of Police (Lic.), 1<sup>st</sup> Floor, Police Station. Defence Colony, New Delhi.
  - (2) The Licensee,Stay Inn Guest House,3649,Gali Ram Nath Patwa,Pahar Ganj,New Delhi-110055.
  - (3) Commissioner MCD, NDMC, Civic Centre of for information & n/a please.

## Condition:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. The means of escape shall be kept unobstructed / unlocked & remain available for speedy evacuation of occupants in case of an emergency.
- 3. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 4. The trained fire fighting staff should be available round the clock.
- 5. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

-11/1-

INSPECTION REPORT

1.Name & address of the building:
Stay Inn Guest House, 3649, Gali Ram Nath Patwa, Pahar Ganj, New Delhi-110055

2. Type of occupancy:
Residential Group A-1 Ground+ 4 Upper Floors Gr. floor –Reception + 01 guest rooms + 01 office 1st to 4th floor 4 guest each floor (Total -17 guest rooms)

3. Type of case:
Fresh

7. Name of the inspecting officer:- D.O. Gurmukh Singh

8. Name & designation of officer
From the building side:9. Year of construction:Prior to 2004

10.	Applicant's letter No:-	144-48/Join	nt CP/Lic (H) da	ited 10	0/01/2017	
7683- 84S.N	Minimum Standards on fire Prevention and fire safety U/R 33	Requirement	Provided at site (PSS)		Remarks MR/NMR	
0.	U/K 33		(155)			
1.	Access to Building	*	9		W.	
0	1) Road width	Less then 6 Mtr.	02 Mtr.		Per MPD-2021 7.2. MR	
	2) Gate width	N/A	N/A	N/	N/A	
	3)Width of internal road	N/A	N/A	N/	'A	
2.	Number, Width Type & Arran	gement of Exits				
	A. Number of staircases				u	
	1. Upper floors	01 No	01 No.		MR	
	2. Basements	N/A	N/A		N/A	
	B. Width of staircase			•		
	1. Upper floors	1.50 Mtr.	1.50 Mtr.	18 J	MR	
	2. Basements	N/A	N/A	_	N/A	
	C. Protection of exits					
	1. Fire check door	N/A	N/A		N/A	
	2. Pressurization	N/A	N/A		N/A	
	D. No. of continuous staircase to terrace	N/A	N/A		N/A	
	E. Width of corridor	N/A	N/A	N/A		
	F. Door size	1.0 Mtr.	1.0 Mtr.			
3.	Compartmentation					
	1) Fire check door	N/A	N/A		N/A	
	2) Sealing of electrical shafts	N/A	N/A		N/A	
	3) Fire rating of shaft door	N/A	N/A		N/A	
	4) Water curtain	N/A	N/A		N/A	
	5) Fire Dampers	N/A	N/A		N/A	
4.	Smoke Management System					
	1) Basements	30 ACPH	N/A		N/A	
	2) Upper floors	12 ACPH	Natural		MR	
5.	Fire Extinguishers					

-N/2-

	1) Total numbers	10 Nos.	10 Nos	MR		
	2) Types	ABC & CO2	ABC & CO2	MR		
	3) ISI marking	Required	Provided	MR		
6.	First-Aid Hose Reel					
	1)Total number at each floor	01 No.	01 No	MR		
	2) Length of hose reel hose	30 Mtr.	30 Mtr.	MR		
	3) Nozzle diameter	5 mm	5 mm	MR		
7.	Automatic Fire Detection & Alarming System					
	1) Type of detectors	N/A	N/A	N/A		
	2) Location of main panel	N/A	N/A	N/A		
	3) Location of repeater panel	N/A	N/A	N/A		
	4) Alternate source of power	N/A	N/A	N/A		
	5) Hooter's Location	N/A	N/A	N/A		
8.	MOEFA	N/A	N/A	N/A		
9.	Public Address System	N/A	N/A	N/A		
10.	Automatic Sprinkler System					
	1) Basement	N/A	N/A	N/A		
	2) Upper floors	N/A	N/A	N/A		
	3) Sprinkler above false	N/A	N/A	N/A		
1.1	ceiling					
11.	Internal Hydrants	27/1		22//		
	1) Size of riser/down-comer	N/A	N/A	N/A		
	2) Number of hydrants per	N/A	N/A	N/A		
	floor	NT/A	27/4	27/4		
12.	3) Hose box	N/A	N/A	N/A		
12.	Yard Hydrants	NI/A	NT/A	NT/A		
	1) Total number of hydrants 2) Hose box	N/A N/A	N/A N/A	N/A N/A		
13.		IN/A	IN/A	N/A		
13.	Pumping Arrangement	NT/A	NI/A	NT/A		
	1) Ground level	N/A	N/A	N/A		
	a) Discharge of main	N/A	N/A	N/A		
	b) Head of main pump	N/A	N/A	N/A		
	c) Number of main pump	N/A N/A	N/A	N/A		
	d) Jockey pump out put	N/A N/A	N/A N/A	N/A N/A		
	e) Jockey pump head	N/A N/A	N/A N/A	N/A N/A		
	f) Stand by pump output	N/A	N/A	N/A		
	g) Stand by pump head	N/A	N/A	N/A		
	h) Auto starting/Manual	N/A	N/A	N/A		
	stopping	1 1/1 1	11/11	1 1/11		
	2) Terrace level		1			
	a) Discharge of pump	450 LPM	450 LPM	MR		
	b) Head of pump	30 Mtr.	30 Mtr.	MR		
	c) Power supply	Required	Provided	MR		
	d) Auto starting of pump	Required	Provided	MR		
14.	Captive Water Storage for Fire		110 11404	17111		
14.	Sapara in account of the late	N/A	N/A	N/A		

	capacity			1.5
	a) Draw-off connection	N/A	N/A	N/A
	b) Fire service inlet	N/A	N/A	N/A
	c) Access to tank	N/A	N/A	N/A
	d) Over head tank capacity	5,000Ltr.	5,000 Ltr.	MR
15.	Exit Signage.	Required	Provided	MR
16.	Provision of Lifts.		*	
1	a) Pressurization of lift shaft	N/A	N/A	N/A
	b) Pressurization of lift lobby	N/A	N/A	N/A
	c) Communication in lift car	N/A	N/A	N/A
	d) Fireman's switch	N/A	N/A	N/A
*	e) Lift signage	N/A	N/A	N/A
17.	Stand by Power Supply	Required	Provided	MR
18.	Refuge Area	N/A	N/A	N/A
	Total area location	N/A	N/A	N/A
19.	Fire Control Room	N/A	N/A	N/A
	a) Detector system panel	N/A	N/A	N/A
	b) Flow switch panel	N/A	N/A	N/A
	c) PA system panel	N/A	N/A	N/A
	d) Battery backup	N/A	N/A	N/A
	e) Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection Syste any:	m for Protection of s	special Risk, if	N/A

The fire protection systems provided in the building were tested, checked at random and found

functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules, grant of fire Safety Certificate, under rule 35 of the Delhi Fire Service Rules 2010, is recommended please.

> Gurmukh Singh Divisional Officer