GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001 Fax No. 011-23412593, Ph. 011-23412225

No. F6/DFS/MS/EH/2017/SZ/

Dated: 1.8./4./1.7...

FIRE SAFETY CERTIFICATE

Certified that M/s Suribachi (Additional) Restaurant (A Unit of Royal Eastern Hospitality Pvt Ltd.) located at T-540, Malviya Nagar, New Delhi-110017, comprised of Ground floor only was granted FSC by this department vide letter No. F.6/DFS/MS/EH/2014/SZ/561 dated 02/05/2014. The premises was re-inspected by the officer concerned of this department on 15/03/2017 in the presence of Mr. Manoj Kumar (Manager) of the restaurant and observed that the said building/premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building/premises is fit for occupancy class-D "Assembly Building" (Restaurant) as above with effect from 19/4/17 for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on 99417 at New Delhi by

(Vipin Kental) Chief Fire Officer

Copy to: -

- 1. M/s Suribachi (Additional) Restaurant, T-540, Malviya Nagar, New Delhi-110017 o/c
- 2. The Joint C.P. (Lic.), First Floor, PS Defence Colony, New Delhi-110049
- 3. The DHO (Central Zone), South MCD, Health Deptt, Lajpat Nagar, New Delhi-24

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety and means of escape facilities shall be maintained in good working condition at all time. Any lapse rendering the fire safety or means of evacuation facilities non-functional shall be the responsibility of the management.
- 2. Building Sanctioning authority may verify any deviation with regard to construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null & void.
- 3. The staff shall be trained for operating fire fighting system and mock evacuation drill be conducted at regular interval and record be maintained.
- 4. The basement shall be used strictly as per the provisions of Building Bye Laws.
- 5. The Owner/Occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules, 2010. The form is available on www.dfs.delhigovt.nic.in.
- 6. The Owner/Occupier shall apply for renewal of this Fire Safety Certificate to the Director in the form 'J' [sub rule (1) of rule 37] along with copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in.

1	Name & Address of the Building	ON REPORT M/s Suribachi (Additional) Restaurant	T-540.	
1	Name & Address of the Dunding		New Delhi-110017	, 1 0 10,	
		(A Unit of Days	al Eastern Hospitality P	out I td)	
	Type of Occupancy	Group-D Assembly Building. (Restaurant)			
	Building comprised of	Ground floor onl	y		
	Type of Case	Renewal	DI 1001 4/07/E/1 D-4-10	2.05.2014	
and the second second second second	Details of Previous NOC		EH/2014/SZ/561 Dated 0		
	Fire Safety Directives Letter No		-III/356-359 dated 22-03	-2005	
	Date of Inspection	15/03/2017			
	Name of the Inspecting Officers	ADO R.N. Singh			
9	Name & Designation of Officers	Mr. Manoj Kumar (Manager)			
	from the building side	1001 D	Leading to the lead of the leading to the leading t	um dan ama nas	
10	Year of construction		at is running in two sections	under one roc	
11	Applicant letter No.	Nil Dated 27/02			
S. No	Minimum standards on Fire Prevention	Old NOC	Provided at Site	Remarks	
	and Fire Safety U/R 33	Dt. 30-12-2005	and the second section in	MR/NMR	
		requirement			
1	Access to Building.			1.00	
	Road width	Required	15 mtr	MR	
	Gate width	N/A	N/A	N/A	
1	Width of internal road	N/A	N/A	N/A	
2	Number, width, type and arrangements of	f exits.			
-	a. Number of Staircase				
	Upper floors	N/A	N/A	N/A	
-	Basement floor	N/A	N/A	N/A	
	b. Width of Staircase	- Statut			
-	Upper floors	N/A	N/A	N/A	
	Basement floor	N/A	N/A	N/A	
	c. Protection of exits	200	THE RESIDENCE AND A SECOND		
	Fire check door	N/A	N/A	N/A	
	Pressurization	N/A	N/A	N/A	
		N/A	N/A	N/A	
		N/A	N/A	N/A	
	e. Width of corridor f. Door size	Required	1.40m, 1.06m, 1.04 &	MR	
لأغاجينا	1. Door size	Required	0.80m	(old case)	
3	Compartmentation.				
	Fire check door.	N/A	N/A	N/A	
	Sealing of electrical shafts.	N/A	N/A	N/A	
	Fire rating of shaft door.	N/A	N/A	N/A	
	Water curtain	N/A	N/A	N/A	
	Fire dampers.	N/A	N/A	N/A	
4.	Smoke Management system.				
	Basement	30 a/c per hour	N/A	N/A	
	Upper floors	12 a/c per hour	N/A	N/A	
5.	Fire Extinguishers.				
	Total numbers	ISI marked	15 No's	MR	
	• Types		ABC-10 & Co2-05	MR	
	ISI Marking		Provided	MR	
7		1	and the state of the		
6.	First Aid Hose Reels.				
6.			One	MR	
6.	Total numbers on each floor. Length of hose-reel hose.	Hose Reels	One 30 m	MR MR	

- 1				
	omatic fire detection & alarming syste Type of detectors	m. N/A	N/A	N/A
1 3 5 10 1	Type of detectors Location of Main Panel	N/A	N/A	N/A
	the particular of the state of	N/A	N/A	N/A
te la	Location of Repeater Panel	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
	Hooter's location		Provided	M/R
8. MO		Required N/A	N/A	N/A
	lic Address System omatic Sprinkler System	IN/A	IV/A	IN/A
	Basement	N/A	N/A	N/A
		N/A	N/A	N/A
	opper moore	N/A	N/A	N/A
11 Tu4s	Sprinkler above false ceiling	N/A	IVA	IVA
	rnal Hydrants.	N/A	N/A	N/A
	Size of Riser/Down-comer	N/A	N/A	N/A
	Number of Hydrant per floor	N/A	N/A N/A	N/A
	Hose box.	IN/A	IV/A	IN/A
	d Hydrants.	N/A	N/A	N/A
	Total number of hydrants.		N/A N/A	N/A N/A
	2. Hose box.	N/A	N/A	N/A
	ping arrangements.			
•	Ground Level	N//A	27/4) DT/A
	Discharge of main pump.	N/A	N/A	N/A
	➤ Head of main pump.	N/A	N/A	N/A
	Number of main pumps.	N/A	N/A	N/A
	Jockey Pump output.	N/A	N/A	N/A
	Jockey Pump head.	N/A	N/A	N/A
	Standby Pump output.	N/A	N/A	N/A
	Standby Pump head.	N/A	N/A	N/A
	Auto Starting / Manual Stopping.	N/A	N/A	N/A
	> Access to pump house	N/A	N/A	N/A
	Terrace Level	450 1 01 6	COO O O40 I D	1.00
	Discharge of pump.	450 LPM	600 & 840 LP	MR
	> Head of pump.	39 mtr	26m & 23.5m	MR
n sin	Power supply.	Required	Provided	MR
	> Auto starting of pump.	Required	Provided	MR
	tive water storage for Fire Fighting.	27/4	TAX OF TA	DI/A
•	Underground tank capacity.	N/A	N/A	N/A
	> Draw-off connection.	N/A	N/A	N/A
	Fire Service Inlet.	N/A N/A	N/A	N/A
	Access to tank.		N/A 5000 Ltr.	N/A
	Overhead tank capacity.	5,000 Ltr		M/R
	Signage.	Required	Provided	M/R
	vision of Lifts.	N/A	N/A	N/A
	• Pressurization of lift shaft.	N/A N/A	N/A N/A	N/A N/A
	Pressurization of lift lobby.	N/A N/A	N/A N/A	N/A N/A
	Communication in lift car.			N/A N/A
	• Fireman's switch.	N/A	N/A	
	Lift signage.	N/A	N/A	N/A
	idby Power Supply	Required	Provided	MR
	uge Area	27/4	NYA	18 27/1
	Total area	N/A	N/A	N/A
	• Location	N/A	N/A al) Restt. T-540, Malvi	N/A

Renewal

M/s Suribachi (Additional) Restt. T-540, Malviya Nagar, ND

19.	Fire Control Room.			
	Detector System Panel.	N/A	N/A	N/A
	Flow Switch Panel.	N/A	N/A	N/A
	PA system Panel.	N/A	N/A	N/A
	Battery backup	N/A	N/A	N/A
	Building floor plan	N/A	N/A	N/A
20.	Special Fire Protection System for the	he Protection of sp	ecial Risk, if any:	N/A

The Fire protection systems provided in the building were tested/ checked and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F6/DFS/MS/EH2014/SZ/561 dated 02-05-2014, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly, DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name

: R.N. Singh

Designation: ADO M/s Suribachi (Additional) Restt. T-540, Malviya Nagar, ND

Renewal

Div. Officer (SD)

Cho (St) M. SCOU FTM.

F. T lefter is put up for sign ple

cko/sp2

M. SCOU WAY.