FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F-6/DFS/MS/SCHOOL/2017/ 1070

Dated: 26 / 4 /2017

FIRE SAFETY CERTIFICATE

Issued on 26 1.4. (17..... at New Delhi by.

(Afth Garg)
Chief Fire Officer
Delhi Fire Service

Copy to:-

The Principal, Govt. Sarvodaya Kanya Vidyalaya, Ashok Vihar, Phase – II, New Delhi – N0052.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- **4.** Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 8. All the exits must be kept free from any obstructing.

Ashok Vihar, Phase – II, New Delhi – 110052. Type of Occupancy: Educational, Three Blocks(BL-1=G+2UF & BL-2,3=G+1 UF Only), : New Type of Case 4. Details of previous NOC : Nil 5. Fire Safety directives Letter No.: DOE circular dated 01/03/2011 No. of Students=2241 : 06-04-2017 6. Date of inspection No. of class rooms=48 Plot area=11401.50 sqm 7. Name of the Inspecting Officer: Udai vir Singh, ADO (WP) Covered area=5067.52 sqm 8. Name and designation of Officer :Ms. Kamal Jeet Kaur (Principal) from the building side 9. Year of Construction : 1976 : Nil Dated 08-03-2017 10. Applicant's letter No.

S No	Minimum standards on fire prevention and fire safety U/R 33	Cr.No.3298- 3398 dated 1- 3-11		Provided at site		Remarks MR/NMR			
1.	Access of building			V 15					
	Road width	Accessible		8m Provided 360cm Provided		MR			
	Gate width					MR			
	 Width of internal road 			NA	NA				
2.	Number, width, Type & Arrangements of exits								
	a. Number of staircases								
	• Upper floors	BL-1=2 BL-2=1 BL-3=1 NA		BL-1=3 BL-2=1 BL-3=1		MR			
	Basements			NA		NA			
	b. Width of staircases	2 12 2		THE NAME OF THE					
	Upper floors	1.5m BL-1=1x140cm,2x1.25c BL-2=1x150cm BL-3=1x160cm NA NA		x1.25cm	m MR				
	Basements					NA			
	c. Protection of exits								
	Fire check door	NA NA 1		NA		NA			
	Pressurization			NA		NA			
	d. No of continuous staircase to terrace			Provided		MR			
	e. Width Of Corridor			Provided		MR			
	f. Door Size	100cm		100cm		MR			
3.	Compartmentation				4.4				
	Fire check door	NA NA		NA		NA			
	Sealing of electrical shafts			NA		NA			
-	Fire Rating of shaft	NA		NA		NA			
	door	NA		NA		NA .			
	Water CurtainFire Dampers	NA		NA		NA			
4.	Smoke managements System	- Carlon							
	Basements	NA		NA		NA			
	Upper floors	NA		NA	NA				
5.	Fire Extinguishers								
* 1	Total numbers	20nos.		27 Provide	ed	MR			
		ARC & C	CO_2	Provided		MR			

6.	First – Aid Hose Reels	In	Block=1	9			
	Total numbers on each	3 30m 5mm		Provided	MR		
	floor			Provided	MR		
	Length of hose reel hoseNozzle diameter			Provided	MR		
	Automatic fire detection and ala	and the same of th					
7.		NA		NA	NA		
	Type of detectors CMain Popul		NA	NA	NA		
	Location of Main Panel GRangeton Population	Panel NA		NA	NA		
	Location of Repeater Par			NA	NA		
	 Alternate source of power Hooters' Location 		NA	NA	NA		
				NA	NA		
8.	MOEFA	NA NA		NA NA	NA		
9.	Public Address System	NA NA		INA	1111		
10.	Automatic Sprinkler System	NA		NA	NA		
	Dascinents			NA	NA		
	• Opper Floor	NA					
	Sprinkler above false ceiling	NA		NA	NA		
11.	Internal Hydrants: In Block =	1	- 1 - 13		3		
	Size of riser/down- com		NA	Provided	NA		
	 Number of hydrants per 		NA	Provided	NA		
	Hose Box		NA	Provided	NA		
12.	Yard Hydrants						
12.	• Total number of	NA		NA	NA		
	hydrants						
	Hose Box	NA		NA	NA		
	11050 201			,			
13.	Pumping Arrangements:	173					
	Ground Level				- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1		
	Discharge of main	NA		NA	NA		
	pump						
	> Head of main pump	NA NA		NA	NA		
	> Number of main			NA	NA		
	pumps				N.T.A.		
	Jockey pump out put	NA NA NA NA		NA	NA		
	Jockey pump head			NA	NA		
	> Standby Pump out put			NA	NA		
	Standby Pump Head			NA	NA		
14	Auto Staring/Manual			NA	NA		
	stopping stopping	11/1					
	> Pump House Access	NA		NA	NA		
	Terrace level	1121					
	Discharge of pump	450 lpm		Provided	MR		
	> Head of the pump	40Mtr Required		Provided	MR		
	> Power supply					Provided	MR
	> Auto starting of pump			Provided	MR		
1.4			required				
14			~D.	NA	NA		
4	Under ground tank connectty	11/1					
	capacity Draw off connection	NA	8	NA NA	NA		
	Fire service inlet	NA NA		Provided	NA		
		NA	1111		NA		
	Access to tankOverhead Tank		000Ltr	Provided	MR		
		10,0	OOLU	Tiovided			
15	capacity Exit Signage	Reg	uired	Provided	MR		

16.	Provision of Lifts							
	Pressurization of Lift S.	haft	NA		NA	NA		
	Pressurization of lift lol	oby	NA		NA	NA		
	Communication in lift (Car	NA		NA	NA		
	Fireman's Grounding S	inding Switch		NA		NA		
	Lift Signage		NA		NA	NA		
17.	Standby power supply		NA		NA	NA		
18.	Refuge Area							
	Total area		NA		NA	NA		
20	> Location		NA		NA	NA		
19.	Fire control room							
	Detector system panel	NA NA NA		NA		NA		
	Flow Switch Panel			NA NA		NA		
	> PA System Panel					NA		
	Battery backup	NA		NA		NA		
	Building Floor Plans	NA		. NA		NA		
20.	Special Fire Protection	NA		NA		NA		
	Systems for Protection of							
•	special Risks, if any;		-	-	*			

Note:-General requirements for schools as per Director of Education circular dated 01/03/2011.

- 2. LPG cylinders in laboratories; Not being used
- 3. Electric wiring ...open Wiring...... MCB and ELCB Electric circuit
- 4. Electric meter board under the staircase.....
- 5. Basement use as per BBL 1983 ... NA
- 6. Emergency telephone no. board Displayed...
- 7. Generator set out side school building

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

Keeping in view the substantial compliance of the minimum standards on fire prevention and fire safety required under the rules it is recommended to grant Fire Safety Certificate under rule 35 of the Delhi Fire Service Rules 2010/issue serial numbers shortcomings as noted at

Note:- Earlier the building was comprised of Two Block(Bl-l= G+2UF & Bl-2= Ground floor only) but now the Block-2 has been demolished and two New blocks of Ground pus one upper floor have been constructed.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name

Designation

Name Volar Vir digh

Designation

Designation

Designation

Muler Aly/37