FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/school/2017/12/627

Dated: 3 /04/2017

FIRE SAFETY CERTIFICATE

Issued on ... 23. 1.7... at New Delhi by.

(Atul Garly) Chief Fire Officer Delhi Fire Service

Copy to:

The Principal, Jaspal Kaur Public School, Shalimar Bagh, B-Pashchim, Delhi – 110088.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

1. Name & address of the building: Jaspal Kaur Public School, located at Shalimar Bagh, B-Pashchim, Delhi – 110088.

2. Type of Occupancy : Educational (Basement +Ground + 3 Upper Floor)

3. Type of Case

: Renewal

4. Details of previous NOC

: F6/DFS/MS/2008/2477 Dated 01/09/2008

5. Fire Safety directives Letter No.: Cir. no262-362 dated 17/01/2005

6. Date of inspection

:24/04/2017

7. Name of the Inspecting Officer: ADO (WP)

No. of Students=2435 No. of class rooms=102

Plot area=4.45 Acre

8. Name and designation of Officer

Covered area=8800 sqm

from the building side

: Sh.G. Mathew (Principal)

9. Year of Construction

: 1987(As declared by school authority)

10. Applicant's letter No.

:JKPS/LB23/DFS/2016 Dated-21/01/2016

				23/121	6/2016 Dated-21/0	1/201	0	
S	Minimum standards on fire	Cir 2	62-362	Provided at site		Remarks		
No	The state of the statety	dated		110 vided at Site			R/NMR	
1	U/R 33	17/01/2005				1413	COTAINIC	
1.	Access of building		6		0			
		Acces		6m Provided		MR		
		Acces	sible Provided (On Road)		ed (On Road)	MR		
	Width of internal road	NA		NA		NA		
2.	Number, width, Type & Arrange	ements of exits						
	a. Number of staircases					T -		
	• Upper floors		5+ Ramp	Provided			MR	
	BasementsWidth of staircasesUpper floors		02	02Provided		MR		
				1	· raca	IVIIV		
			3x150cm	1x14 1x22 Floo			MR(old case)	
	c. Basements		1x150cm& 1x100cm	2x140cm (Up to 1 st Floor) Basement =1x115cm &1X107CM			MR (Being	
	d. Protection of exits						old case)	
	 Fire check door 		NA	•	NA		214	
	 Pressurization 		NA		NA		NA	
	e. No of continuous staircase to		01		Provided		NA	
	terrace		01		Tiovided		MR	
	f. Width Of Corridor g. Door Size		2mtrs		235 cm		MR	
			100cm		110cm Provided		MR	
			Multi activity hall= 2m(At 1 st Floor)		Multi activity hall= 8x2m		1711	
3.	Compartmentation		/					
	Fire check door		NA	NA			NA	
	 Sealing of electrical shafts 		NA		NA		NA	
	 Fire Rating of shaft door 		NA				NA	
	Water Curtain	-	NA		NA			
T.B	 Fire Dampers 	-	NA		NA NA		NA	
	Smoke managements System				11/1		NA	
1	Basements		Required		Exhaust Fan		MD	

	Total numbers		29 nos.		Provided	-	MR		300
	Types		ABC &		Provided		MR		
	IS marking		ISI mar		Provided		MR		
6.					TTOVIGOU		IVIIC		
	Total numbers on each	ch floor	03		Provided		MR		
	• Length of hose reel h		30m		Provided		MR		
	Nozzle diameter	050	5mm		Provided		MR		
7.		alarming			Trovided		IVIIX		
	Type of detectors		NA	NA		NA			
	Location of Main Par	_	NA	NA		NA NA	,		
	 Location of Repeater 		NA	NA		NA NA	-		
	Alternate source of po	the secondary and	NA	NA		NA			
	Hooters' Location		NA	NA		NA			
8.	MOEFA		NA	NA					
9.	Public Address System		Required	Provided		NA			
10		1	cequired	TTOVIGEO		MR			
	Basements	Requ	ired	Provided		MR			
	 Upper Floor 	NA	irea	NA	•	NA NA			
	 Sprinkler above false 	NA		NA		NA NA			
	ceiling			11/1		INA			
11.									
	Size of riser/down	100m	m	Provided		MR			
	comer	_ 53111		210 11000		IVII			
	 Number of hydrants 	03		Provided		MR		_	
	per floor					IVIIC			
	Hose Box	03	(k	Provided		MR			
12.	Yard Hydrants	17				1,111			
	 Total number of 	NA		NA		NA			
	hydrants			10. 900, 00		1111			
	Hose Box	NA		NA	7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	NA			
13.	Pumping Arrangements:								
	Ground Level					0			
	 Discharge of main 	NA		NA		NA			
	pump								
	Head of main pump	NA		NA		NA			
	Number of main	NA		NA		NA	x 10 3.		
	pumps								
	Jockey pump out put	NA	V	NA		NA			
	> Jockey pump head	NA		NA		NA	4		
	Standby Pump Hand	NA		NA		NA			
	Standby Pump HeadAuto Staring/Manual	NA		NA		NA			
	stopping	NA		NA		NA			
2	Pump House Access	NIA		NT 4		_ =====================================			
	Terrace level	NA		NA		NA			
	Discharge of pump	450 1	22	0.1 0 45	0.1	1,			
	8- or bamb	450 lpi 180 lpi		Only 2x45	U lpm	MR	2.		
	➤ Head of the pump	40Mtr	.11	provided a Provided	t 3 floor) (D			
	> Power supply	Requir	ed	Provided		MR			
		Requir		Provided		MR			
	Auto starting of pump	_	cu	riovided		MR			
14.	Captive water Storage for fire	fighting:							TO SECURITY OF
	Under ground tank	NA		NA		NA			
la serie	capacity		*						STATE OF
	Draw off connection	NA		NA		NA			The same
	Fire service inlet	NA		NA		NA			
	Access to tank	NA		NA		NA			
924	Overhead Tank	10,000	Ltrs	Provided 1	8,000 ltrs	MR		11.1	
The same of	capacity							. Vy	

h

1								
16.								
T	Pressurization of Lift Shaft		naft 1	NA	NA	NA		
	>	 Pressurization of lift lobby Communication in lift Car Fireman's Grounding Switch 		NA	NA	NA		
	>			NA	NA	NA		
	>			NA	NA	NA		
	>	Lift Signage	1	NA	NA	NA		
17.	Standl	by power supply]	NA	NA	NA		
18.	Refuge Area							
	>	Total area]	NA	NA	NA		
	>	Location]	NA	NA	NA		
19.	Fire control room							
	> Detector system		NA		NA	NA		
	>	Flow Switch Panel	NA		NA	NA		
	>	PA System Panel	NA		NA	NA		
	>	Battery backup	NA		NA	NA		
	>	Building Floor Plans	NA		NA	NA		
20.	Syster	al Fire Protection as for Protection of I Risks, if any;	on of		NA	NA		

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide letter no. F6/DFS/MS/2008/2477 Dated 01/09/2008 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Signature of the Inspecting Officer

Name Way Vir on

Designation ADO/wP

Name

Designation

7. (PO W21 - 42-(Po (West) In Joy (1))

FIPIS