GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE NEW DELHI- 110001

NO. FG DF3 MS BHOT 2017 642

DATED:

FIRE SAFETY CERTIFICATE

Certified that Ambika Palace (Banquet Hall) located at B-3/B, Main Wazirabad Road, Bhajanpura, Deihi-110053 running on 1st, mezzanine and 2nd floor of the building comprised of basement, ground, 1st, mezzanine and 2nd floor, owned/occupied by Ambika Palace (Banquet Hall) have compiled with the fire prevention and fire safety requirements in accordance with rules 33 of the Delhi Fire Service Rules, 2010 and verified by a team of officers of this department on 06/04/2017 in the presence of Mr. Shashi Kant Aggarwal, owner of the Banquet Hall and found that the 1st, mezzanine and 2nd floor of the building is fit for occupancy class "D" 'Assembly Building' with effect from ..a. (1.2.5.) (1.7.1) for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Deihi Fire Service Rules, 2010, printed overleaf.

Issued on at New Delhi by

(Vipin Kental) Chief Fire Officer

To.

The Owner.
Ambika Palace (Banquet Hail),
B-3/B, Main Wazirabad Road,
Bhajanpura, Deihi-110053

Copy to:-

 The Deputy Health Officer (EDMC), SHD (N)-Zone, Health Department, Delhi-110032

- Conditions -

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction /unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.
- 7. The owner / occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule (37)] along with a copy of this Certificate, six months prior to its expiry.

1. Name & address of the building Ambika Palace (Banquet Hall),

B-3/B Main Wazirapad Road,

Bhajanpura, Delhi-110053

Building is comprised of Basement, Ground plus two floors (Banquet hall is

running on Ist, Mez & IInd floor only)

3. Type of Occupancy : Assembly (Banquet Hall)

4. Type of Case : New

5. Details of Previous NOC letter no. : Nil

6. Fire Safety directive letter no : NBC Part-IV

7. Date of Inspection : 06/04/2017

8. Name of the Inspecting officers : ADO V. B. Yadav and ADO Om Prakash

Name and designation of Officer

from the building side . . : Mr. Shashi Kant Aggrawal (Owner)

10. Year of Construction : 2003

11. Applicant's letter No. - Letter No. Nii, Dated- 23/02/17

Br.	Minimum Standards on Fire	TNRC Part.IV	Provided at Site	Domonda			
No.	Prevention and Fire Safety U/R33	Requirement	LIANIAGA OF OTHE	Remarks MR/NMR			
01	Access to Building.			IVII (7) VIVII (
	Road width	- , 06 mtr.	24 mtr.	MR			
	Gate width	N/A =	N/A	N/A			
	Width of Internal road	N/A	N/A	N/A			
Φ2	Number, Width, Type and Arrange	ement of Exits.					
	a. Number of Staircases						
1	• Upper floor	02 nos.	02 nos.	WR' T			
	 Basement 	02 nos.	02 nos.	MR			
	b. Width of Staircases			-			
	 Upper floor 	1 50 mtr (old building)	3.65 & 1.10 mtr	MR			
	• Basement	1.25 mtr	1.35 & 0.93 mtr	MR'			
	c. Protection of Exits						
	 Fire check door 	Required	Provided	MR			
	 Pressurization 	NIA	N/A	1 - N/A			
	a No of Continuous Starroases to Terrace	01 no.	01 no.	MR			
	e. Width of Corridor	· N/A	. N/A	N/A			
0.0	f. Door Size	02 mtr.	02 mtr.	MR			
03	Compartmentation.						
	Fire check door	Not Required	Exit of basement separated	MR 1			
	 Sealing of electrical shafts 	- N/A	Concealed type	N/A			
	 Fire rating of shaft door 	N/A	N/A	N/A			
	• Water curtain	N/A	N/A	N/A			
	• Fire dampers	N/A	N/A	N/A			
04	Smoke Management System.						
	Basement	Required	Exhaust fans. Provided	MR			
	• Upper floor	Required	Ventilated	MR			
05.	Fire Extinguishers						
	Total numbers	12 nos.	12 nos.	VIR			
	• types	ABC/CO2	Provided	MR.			
	 ISI marking 	S marked	Provided	MR			

		or the AM control of the Editional Confedence in the Edition Confedence on the Edition Confedenc		
)6	First-Aid-Hose Reels			
	Total numbers on each floor	01 No.	01 No.	MR
	Length of hose reel hose	30 mtr.	30 mtr.	MR
	Nozzle diameter	05 mm	05 mm	MR
7	Automatic Fire Detection and Alarming S	ystem.		
-	Type of detectors	Required	Provided	MR
	Location of main panel	N/A	N/A	N/A
	Location of repeater panel	N/A	N/A	N/A
	Alternate source of power	Required	Provided	MR
	Hooter's location	Staircase	Provided	MR
8	MOEFA	Required	Provided	MR
9	Public Address System.	Required	Provided	MR
0	Automatic Sprinkler System.			
	Basement	Required	Provided	MR
	• upper floor	N/A	N/A	N/A
	sprinkler above false ceiling	N/A	N/A	N/A
1	Internal Hydrants		1 477	
	size of riser/down-comer	100 mm	100 mm	MR
	Number of hydrants per floor	01 No.	01 No.	MR
	Hose box per floor			
2	Yard Hydrants.	01 No.	01 No.	MR
4			* <u></u>	
	 Total number of hydrants 	N/A	N/A	N/A
	Hose box	N/A	N/A	N/A
3	Pumping Arrangements.			
3	Pumping Arrangements. Ground Level			
3	Ground Level		2280 Lpm.	WR WR
3	Ground Level Discharge of main pump	2280 Lpm. 40 M	40 M	MR
3	Ground Level Discharge of main pump Head of Main pump	40 M 01 No.	40 M 01 No.	MR MR
3	Ground Level Discharge of main pump Head of Main pump	40 M 01 No. 180 Lpm.	40 M 01 No. 180 Lpm.	MR MR MR
3	Ground Level Discharge of main pump Head of Main pump Number of main pumps	40 M 01 No. 180 Lpm. 40 M	40 M 01 No. 180 Lpm. 40 M	MR MR MR
3	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put	40 M 01 No. 180 Lpm. 40 M 2280 Lpm.	40 M 01 No. 180 Lpm. 40 M 2280 Lpm.	MR VIR MR MR
3	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M	MR MR MR MR MR
3	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Reguired	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided	MR MR MR MR MR MR
3	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M	MR MR MR MR MR
3	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required Required	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided Provided	MR MR MR MR MR MR MR
3	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required Required	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided Provided	MR MR MR MR MR MR MR
3	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump Head of the Pump	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required Required 450 Lpm. 40 M	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided Provided 450 Lpm. 40 M	MR MR MR MR MR MR MR MR
3	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump Head of the Pump Power supply	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required Required 450 Lpm. 40 M Required	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided Provided 450 Lpm. 40 M Provided	MR MR MR MR MR MR MR MR
	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required Required 450 Lpm. 40 M	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided Provided 450 Lpm. 40 M	MR MR MR MR MR MR MR MR
	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump Captive Water Storage for Fire Fighting.	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required Required 450 Lpm. 40 M Required	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided Provided 450 Lpm. 40 M Provided	MR MR MR MR MR MR MR MR
	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump Captive Water Storage for Fire Fighting. Underground tank capacity	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required Required 450 Lpm. 40 M Required Required Fequired Required Required Required	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided Provided 450 Lpm. 40 M Provided	MR MR MR MR MR MR
	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump Captive Water Storage for Fire Fighting Underground tank capacity Draw-off connection	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required Required 450 Lpm. 40 M Required 70 M Required 71 Required 72 Required 73 Required 74 Required 75 Required	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided Provided Provided Provided Provided 450 Lpm. 40 M Provided Provided Provided	MR
	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump Captive Water Storage for Fire Fighting. Underground tank capacity Draw-off connection Fire service inlet	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required Required A50 Lpm. 40 M Required Fequired Required Required Required Required	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided Provided Provided A50 Lpm. 40 M Provided Provided Provided Provided Provided Provided	MR
	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump Captive Water Storage for Fire Fighting. Underground tank capacity Draw-off connection Fire service inlet Access to tank	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided Provided 450 Lpm. 40 M Provided 450 Lpm. 40 M Provided Provided Provided Provided	MR
4	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump Captive Water Storage for Fire Fighting. Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required Required A50 Lpm. 40 M Required	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided	MR M
4	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump head Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump Captive Water Storage for Fire Fighting Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided Provided 450 Lpm. 40 M Provided 450 Lpm. 40 M Provided Provided Provided Provided	MR
4	Ground Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump Captive Water Storage for Fire Fighting. Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts.	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required Required 450 Lpm. 40 M Required	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided	MR M
4	Oround Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump Captive Water Storage for Fire Fighting. Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts.	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required Required 450 Lpm. 40 M Required	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided Provided Provided A50 Lpm. 40 M Provided N/A	MR MR MR MR MR MR MR MR MR MR MR MR MR M
4	Oround Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump Captive Water Storage for Fire Fighting. Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts. Pressurization of Lift Shaft Pressurization of Lift Shaft	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided N/A N/A	MR MR MR MR MR MR MR MR MR MR MR MR MR M
4	Oround Level Discharge of main pump Head of Main pump Number of main pumps Jockey pump out put Jockey pump head Standby pump out put Standby pump head Auto starting /manual stopping Pump house access Terrace Level Discharge of pump Head of the Pump Power supply Auto Starting of pump Captive Water Storage for Fire Fighting. Underground tank capacity Draw-off connection Fire service inlet Access to tank Overhead Tank capacity Exit Signage. Provision of Lifts.	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Required Required 450 Lpm. 40 M Required	40 M 01 No. 180 Lpm. 40 M 2280 Lpm. 40 M Provided Provided Provided A50 Lpm. 40 M Provided N/A	MR M

4	Total a libra Downer Stripply	Required	Provided	MR)		
17 /	Standby Power Supply	1.00				
18/	Refuge Area					
		N/A	N/A	N/A		
1	Total area	N/A	N/A	I N/A		
40	Location Control Room					
19.	N//					
	Detector system panel	N/A	N/A	N/A		
	Flow switch panel	N/A	N/A	N/A		
	PA system panel	N/A	N/A	N/A		
	Battery backup	N/A	N/A	N/A		
	o Illian Clear Diane	N/A	N/A	N/A		
20	Special Fire Protection Systems for Protection of Special Risks, if any:	N/A	N/A	N/A		

The shortcomings communicated vide letter no. F6 /DFS/MS/2016/2058 dated 30/08/16 have been rectified. The basement is being used as parking and ground floor is on rent for motor cycle showroom. The fire protection systems provided in the building were tested/onecked and found functional at the time of inspection.

Keeping in view the compliance of the minimum standards on fire prevention and fire safely required under the NBC Part-IV, it is recommended to issue Fire Safety Certificate.

Signature of the Inspecting Orice

- Om Prakesh

Designation :- A.D.O

Signature of Name . - V. B. Yadav

Designation : - A.D.O (Tahirpur)

submitted pl-

(F.O. of all the short comings membraned in letter at 30.8-16 are complied now.

REFONDZ

28/4

lir the Short commings commicated earlier uble our letter

are recte fired now.

CED (ND24)