GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI-110001

No.F6/DFS/MS/GH/SZ/2017/ 650

Dated: 05/05/17

FIRE SAFETY CERTIFICATE

Issued of Soll 7 at New Delhi by.

(VIPEN KENTAL) CHIEF FIRE OFFICER

Copy to:-

1. The Manager, Hotel Ashu Palace Guest house, 12A/34, WEA, Karol Bagh, New Delhi- 05

2. The Joint C.P.(Lic.), Police Station, Defence Colony, 1st floor, New Delhi

Following Fire Safety Directives must be adhered to: -

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non-functional of fire safety measures shall be at the risk & responsibility of the management.
- 3. The trained firefighting staffs should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. The basement shall be used as per the provisions of BBL.
- 6. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 7. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form "J" [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in

INSPECTION REPORT

1. Name & address of the building

: M/s Hotel Ashu Palace Guest house, 12A/34, WEA,

Karol Bagh, New Delhi- 05.

2. Type of Occupancy

: Lodging House

3. Type of Case

: Renewal

4. Details of previous NOC : F6/DFS/MS/GH/2013/SZ/479 dated 25.06.2013 (for 28 guest rooms)

5. Fire Safety directives letter No :

: Nil

6. Date of inspection

: 20-04-2017

7. Name of the Inspecting Officers

: M.K. Chattopadhyay, DO(South West)

8. Name and designation of officers

from the building side

: Mr. Raj Kumar, manager

9. Year of Construction

: Before 2006

10. Applicant's letter No.

: nil dated nil

The said guest house is comprised of basement (storage), ground floor (reception, office), first floor (08 guest room), second floor (08 guest rooms), third floor (08 guest rooms) and forth floor (01 store, 04 rooms for staff with pantry) (total 24 guest rooms)

S. No.	Minimum Standards on fire prevention and fire safety U/R 33	Existing fire safety requirements as per letter dated 25.06.2013	Provided at site	Remarks MR/NMR	
1	Access to building	Let 1			
	• Road width	06 mts	Provided (09 mts)	MR	
	Gate width		Directly accessible	MR	
	• Width of internal road	N/A	N/A	N/A	
2	Number, Width, Type & Arrangemen	nt of Exits			
	a. Number of staircases	-	2, 1,47.5	-	
	• Upper Floors	01	01	MR being old case	
	Basements	01	01	MR being old case	
	b. Width of staircases	-	-	<u>-</u>	
	• Upper Floors	1.25 mts	1.33 mts	MR being old case	
	Basements	1.25 mts	1.20 mts	MR being old case	
	c. Protection of exits		-		
	Fire check door	N/A	N/A	N/A	
	Pressurization	N/A	N/A	N/A	
	e. No. of continuous staircases to terrace	01	01	MR	
	g. Width of Corridor	1.25 mts	1.33 mts	MR	
	h. Door Size	Old case	0.80 mts	MR being old case	
	Compartmentation.				
	Fire check door	N/A	N/A	N/A	
	Sealing of electrical shafts	N/A	N/A	N/A	
	Fire Rating of shaft door	N/A	N/A	N/A	
	Water Curtain	N/A	N/A	N/A	
	Fire Dampers	N/A	NI/A	NI/A	

	Basements	12 a/c per hour	Exhaust fan provided	MR			
	Upper floors	12 a/c per hour	Natural Ventilation	MR			
5	Fire Extinguishers						
	Total numbers	20	Provided	MR			
	• Types	CO ₂ , ABC, WCO ₂	Provided	MR			
	IS marking	ISI marked	Provided	MR			
6	First-Aid Hose Reels.						
	 Total numbers on each floor 	01	Provided	MR			
	 Length of hose reel hose 	30 m	Provided	MR			
	Nozzle diameter	5 mm	Provided	MR			
7	Automatic fire detection and alarming	system.					
	Type of detectors	N/A	N/A	N/A			
	Location of Main Panel	N/A	N/A	N/A			
	Location of Repeater Panel	N/A	N/A	N/A			
	Alternate source of power	N/A	N/A	N/A			
	Hooters' Location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.		4				
	Basement	Required	Provided	MR			
	 Upper Floor Sprinkler above false ceiling 	N/A	N/A	N/A			
	Sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants						
	Size of riser/down-comer	N/A	N/A	N/A			
	Number of hydrants per floorHose Box	N/A	N/A	N/A			
	• Hose Box	N/A	N/A	N/A			
12	Yard Hydrants.		2				
	Total number of hydrants	N/A	N/A	N/A			
	Hose Box	N/A	N/A	N/A			
13	Pumping Arrangements.		***				
	Ground Level						
	Discharge of main Pump	N/A	N/A	N/A			
	Head of Main pump	N/A	N/A	N/A			
	Number of main pumps	N/A	N/A	N/A			
	Jockey Pump out put	N/A	N/A	N/A			
	Jockey pump head	N/A	N/A	N/A			
	> Standby Pump out put	N/A	N/A	N/A			

1	> Standby Pump Head	N/A	N/A	N/A				
	Auto Starting/ Manual stopping	N/A	N/A	N/A				
35%	> Pump House Access	N/A	N/A	N/A				
	Terrace level							
	> Discharge of pump	450 LPM	450 LPM	MR				
Y	➤ Head of the pump	30 mts	30 mts	MR				
	Power Supply	Required	Provided	MR				
	> Auto Starting of pump	Required	Provided	MR				
14	Captive Water Storage for fire fighting.							
	Underground tank capacity	N/A	N/A	N/A				
	> Draw-off connection	N/A	N/A	N/A				
	> Fire service inlet	N/A	N/A	N/A				
	> Access to tank	N/A	N/A	N/A				
	Overhead Tank capacity	Old case	6,000 lts	MR being old case				
15	Exit Signage.	Required	Provided	MR				
16	Provision of Lifts.							
	Pressurization of Lift Shaft	N/A	N/A	N/A				
	Pressurization of Lift lobby	N/A	N/A	N/A				
	Communication In lift Car	Required	Provided	MR				
	Fireman's Grounding Switch	Required	Provided	MR				
	Lift Signage	Required	Provided	MR				
17	Standby power supply	Required	Provided (125 KVA)	MR				
18	Refuge Area.							
	> Total Area	N/A	N/A	N/A				
	> Location	N/A	N/A	N/A				
19	Fire Control Room							
	Detector System Panel	N/A	N/A	N/A				
	Flow Switch Panel	N/A	N/A »	N/A				
	PA System Panel	N/A	N/A	N/A				
	Batter backup	N/A	N/A	N/A				
*	Building Floor Plans	N/A	N/A	N/A				
20	Special Fire Protection Systems for Protection of special Risks, if any:	Required	Two ABC type fire extinguisher found provided near elect. panel	MR				

The fire protection systems provided in the building were checked and found functional at the time of inspection.

In view the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the NOC issued vide letter No. F6/DFS/MS/GH/2013/SZ/479 dated 25.06.2013, renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended. DFA is put up for approval & signature please. Signature of the Inspecting Officer Name M.K.CHATTOPADHYAY Div. Officer (South West) Syl Miscell FIM Wally. F.T. letter is put up for Sign. please.