FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/EH/WZ/2017/

639

Dated: 04/04/2017

FIRE SAFETY CERTIFICATE

Issued on at New Delhi by.

Chief Fire Officer Delhi Fire Service

Copy to:

Sh. Amlan (Manager), B – 2/1, Ashok Vihar, Phase – II, New Delhi –

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

1. Name & address of the building: Sagar Ratna located at Ground Floor, B – 2/1, Ashok Vihar, Phase – II, New Delhi - 110052

2. Type of Occupancy : Assembly

3. Type of Case : Renewal

4. Details of previous NOC : F6/DFS/MS/EH/WZ/2014/342 dated 21-03-2014

5. Fire Safety directives Letter No.: Nil

6. Date of inspection : 26-04-2017

7. Name of the Inspecting Officer: Udaivir Singh ADO (WP)

8. Name and designation of Officer

from the building side : Sh. Amlan (Manger)

9. Year of Construction : 2006

10. Applicant's letter No. : Nil dated 21-03-2017

S No	Minimum standards on fire prevention and fire safety U/R 33	BBL Requirements				
1.	Access of building					
	Road width	6 m	8m Provided	MR		
	Gate width	NA	NA	NA		
	Width of internal road	NA	NA	NA		
2.	Number, width, Type & Arrange	ments of exits				
	a. Number of staircases					
	 Upper floors 	NA	NA	NA		
	 Basements 	NA	NA	NA		
	b. Width of staircases					
	 Upper floors 	NA		NA		
	 Basements 	NA	NA	NA		
	c. Protection of exits			8 · · · · · · · · · · · · · · · · · · ·		
	 Fire check door 	NA	NA	NA		
	 Pressurization 	NA	NA	NA		
	d. No of continuous staircase to terrace	NA	NA	NA		
	e. Width Of Corridor	NA	NA	NA		
	f. Door Size	1m	1x115cm1x80cm Provided	The second secon		
3.	Compartmentation					
	Fire check door	NA	NA	NA		
	 Sealing of electrical 	NA	NA	NA		
	shafts	NA	NA	NA		
	 Fire Rating of shaft door 	NA ,	NA	NA		
	Water Curtain	NA	NA	NA		
	Fire Dampers			Verify (1992) [23]		
4.	Smoke managements System					
	Basements	30 a/c per	NA	NA		
	 Upper floors 	hour				
THE REPORT OF THE PERSON OF TH		12 a/c per hour	Provided	MR		
5.	Fire Extinguishers					
	Total numbers	02 nos. each	9 Provided	MR		

	First – Aid Hose Reels				4)			
6.	Total numbers on each floor	or	2	I	Provided		MR	
			30 m	I	Provided		MR	
	Length of hose reel hoseNozzle diameter		5 mm]	Provided		MR	
	Automatic fire detection and alarm							
7.		IIIIg S	NA		NA	N	A	
	Type of detectors		VA		NA	N	[A	
	Location of Main Panel	-	NA		NA		ΙA	
	 Location of Repeater Pane 		Required		Provided	_	1R	
	 Alternate source of power 		NA		NA	-	JA .	
	Hooters' Location						MR I	
8.	MOEFA		Required		Provided			
9.		Public Address System NA NA NA						
10.	Automatic Sprinkler System			T	T A	N	JA	
	Dascincius	NA		-	NA		NA NA	
	Upper Floor	NA		_	NA		NA NA	
	Sprinkler above false	NA			NA	1	NA	
	ceiling							
11.	Internal Hydrants: common with	the m	all	_		-	(D)	
	Size of riser/down-	100 mm		-	Provided		MR	
	comer	1			Provided	I	MR	
	 Number of hydrants 			1		-	A (ID	
	per floor	Requ	aired		Provided	1	MR	
	Hose Box							
12.	To some and the source of the							
12	Total number of	NA		_	NA		NA	
	hydrants	NA			NA		NA	
	Hose Box							
13								
	Ground Level						N.T.1	
	 Discharge of main 	NA			NA		NA	
	pump	NA			NA		NA	
	> Head of main pump	NA			NA		NA	
	Number of main pumps	NA			NA		NA	
	Jockey pump out put	NA			NA		NA	
	Jockey pump head	NA			NA		NA	
	Standby Pump out put	NA			NA		NA	
	Standby Pump Head	NA			NA		NA	
	Auto Staring/Manual							
	stopping	NA			NA		NA	
	Pump House Access) (D	
	Terrace level	450	lpm		Provided		MR	
	Discharge of pump	40 1			Provided		MR	
	Head of the pump		quired		Provided		MR	
	> Power supply	Rec	quired		Provided		MR	
	> Auto starting of pump	- 1 .*						
14	4. Captive water Storage for fire f				NIA		NA	
	 Under ground tank 	NA			NA		NA	
	capacity	NA			NA Provided		MR	
	> Draw off connection		quired		NA		NA	
	> Fire service inlet	NA			Provided Provided		MR	
	> Access to tank	5, (000 litres		Provided		IVIIX	
	Overhead Tank							
	capacity	D 1			Provided		MR	
570	5 Exit Signage	Required			riovided		IVIIC	
16. Provision of Lifts Pressurization of Lift Shaft NA NA NA					NA			
	> Pressurization of Lift S	natt	NA NA	-	NA NA		NA	
	> Pressurization of lift lo	Cor	NA NA		NA		NA	
	Communication in lift	Cal			NA		NA	

1 10 1					
18.	Refuge Area				
	> Total area	-	NA	NA	NIA
19.	Location		NA	NA	NA NA
19.	Fire control room Detector system panel	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			1121
	Flow Switch Panel	NA NA		NA	NA
	➤ PA System Panel	NA		NA NA	NA
	Battery backup	NA		NA	NA NA
20.	Building Floor Plans Special Fire Protection	NA		NA	NA
20.	Systems for Protection of	NA		NA	NA
	special Risks, if any;				
	The fire protection gust	-			

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide Letter No. F6/DFS/MS/EH/WZ/2014/342 dated 21-03-2014 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Signature of the/Inspecting Officer

Name Volvi Vir high Designation Also/wp

Name

Designation

1) 9/10 /mulis 27/4/17

The cho W23 - 6/2

The West of 04/1)