FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No. F6/DFS/MS/2017/WZ/7//

Dated: 17/05/2017

FIRE SAFETY CERTIFICATE

Certified that the **Pearls PGF Limited** located at **Plot no. B – 1, Netaji Subhash Place, Pitampura, Delhi – 110034** comprised of 3 Basement + Ground + 12 Upper Floors was issued FSC vide Letter No. F6/DFS/MS/2014/321dated 10-03-2014. The premises was re inspected by the officers concerned of this department on 08-05-2017 in the presence of Mr. Attar Singh found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Mercantile & Business Building" Group F & Group E with effect from

Mercantile & Business Building Group F & Group E with effect from for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

(Atul Garg) Chief Fire Officer, Delhi Fire Service.

Copy to:

Sh. Attar Singh (Authorised Signatory),
 Plot No. B – 1,
 Netaji Subhash Place, Pitampura, Delhi – 110034.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. Basement shall be used as per building bye laws.
- 7. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.
- 8. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.

INSPECTION REPORT

1. Name & address of the building: Pearls PGF Limited, Located at, $\,\mathrm{B}-1,\,\mathrm{Netaji}$ Subhash Place, Pitam Pura, Delhi – 110034.

2. Type of Occupancy

: 3 Basement + Ground + 12 Upper Floors

3. Type of Case

: Renewal

4. Details of previous NOC: Letter No. F6/DFS/MS/2014/321 dated- 10-03-2014

5. Fire Safety directives Letter No.: Letter No. F6/DFS/MS/BP/2006/824 dated-04-04-2006

6. Date of inspection

: 08-05-2017

7. Name of the Inspecting Officer: Do (West) ADO (WP)

8. Name and designation of Officer

from the building side

: Sh. Attar Singh

9. Year of Construction

: 2009

10 Applicant's letter No.

S No	Minimum standards on fire prevention and fire safety l		BBL Requirements		Provided at site	1	narks /NMR	
1.	Access of building	-						
1.	Ü	T	22 m		D 111) (D		
	Road widthGate width		6 m		Provided MR Provided MR			
*	Gate widthWidth of internal ro	_	6 m		Provided	MR MR		
2.					Trovided	IVIIV		
۷.	Number, width, Type & An		ents of exits			1		
	Upper floors			o 12 th Provided		MD		
	opper moors	Floo		12	Flovided	MR		
	 Basements 		2 ramps		Provided	MR		
	b. Width of staircases							
	 Upper floors 	4x1	Tower-1 = 131cm,140cm,		,	MR(Old		
		2x1	.25cm	Tower-2 = 131cm,140cm,			Case)	
				Up t 1x12	o 4 th Floor=1x114cr	n &		
		4x1.	.5m &	3x13	1cm, 1x140cm,2x12	0cm	MR(Old	
	 Basements 	2x1.	.25cm		8		Case)	
	c. Protection of exits							
	 Fire check door 		uired	Pro	ovided	N	ИR	
	 Pressurization 		Required Provide		P. C. STONE	N	ИR	
	d. No of continuous staircase to terrace	4		Pro	ovided	N	MR	
	e. Width Of Corridor	1.5n	1.5m Provided		MR			
	f. Door Size			Provided		N	AR .	
3.	Compartmentation							
	 Fire check door 		uired		ovided	N	/IR	
11	 Sealing of electrical shafts 	Req	uired	Provided		N	MR	
	 Fire Rating of shaft door 	Requ	uired	Pro	vided	N	MR	
	Water Curtain	Requ	Required Pr		Provided		MR	
	• Fire Dampers	Requ	uired	Pro	vided	MR		

		System				Y			
		Basements		/c per hour		uired	M		
			12 a	de per hour		en able window	M	lR	
		 Upper floors 			Pro	vided			
		n' n' '1							
-	5.	Fire Extinguishers	141	nos.	Pro	vided	M	ſR.	
		• Total numbers		2, WCO2, ABC		110 /1000		MR	
		• Types		marked	110.1000		1R		
	5.	• IS marking First – Aid Hose Reels	101						
-).	Total numbers on	4 fc	or upper floor	Pro	vided	N	1R	
		each floor	30		Pro	vided	N	1R	
		 Length of hose reel 		XI					
		hose	5 m	ım	Pro	vided	N	1R	
		 Nozzle diameter 							
	7.	Automatic fire detection and	alarn	ning system	D.			MD	
		 Type of detectors 		Smoke &	Prov	ided		MR	
				Heat	Daore	idad		MR	
		Location of Main Par		Required Required	Provided Provided			MR	
		Location of Repeater		Required	1100	ided		TVIIC	
		Panel • Alternate source of		Required	Prov	ided		MR	
		power		110 9 0111 0 01					
		Hooters' Location		Required	Prov	ided		MR	
-	8.	MOEFA		Required	Prov	ided		MR	
-	9.	Public Address System		Required	Prov	ided		MR	
-	10.	Automatic Sprinkler System		*					
		Basements		Required		Provided	MR		
		Upper Floor		Required		Provided	MR		
		Sprinkler above false	e	Required	Provided M		MR		
		ceiling				14			
	11.	Internal Hydrants		1.50		D '1 1	MR		
		Size of riser/down-		150 mm		Provided Provided	MR		
		comer		4 for upper flo Required	ors	Provided	MR		
		Number of hydrants floor	per	Required		Tiovided	1,11		
		Hose Box					2 2		
-	12.	Yard Hydrants							
	12.	Total number of		Required		Provided	MR	2	
		hydrants		1					
		Hose Box		Required	Provided		MR	2	
		`							
	13.	Pumping Arrangements		1					
		Ground Level	140000	2850 lpm		Provided	MR		
		Discharge of main pump Head of main pump		p 2850 lpm 110 m				3	
		Head of main pumpNumber of main pu		2	Provided M Provided M Provided M Provided M Provided M		MI	- 1	
		Jockey pump out pu		180 lpm				MR	
		Jockey pump bead	-	110 m			МI	2	
	15 ×5	> Standby Pump out p	out	2850 lpm					
		> Standby Pump Head	1	110 m		Provided	MI		
		> Auto Staring/Manua	al	Required		Provided	MI	R	
		stopping					1		
		> Pump House Acces	S	Required	- Victoria (Inc. 18)	Provided	M	K	
		Terrace level Discharge of nump		N. D.		ND	NF		
		Discharge of pumpHead of the pump		Not Required		NR NR	NE		
		Power supply		Not Required		NR NR	NF		
		1 Ower suppry		Not Required	L ,	IVIX	INI	1	

14.	Captive water Storage for fire fighting							
	Under ground tank capacity	2,00,000 litres		Provided	MR			
	Draw of connection	Rec	uired	Provided	MR			
	Fire service inlet	Rec	uired	Provided	MR			
	Access to tank	Required		Provided	MR			
10.000	 Overhead Tank capacity 		000 litres``	Provided	MR			
15	Exit Signage	Required		More Exit Signs Provided	MR			
16.	Provision of Lifts							
	Pressurization of Lift Sha		Required	Provided	MR			
	Pressurization of lift lobby		Required	Provided	MR			
	Communication in lift Ca	=	Required	Provided	MR			
	Fireman's Grounding Swi	itch	Required	Provided	MR			
	➤ Lift Signage		Required	Provided	MR			
17.	Standby power supply		Required	Provided	MR			
18.	Refuge Area							
	Total area		Required 4 th , 6, 9 th ,	Provided	MR			
	Location	> Location		Provided	MR			
1.0			Terrace Floor					
19.	Fire control room							
	Detector system panel		uired	Provided	MR			
	Flow Switch Panel		uired	Provided	MR			
			uired	Provided	MR			
	Battery backup		uired	Provided	MR			
20	Building Floor Plans	Required		Provided	MR			
20.			flooding	Provided	MR			
			em for HT &					
2.61	if any;	LTr	panel	· ·				

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of minimum standards on fire prevention and fire safety as required under the rules the NOC issued vide Letter No. F6/DFS/MS/2014/321 dated- 10-03-2014 renewal under rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Officer

Officer

Name Udas Vir Sigh

Signature of the Inspecting

Name Sh. Mohesh Verma

Designation Do/w

Designation ADO/WP