GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE, CONNAUGHTPLACE NEW DELHI- 110001

No.F6/DFS/MS/School/NDZ/2017/ 789

Dated: 31/05/17

FIRE SAFETY CERTIFICATE

Issued on at New Delhi by

(Vipin Kental)

Chief Fire Officer

% Rs

To,

The Principal
Dashmesh Public School
C-Block, Vivek Vihar, Delhi-95,

Copy to:-

The Director of Education GNCT of Delhi, Old secretariat Delhi -54.

- Conditions -

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- All the fire fighting equipments shall be maintained in good working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. The clarification with regards electrical installation, ventilation, structure stability set back areas, occupancy and constructional deviation in building etc .may be got verified from the authorities concerned.
- 5. This Fire Safety certificate can not be treated in any case for regularizations of unauthorized construction if any.

The owner / occupier shall submit a declaration every year in form 'K' provided inthe first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

1. Name & address of the building: Dashmesh Public School at C-Block, Vivek Vihar,

Delhi -95.

Building is comprised of

: Ground +2 upper floors

3. Type of Occupancy 4. Type of Case

: Educational : Renewal

5. Details of Previous NOC letter : F.6/DFS/MS/School/2014/519 dated 25/04/14

6. Fire Safety direction letter No : Circular No.262-362 Dated 17.01.2005 Director of

Education

7. Date of Inspection

: 22/05/17

8. Name of the Inspecting officers: ADO R.K. Yadav

9. Name and designation of Officer

from the building side

: Smt.Sarita Sexena (Principal)

10. Year of Construction

: 1980

11. Applicant's letter No

: DPS/No.64/1257dated 27/04/17

NO.	Minimum Standards on fire prevention and fire safety U/R33	Old Circular	Provided at Site	Remarks		
1		Requirement	Site			
	Access to building Road width	06 Mtrs.	A.F. NALO	NACO.		
		Ub IVITIS.	15 Mtrs.	MR		
	Gate widthWidth of internal road	N/A	N/A	N/A		
		N/A	N/A	N/A		
2	Number, Width, Type and Arrangement of Exits					
	Number of Staircases					
	Upper Floor	02 Nos	02 Nos.	MR		
	Basement	N/A	N/A	N/A		
	B. Width of Staircases					
	Upper Floor	1.5 M	1.5 M & 1.15 M	MR		
	Basement	N/A	N/A	N/A		
	c. Protection of exits					
	Fire check door	N/A	N/A	N/A		
	 Pressurization 	N/A	N/A	N/A		
	e. No. of continuous staircases to	2 nos.	2 Nos.	MR		
	terrace g. Width of Corridor	1.5 M	1.8 M	MR		
	h. Door Size	1.0 Mtrs	1.0 Mtrs	MR		
3	Compartmentation.					
	Fire check door	N/A	N/A	N/A		
	 Sealing of electrical shafts 	N/A	N/A	N/A		
	 Fire rating of shaft door 	N/A	N/A	N/A		
	Water curtain	N/A	N/A	N/A		
	Fire Dampers	N/A	N/A	N/A		
4	Smoke Management System.					
	Basement	N/A	N/A	N/A		
	Upper floor	N/A	N/A	N/A		
5.	Fire Extinguishers	1471	14/7	13//		
	Total numbers	12 Nos.	12 Nos.	MR		
	Types	ABC & Co2	ABC & Co2	MR		
	IS marking	ISI marked	ISI marked	MR		
6	First-aid-Hose Reels.	-				
	Total numbers of each floor	1 no.	1 no.	MR		
	 Length of hose reel hose 	30 M	30 M	MR		
	Nozzle diameter	5 mm	5 mm	MR		

7	 Automatic fire detection and alarming syste Type of detectors 	N/A	N/A	N/A
	Location of main panel	N/A	N/A	N/A
	· · · · · · · · · · · · · · · · · · ·	N/A	N/A	N/A
	Location of repeater panel	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
0	Hooter's location			
8	MOEFA	N/A	N/A	N/A
9	Public address System.	N/A	N/A	N/A
10	Automatic Sprinkler System.	ALI/A	N.//A	1
<u> </u>	Basement	N/A	N/A	N/A
	upper floor	N/A	N/A	N/A
	 sprinkler above false ceiling 	N/A	N/A	N/A
11	Internal Hydrants	Required	Provided	MR
	size of riser/down-comer	100 MM	100 MM	MR
	Number of hydrants per floor	1 No.	1 No.	MR
	Hose Box	1 No.	1 No.	MR
	11000 200	1110.	1110.	1011
12	Yard Hydrants.			
-	Total number of hydrants	N/A	N/A	N/A
	Hose Box	N/A	N/A	N/A
13	Pumping Arrangements.	14//	10/3	13//1
10	Ground Level	N/A	N/A	N/A
-		N/A	N/A	N/A
	,	N/A	N/A	N/A
	> Number of main pumps	N/A	N/A	N/A
	> Jockey pump out put	N/A	N/A	N/A
	> Jockey pump head	N/A	N/A	N/A
	> Standby pump out put	N/A	N/A	N/A
	> Standby pump Head	N/A	N/A	N/A
	Auto Starting /Manual stopping	N/A	N/A	N/A
	Pump House Access	N/A	N/A	N/A
	Terrace Level	Required	Provided	MR
	Discharge of pump	450 LPM	450 LPM	MR
	Head of the Pump	40 M	40 M	MR
	Power supply	Required	Provided	MR
	Auto Starting of pump	Required	Provided	MR
14	Captive Water Storage for Fire Fighting.			
	Underground tank capacity	N/A	N/A	N/A
	> Draw-off connection	N/A	N/A	N/A
	> Fire service inlet	N/A	N/A	N/A
	> Access to tank	N/A	N/A	N/A
	Overhead Tank capacity	5000 Ltrs.	5000 Ltrs.	MR
15	Exit Signage.	N/A	N/A	N/A
16	Provision of Lifts.	IV/A	IV/A	IV/A
10		N/A	NI/A	NI/A
	Pressurization of Lift Shaft		N/A	N/A
	Pressurization of Lift lobby	N/A	N/A	N/A
1.00	Communication in lift car	N/A	N/A	N/A
17.	Standby power supply	N/A	N/A	N/A
18	Refuge Area.	N/A	N/A	N/A
	Total area	N/A	N/A	N/A
	Location	N/A	N/A	N/A
19	Fire Control Room	N/A	N/A	N/A
	Detector system panel	N/A	N/A	N/A
	Flow switch panel	N/A	N/A	N/A
	PA system panel	N/A	N/A	N/A
	Battery backup	N/A	N/A	N/A
	Building Floor Plans	N/A	N/A	N/A

20	Special Fire Protection systems for	N/A	N/A	N/A	,
	protection of special Risks, if any:	(4)			

The fire protection systems provided in the building were tested/checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules. The NOC issued vide letter no. F.6/DFS/MS/School/2014/519 dated 25/04/14 renewal under the circular no.262-362 dated 17.01.2005 is recommended.

Signature of the Inspecting Officer 1512

Name

: R. K. Yadav

Designation: ADO (Laxmi Nagar)

178/cro (NDZ)
30/17/20/20

C. 7.0

m.scell

F7101.

Sa, FT hetter co put up for signature Hear

CFO(MDZ)

m scell le 31/5