GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6 / DFS / MS / School/2017 / W2 / 7 57

Dated: 26/5/17

FIRE SAFETY CERTIFICATE

Certified that the Govt. Girls Sr. Sec. School No.-1, Roop Nagar, Delhi-07 comprised of 02 blocks, Ground and 03 upper floors each owned/ occupied by Govt. Girls Sr. Sec. issued Fire Safety Certificated vide this office 6/DFS/MS/School/2013/WZ/504 dated 01.07.2013. The premise was re-inspected by the officer concerned of this department on 09.05.2017 in the presence of Smt. Som Lata, Vice Principal and observed that all the fire prevention and fire safety arrangements as provided in the premise found in good working condition and there is no additional construction. The premise have therefore deemed complied with the requirements under rule 33 of the Delhi Fire Service Rules, 2010 and the building premise is fit for occupancy under Educational "Group B" with effect from2.6.1.7..... for a period of three years in accordance with the rule 36 unless renewed under rule 37 or sooner cancelled under rule 40, subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010,

Conditions for the validity of Fire Safety Certificate:

- 1. All the fire safety arrangement provided there-in shall be maintained in good working conditions
- 2. Loss of life or property due to non functional fire safety measure shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation with regard to the construction etc shall be verified by the concerned building sanctioning agency.
- 5. This certificate cannot be treated in any case for regularizations of unauthorized construction.
- 6. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director of Form 'J' [sub rule (1) of rule 37] along with a copy of this Certificate, six months prior to its expiry".
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on WWW.dfs.Delhigovt.nic.in

Issued on ...26.1.7.1.7...... at New Delhi

Ph:-011-23414250

Copy to: -

- 1. The Director, Education, Government of N.C.T of Delhi. Old Sectt. Delhi = 110054.
- 2. The Principal, Govt. Girls Sr. Sec. School No.-1, Roop Nagar, Delhi-07.

INSPECTION REPORT

1. Name & address of the building : Govt. Girls Sen. Sec. School No.-3, Roop Nagar, Delhi-07. 2.

Type of Occupancy :Educational

3. Type of Case :Renewal (02 blocks-Ground plus 03 upper floors)

4. Details of previous NOC :F6/DFS/MS/School/2013/WZ/504 Dated: 01/07/2013

5. Fire Safety directives letter No : NBC Part-IV Date of inspection : 09/05/2017

7. Name of the Inspecting Officers : ADO (RN)

8. Name and designation of officers

from the building side : Mrs. Som Lata, Vice-Principal

9. Year of Construction : 1966/1979

10. Applicant's letter No. : GGSSS No.-1/RN/2017/PWD dated: 14.03.2017

Plot Area-18753m2 Covered Area: 7010m2 No of class rooms –26 nos. No of students--1023nos.

	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR	
1	Access to building				
	Road width	06m	12m	MR	
	Gate width	4.5m	4.5m	MR	
	Width of internal road	06m	06m	MR	
2	Number, Width, Type & Arrangement of Exits	261			
	a. Number of staircases		*		
	Upper FloorsBasements	Block-1 -01 Block-II02	Block-1 –01 Block-II02	MR(old case)	
	b. Width of staircases	NA	NA	NA	
	• Upper Floors	1.5 m	Block-1 –2m Block-II—1.7m&1.18m	MR(old case)	
	Basements	NA	NA	NA	
	c. Protection of exits	, , , , , , , , , , , , , , , , , , , ,			
	Fire check door	NA	NA	NA	
	Pressurization	NA	NA	NA	
	d. No. of continuous staircases to terrace e. Width of Corridor	01each block	01each block	MR	
	f. Door Size	Required	2.35m	MR	
3		1 m	1m &1.15m two doors	MR	
	Compartmentation.		· · · · · · · · · · · · · · · · · · ·	N.	
			W.		

	Fire check door	NA	NA	NA		
	Sealing of electrical shafts	NA	NA	NA		
	Fire Rating of shaft door	NA	NA	NA		
	Water Curtain					
	• Fire Dampers	NA	NA	NA		
4		NA	NA	NA		
4	Smoke Management System.					
	Basements	30 a/c per hour	NA	NA		
	• Upper floors	12 a/c per hour	Natural Ventilated	MR		
5	Fire Extinguishers					
	Total numbers	34nos	34nos	MR		
	• Types	ABC/Co2	ABC/co2-34	MR		
	ISI marking	ISI Marked	Provided	MR		
6	First-Aid Hose Reels.					
	Total numbers on each floor	01in each block	Provided	MR		
	 Length of hose reel hose 	30m	30m	MR		
	Nozzle diameter	5mm	5mm	MR		
7	Automatic fire detection and alarming system.					
	Type of detectors	NA	NA	NA		
	Location of Main Panel	NA	NA	NA		
	• Location of Repeater Panel	NA	NA	NA		
	Alternate source of power	NA	NA	NA		
	Hooters' Location	NA	NA	NA		
8	MOEFA	NA	NA	NA		
9	Public Address System.					
10	Automatic Sprinkler System.					
	Basement	NA	NA	NA		
	Upper Floor	NA	NA	NA		
	Sprinkler above false ceiling	NA	NA	NA		
11	Internal Hydrants					
	Size of riser/down-comer	01	01(Provided)	MR		
	Number of hydrants per floor	NA	Provided	NA		
	Hose Box	NA	Provided	NA		
12	Yard Hydrants.	,1	% ,			
	Total number of hydrants	NA	NA	NA		



	Hose Box	NA	NA	NA	
13	Pumping Arrangements.				
	Ground Level		, , , , , , , , , , , , , , , , , , , ,		
	Discharge of main Pump	N/A	N/A	N/A	
	➤ Head of Main pump	N/A	N/A	N/A	
	> Number of main pumps	N/A	N/A	N/A	
	Jockey Pump out put		NA NA	NA	
	Jockey pump head	NA	NA NA	NA	
	> Standby Pump out put	NÁ			
	> Standby Pump Head	N/A	N/A	N/A	
	> Auto Starting/ Manual stopping	N/A	N/A	N/A	
	> Pump House Access	N/A	N/A	N/A	
	Terrace level	450lpm	450lpm	MR	
	Discharge of pump	40m	40m	MR	
	➤ Head of the pump	NA	NA	NA	
	> Power Supply	Required	Provided	MR	
	> Auto Starting of pump	Required	Tiovided	17111	
4	Captive Water Storage for fire fighting.				
	Underground tank capacity	NA	1,00,000 ltr.	NA	
	> Draw-off connection	NA	NA	NA	
	> Fire service inlet	NA	NA		
	> Access to tank	NA	NA	NA	
	Overhead Tank capacity	10,000 ltrs	15,000ltr each block	MR	
5	Exit Signage.	Required	Provided	MR	
6	Provision of Lifts.				
	Pressurization of Lift Shaft	N/A	N/A	N/A	
	Pressurization of Lift lobby	N/A	N/A	N/A	
	Communication In lift Car	N/A	N/A	N/A	
	Fireman's Grounding Switch	N/A	N/A	N/A	
	Lift Signage	N/A	N/A	N/A	
17	Standby power supply	Required	Provided	MR	
18	Refuge Area.	, , , ,		2	



	➤ Total Area	N/A	N/A	N/A
	> Location	N/A	N/A	N/A
19	Fire Control Room		€	
	Detector System Panel	N/A	N/A	N/A
	Flow Switch Panel	N/A	N/A	N/A
	PA System PanelBatter backupBuilding Floor Plans	N/A	N/A	N/A
		N/A	N/A	N/A
		N/A	N/A	N/A
0	Special Fire Protection Systems for Protection of special Risks, if any:	N/A	N/A	N/A

Accordingly, the fire protection systems provided in the building were tested/ checked randomly and found in working condition at the time of inspection.

Keeping in view the satisfactory compliance of the minimum standards on fire prevention and fire safety required as stipulated in Director of Education Circular / NBC Part 4, the FSC issued vide letter of even no 504 dated 01.07.2013 renewal under rule 35 of the Delhi Fire Service Rules, 2010 is recommended

Signature of the Inspecting Officer

Name:- Rajesh Kumar Designation:- ADO/RN

Do 1 N 60 0 Shugh 16.5.17

Dycho(M2)

15 19817

As approved, F.T. letter is puty

1/1/11