## GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

Fax No. 011-23412593, Ph. 011-23412225

No. F6/DFS/MS/GH/2017/SZ/ 8 60

Dated: 15/06/17

## FIRE SAFETY CERTIFICATE

Certified that M/s Vishal Residency Guest House situated at Khasra No. 103/2/2, NH-8, Rangpuri Extn., Mahipal Pur, New Delhi, comprised of Basement, Ground floor (13 Guest Rooms), 1<sup>st</sup> floor (14 Guest Rooms), 2<sup>nd</sup> floor (11 Guest Rooms), Total 38 Guest Rooms was granted Fire Safety Certificate by this department vide letter No. F.6/DFS/MS/GH/2014/SZ/794 dated 26-06-2014. The premises/building was re-inspected by the officer concerned of this department on 03/06/2017 in the presence of Mr. Naresh (Manager) of the guest house and found that the said premises/building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the building /premises is fit for occupancy class "Residential (Guest house) Group-A" as above with effect from the date of issue of this certificate for a period of Three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

T 1	at Mary Dalle by
Issued on	at New Delhi by

(Vipin Kental) Chief Fire Officer

Copy to: -

- 1. The Joint C.P. (Lic.), First floor, PS Defence Colony, New Delhi-110049
- 2. M/s Vishal Residency Guest House, Kh. No. 103/2/2, NH-8, Rangpuri Extn., Mahipal Pur, New Delhi-110037

## Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety and means of escape facilities shall be maintained in good working condition at all time. Any lapse rendering the fire safety or means of evacuation facilities non-functional shall be the responsibility of the management.
- 2. Building Sanctioning authority may verify any deviation with regard to construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null & void.
- 3. The staff shall be trained for operating fire fighting system and mock evacuation drill be conducted at regular interval and record be maintained.
- 4. The basement shall be used strictly as per the provisions of Building Bye Laws.
- 5. The Owner/Occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules, 2010. The form is available on <a href="www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.
- 6. The Owner/Occupier shall apply for renewal of this Fire Safety Certificate to the Director in the form 'J' [sub rule (1) of rule 37] along with copy of this certificate, six months prior to its expiry. The form is available on <a href="https://www.dfs.delhigovt.nic.in">www.dfs.delhigovt.nic.in</a>.

	INSPECTION				
1	Name & Address of the Building	Vishal Residency Guest House situated at Kh. No. 103/2/2, NH-8, Rangpuri Extn., Mahipal Pur, ND-37			
2	Type of Occupancy	Residential & Lodging, Group-A (Guest House)			House)
3	Building Comprised of	Basement, Ground + Two upper floors			
4	Type of Case	Renewal			
5	Details of Previous NOC	F6/DFS/MS/GH/2014/SZ/794 Dated 26.06			6.2014
6	Fire Safety Directives Letter No	Nil			=
7	Date of Inspection	03.06.2017			
8	Name of the Inspecting Officers	ADO R.N. Singh			
9	Name & Designation of Officers from the building side	Mr. Naresh (Manager)			
10	Year of construction	Basement (Storage) Ground floor (13 First floor (14 G. Rooms), 2 <sup>nd</sup> floor (11 Total 38 Guest Rooms			13 G. Room) 11 G. Rooms
11	Applicant letter No.	Nil Da	ted 16	-05-2017	
S. No	Minimum standards on Fire Prevention and Fire Safety U/R 33	As per old Provided at Site NOC-2011		Remarks MR/NMR	
1	Access to Building.				
Y	Road width	Rea	uired	10 mtr.	MR
	Gate width		/A	N/A	N/A
	Width of internal road		/A	N/A	N/A
2	Number, width, type and arrangements of		77.	14/11	1471
2	a. Number of Staircase	CAILS.			
		Pag	uired	Two	MR
	Upper floors	-	uired	Three	MR
	Basement floor	Req	uncu	Tinee	IVIX
	b. Width of Staircase	D	. 1	1 47 0 0 05	D ( 11 )
	Upper floors	Requ			R (old case)
	Basement floor	Requ	ired	1.15, 0.99 & 0.91 mtr M	R (old case)
	c. Protection of exits				
	Fire check door		/A	N/A	N/A
	Pressurization	N	/A	N/A	N/A
	d. No. of continuous staircase to terrace	Req	uired	Two provided	MR
	e. Width of corridor	N	/A	N/A	N/A
	f. Door size	1	m	Provided	MR
3	Compartmentation.				
	Fire check door.	N/A		N/A	N/A
	<ul> <li>Sealing of electrical shafts.</li> </ul>	Required		Provided	MR
	Fire rating of shaft door.	N	/A	N/A	N/A
	Water curtain	N	/A	N/A	N/A
	Fire dampers.	N	/A	N/A	N/A
4.	Smoke Management system.				
	Basement	30 A	СРН	Exhaust fans provided	MR
	Upper floors		CPH	Natural ventilation	MR
5.	Fire Extinguishers.				
	Total numbers			12 Nos.	MR
	• Types	ISIn	narked		MR
		101 11	iai neu	Yes	MR
6	101111111111111111111111111111111111111			103	1411/
6.	First Aid Hose Reels.	TT	n # = -1	Т	MAD
	<ul> <li>Total numbers on each floor.</li> </ul>	Hos	e-reel	Two	MR
	<ul> <li>Length of hose-reel hose.</li> </ul>			30 m	MR
	Nozzle Diameter			05 mm	MR

/	/	

7	Automatic fire detection & alarming system	em		
	• Type of detectors	N/A		
	Location of Main Panel	N/A N/A	N/A	N/A
	Location of Repeater Panel	N/A	N/A	N/A
	Alternate source of power	N/A	N/A	N/A
	Hooter's location		N/A	N/A
8.	MOEFA	N/A	N/A	N/A
9.	Public Address System	Required	Provided	MR
10.	Automatic Sprinkler System	N/A	N/A	N/A
	Basement	Possil 1	•	
	Upper floors	Required	Provided	MR
	Sprinkler above false ceiling	N/A	N/A	N/A
11.	Internal Hydrants.	N/A	N/A	N/A
	Size of Riser/Down-comer	D I		
	Number of Hydrant per floor	Required	100 mm	MR
	Hose box.	Required	2 No's	MR
12.	Yard Hydrants.	Required	2 No's	MR
	Total number of hydrants.	NI/A		
	Hose box.	N/A	N/A	N/A
13.	Pumping arrangements.	N/A	N/A	N/A
	Ground Level			-
	Discharge of main pump.	N/A		
	Head of main pump.	N/A	N/A	N/A
	Number of main pumps.	N/A	N/A	N/A
	Jockey Pump output.	N/A	N/A	N/A
	Jockey Pump head.	N/A	N/A	N/A
	Standby Pump output.	N/A	N/A	N/A
	Standby Pump head.	N/A	N/A	N/A
	Auto Starting/Manual Stopping.	N/A	N/A	N/A
	Pump House Access	N/A	N/A	N/A
		N/A	N/A	N/A
	Discharge of pump.	450 1 70 5	The Desire of the second	
	Head of pump.	450 LPM × 2	450 LPM × 2	MR
	Power supply.	40 mtr	40 mtr	MR
	> Auto starting of pump.	Required	Provided	MR
4. C	aptive water storage for fire fighting.	Required	Provided	MR
	Underground tank capacity.			
	> Draw-off connection.	N/A	N/A	N/A
	Fire Service Inlet.	N/A	N/A	N/A
	Access to tank.	N/A	N/A	N/A
	Overhead tank capacity.	Required	Provided	MR
5. Ex	xit Signage.	15,000 Ltr.	15,000 Ltr	MR
	ovision of Lifts.	Required	Provided	MR
	Pressurization of lift shaft.			
	Pressurization of lift lobby.	N/A	N/A	N/A
	Communication in lift car.	N/A	N/A	N/A
	• Fireman's switch.	N/A	N/A	N/A
		N/A	N/A	N/A
7 Sta	Lift signage.  And by Power S.	N/A	N/A	N/A
	andby Power Supply	Required	Provided	MR
. Re	fuge Area			AVIII
And the same	Total area	N/A	N/A	N/A
	• Location	N/A	N/A	N/A

19.	Fire Control Room.					
	Detector System Panel.	N/A	N/A	N/A		
	Flow Switch Panel.	N/A	N/A	N/A		
	PA system Panel.	N/A	N/A	N/A		
	Battery backup	N/A	N/A	N/A		
	Building floor plan	N/A	N/A	N/A		
20.	Special Fire Protection System for the Protection of special Risk, if any.	N/A	N/A	N/A		

The Fire protection systems provided in the building were randomly checked/ tested and found functional at the time of inspection.

Keeping in view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under the rules, the FSC issued vide letter No. F6/DFS/MS/GH/2014/SZ/794 dated 26.06.2014, renewal under rule 37 of the Delhi Fire Service rules, 2010 is recommended.

Accordingly DFA is put up for approval and signature please.

Signature of the Inspecting Officer

Name : R.N. Singh

Designation: ADO

Div. Officer (SD)

ALFIRE SERVI