GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: CANNAUGHT PLACE NEW DELHI- 110 001

No.

F6 | DF3/ms/ 9H/2017/856

Dated

15/06/17

FIRE SAFETY CERTIFICATE

Issued on 15/6/17 at New Delhi by

(Vipin Kental)
Chief Fire Officer

Copy to-

- The Addl.Commissioner of police (Lic.),
 1st Floor Police station, Defence Colony, New Delhi
- Om International Guest House
 C-15/219, Opp. District Centre, Laxmi Nagar Delhi-92.

CONDITIONS:

- 1. All the means of escape shall be kept free of all type of obstruction all the time.
- 2. All the employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.
- 3. All the fire fighting equipments shall be maintained in perfect working condition all the time and any lapse rendering non-functional of fire safety measures, management shall be responsible.
- 4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.
- 5. This NOC may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in

	J	INSPE	CTION REPORT	394 V-10 W-11 V-10 II	17 14 14	
8	2. Building is comprised of Centre, Laxmi Nagar Delhi-92. 2. Building is comprised of Ground+ mezzanine+ three upper floor Residential Renewal 3. Type of Case Renewal 4. Details of Previous NOC Fire Safety direction letter No Nil 6. Date of Inspection Officers: ADO R.K.Yadav 8. Name of the Inspecting Officers: ADO R.K.Yadav 9. Year of Construction Sudden Sudden Sungh (Manager) 10. Applicant's letter No Sudden Su					
1	No	Minimum Standards on fire prevention and fire safety U/R33	Requirement	Provided at Sit	e Remarks	
2		Road width Gate width Width of internal road Number, Width, Type and Arrangement of a. Number of Staircases Upper Floor Basement B. Width of Staircases Upper Floor Basement c. Protection of exits Fire check door Pressurization e. No. of continuous staircases to terrace g. Width of Corridor	6 m N.A. N.A. of Exits 1 no. N.A. 1.25 m N.A. N.A. N.A. 1.10.	30 m N.A. N.A. 1 n o. N.A. 1.30 m N.A. N.A.	MR N.A. N.A. MR N.A. MR N.A. MR N.A.	
		h. Door Size	N.A.	N.A.	N.A.	
3		Compartmentation.	1 m	1 m	MR	
eller destinance states productively of commonwealth in the set of destination plane.		 Fire check door Sealing of electrical shafts Fire rating of shaft door Water curtain Fire Dampers 	N.A. N.A. N.A.	N.A. N.A. N.A.	N.A. N.A. N.A.	
		Smoke Management System.	N.A.	N.A.	N.A.	
		Basement Upper floor	N.A. N.A.	N.A. N.A.	N.A. N.A.	

* old case. Farlier NOCIFSC cosmed voice letter No. FG IDFS/ MS/

5.	Fire Extinguisher					
	Total numbers	08 no.	08 no.	MR		
	Types	CO ₂ & ABC	Provided	MR	/	
	ISI marking	ISI marked	Provided	MR	1	
6	First-aid-Hose Reels.					
	Total numbers of each floor	01 no.	01 no.	MR		
	Length of hose reel hose	30 m	30 m	MR		
	Nozzle diameter	5 mm	5 mm	MR		
7	Automatic fire detection and alarming system.					
	Type of detectors	N.A.	N.A.	N.A		
	Location of main panel	N.A.	N.A.	N.A		
	Location of repeater panel	N.A.	N.A.	N.A		
	Alternate source of power	N.A.	N.A.	N.A		
	Hooters's location	N.A.	N.A.	N.A	-	
8	MOEFA	Required	Provided	MR		
9	Public address System.	Required	Provided	MR		
10	Automatic Sprinkler System.		TENTON COLUMN TO THE PROPERTY OF THE PROPERTY		1	
	basement	N.A.	N.A.	N.A.		
	upper floor	N.A.	N.A.	N.A.		
1	sprinkler above false ceiling	N.A.	N.A.	N.A.		
11	Internal Hydrants					
	size of riser/down-comer	N.A.	100 mm	MR	1	
	Number of hydrants per floor	N.A.	1 no.	MR	-/	
	Hose Box	N.A.	1 no.	MR		
2	Yard Hydrants.					
	Total number of hydrants	N.A.	N.A.	N.A.		
131-2	Hose Box	N.A.	N.A.	N.A.	-	
.3	Pumping Arrangements.		The state of the s			
	Ground Level	N.A.	N.A.	N.A.		
	Discharge of main Pump	N.A.	N.A.	N.A.		
	Head of Main Pump	N.A.	N.A.	N.A.		
	Number of main pumps	N.A.	N.A.	N.A.		
	Jockey pump out put	N.A.	N.A.	N.A.		
	Jockey pump head	N.A.	N.A.	N.A.		
	> Standby pump out put	N.A.	N.A.	N.A.		
	Standby pump Head	N.A.	N.A.	N.A.		
	Auto Starting / Manual stopping	N.A.	N.A.	N.A.		
	Pump House Access	N.A.	N.A.	N.A.	***	
	Terrace Level					
	Discharge of pump	450 LPM	450LPM	MR	1	
	Head of the Pump	40 m	40 m	MR	-	
_	Power supply	Required	Provided	MR		
	Auto Starting of pump			17111		

Om International Guest House at C-15/219, Opp. District Centre, Laxmi Nagar Delhi-92.

14	Captive Water Storage for Fire Fighting.				
	Underground tank capacity	N.A.	N.A.	N.A.	
	Draw-off connection	N.A.	N.A.	N.A.	
	Fire service inlet	N.A.	N.A,	N.A.	
	Access to tank	Required	Provided	MR	
	Overhead Tank capacity	12,000 Liters	12,000 Liters	MR	
15	Exit Signage.	Required	Provided	MR	
16	Provision of Lifts.				
	Pressurization of Lift Shaft	N.A.	N.A.	N.A.	
	Pressurization of Lift lobby	N.A.	N.A.	N.A.	
	Communication in lift car	Required	Provided	MR	
	Firemen's grounding switch	Required	Provided	MR	
	Lift Signage	Required	Provided	MR	
17	Standby power supply	Required	Provided	MR /	
18	Refuge Area.				
	Total area	N.A.	N.A.	N.A.	
	Location	N.A.	N.A.	N.A.	
19	Fire Control Room				
	Detector system panel	N.A.	N.A.	N.A.	
	Flow switch panel	N.A.	N.A.	N.A.	
	PA system panel	N.A.	N.A.	N.A.	
	Batter backup	N.A.	N.A.	N.A.	
	Building Floor Plans	N.A.	N.A.	N.A.	
20	Special Fire Protection systems for protection of special Risks, if any:	N.A.	N.A.	N.A.	

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the Rules the NOC issued vide Letter No- F.6/DFS/MS/GH/2014/686 dated 05/06/14 renewal under Rule 35 of the Delhi Fire Service Rules 2010 is recommended.

Signature of the Inspecting Office 2017

Name

R.K.Yadav

Designation

ADO (LN)

Submitted please

DO (EAST)