GOVERNMENT OF NATIONAL CAPITAL TERRITOTY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110001

Fax No. 011-23412593, Ph. 011-23412225

No. F6/DFS/MS/Indl/2017/SZ/

891

Dated: 21/06/17

FIRE SAFETY CERTIFICATE

Phase-II, New Delhi-110020, comprised of Basement, Ground, Mezzanine + One upper floor was granted Fire Safety Certificate by this department vide letter No. F6/DFS/MS/2013/SZ/1366 dated 31/12/2013. The building/premises was re-inspected by the officer concerned of this department on 03.06.2017 in the presence of Mr. Inderpal Singh (Director) and found that the said premises have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class "Industrial Building" Group-G with effect from the date of issue of this certificate for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on . 21./06/47... at New Delhi by

(Vipin Kental) Chief Fire Office

Copy to:-

1. M/s Ultimate Fashions Pvt. Ltd., S-41, Okhla Industrial Area, Phase-II, ND-110020

2. The Ex. Engineer (Bldg.), Bldg. Deptt., South MCD, Civic Centre, Minto Road, ND -110002

Conditions for the validity of Fire Safety Certificate

- 1. All the fire safety and means of escape facilities shall be maintained in good working condition at all time. Any lapse rendering the fire safety or means of evacuation facilities non-functional shall be the responsibility of the management.
- 2. Building Sanctioning authority may verify any deviation with regard to construction/occupancy in the building. In case of any deviation, the fire safety certificate stands null & void.
- 3. The staff shall be trained for operating fire fighting system and mock evacuation drill be conducted at regular interval and record be maintained
- 4. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 5. The Owner/Occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules, 2010. The form is available on www.dfs.delhigovt.nic.in.
- 6. The Owner/Occupier shall apply for renewal of this Fire Safety Certificate to the Director in the form 'J' [sub rule (1) of rule 37] along with copy of this certificate, six months prior to its expiry. The form is available on www.dfs.delhigovt.nic.in.

	INSPECT	TON REPOR	RT -		-	
1	Name & Address of the Building	M/s Ultimate Fashions Pvt. Ltd, S-41, Okhla Industrial Area Phase-II, New Delhi-20				
2	Type of Occupancy	Industrial Building (Group-G)				
3	Building Comprised of	Basement, Ground, Mezzanine + 1 upper floor.				
4	Type of Case	Renewal	Tourc	i, iviczzannie i i uppe	1 11001.	
5	Details of Previous NOC		/2013	/SZ/1366 Dated 31-12	2 2013	
6	Fire Safety Directives Letter No			P/549 Dated 06-04-19		
7	Date of Inspection	03-06-2017	() (ID	17547 Daica 00-04-15	74	
8	Name of the Inspecting Officers	ADO R.N. Singh				
9	Name & Designation of Officers	Mr. Inderpal Singh (Director)				
	from the building side	in inderput shigh (Director)				
10	Year of construction	1994			*	
11	Applicant letter No.	Nil Dt. Nil O	DDN	lo. 6709 Dt. 18.05.201	17	
S. No	Minimum standards on Fire	As Per Ole		Provided at Site	Remarks	
	Prevention and Fire Safety U/R 33	NOC-201.			MR/NMI	
1	Access to Building.				1721011111	
	1. Road width	Required		6 mtr	MR	
	2. Gate width	Required		4.5 mtr	MR	
	3. Width of internal road	N/A	7,000			
2	Number, width, type and arrangements			N/A	N/A	
Žid.	a. Number of Staircase	or exits.				
	1. Upper floors	2 No's 2 No's				
	2. Basement floor			2 No's	MR	
	, and the control of	2 No's 2 No's		MR		
	b. Width of Staircase					
	1. Upper floors				MR (old case)	
	2. Basement floor	Required 1.25 & 1.14 r		1.25 & 1.14 mtr	MR (old case)	
	c. Protection of exits 1. Fire check door					
		Required in basement Provided		MR		
	2. Pressurization	N/A N/A		N/A		
	d. No. of continuous staircase to terrace	Two		Two	MR	
	e. Width of corridor	N/A N/A		N/A		
	f. Door size	N/A		N/A	N/A	
3	Compartmentation.			3 1		
	1. Fire check door.	Required in basement		nt Provided	MR	
	2. Sealing of electrical shafts.	N/A		N/A	N/A	
	3. Fire rating of shaft door.	N/A		N/A	N/A	
	4. Water curtain	N/A		N/A	N/A	
	5. Fire dampers.	N/A				
4.	Smoke Management system.	N/A		N/A	N/A	
7.	1. Basement	30 a/c par hour Evhauet for and 1 1		1 10		
1	2. Upper floors			Exhaust fan provided	MR	
		12 a/c per not	ui	Exhaust fan provided	MR	
5.	11					
5.	Fire Extinguishers.			22 No.20	MD	
5.	Fire Extinguishers. 1. Total numbers	ISI Markad	Co2	22 No's	MR	
5.	Fire Extinguishers. 1. Total numbers 2. Types	ISI Marked	Co2-(07, W.Co2-05, ABC-10	MR	
	Fire Extinguishers. 1. Total numbers 2. Types 3. ISI Marking	ISI Marked	Co2-6			
5.	Fire Extinguishers. 1. Total numbers 2. Types 3. ISI Marking First Aid Hose Reels.		Co2-(97, W.Co2-05, ABC-10 Provided	MR MR	
	Fire Extinguishers. 1. Total numbers 2. Types 3. ISI Marking First Aid Hose Reels.	ISI Marked Hose-reel	Co2-(07, W.Co2-05, ABC-10	MR	

7	Automatic Fire Detection and Alarming sy	N/A	N/A	N/A
	1. Type of detectors	N/A N/A	N/A	N/A
	2. Location of Main Panel	N/A	N/A	N/A
	3. Location of Repeater Panel	N/A N/A	N/A	N/A
	Alternate source of power Hooter's location	N/A N/A	N/A	N/A
		N/A	N/A	N/A
8.	MOEFA		N/A	N/A
9.	Public Address System	N/A	IN/A	IN/A
0.	Automatic Sprinkler System	DT/A	Provided	N/A
	1. Basement	N/A	N/A	N/A
	2. Upper floors	N/A	N/A N/A	N/A
	Sprinkler above false ceiling	N/A	IN/A	IVIA
1.	Internal Hydrants.	DI/A	N/A	N/A
	Size of Riser / Down-comer	N/A	N/A	N/A
	2. Number of Hydrant per floor	N/A		N/A
(4)	3. Hose box.	N/A	N/A	IN/A
12.	Yard Hydrants.	DT/A	NI/A	N/A
	Total number of hydrants.	N/A	N/A	-
	2. Hose box.	N/A	N/A	N/A
13.	Pumping arrangements.			
	Ground Level			27/1
	Discharge of main pump.	N/A	N/A	N/A
	> Head of main pump.	N/A	N/A	N/A
	Number of main pumps.	N/A	N/A	N/A
	> Jockey Pump output.	N/A	N/A	N/A
	Jockey Pump head.	N/A	N/A	N/A
	Standby Pump output.	N/A	N/A	N/A
	Standby Pump head.	N/A	N/A	N/A
	Auto Starting / Manual Stopping.	N/A	N/A	N/A
	Pump House Access	N/A	N/A	N/A
	Terrace Level			
	Discharge of pump.	Required	1200 LPM	MR
	> Head of pump.	Required	40 mtr	MR
	Power supply.	Required	Provided	MR
	Auto starting of pump.	Required	Provided	MR
14.	Captive water storage for fire fighting.			
	Underground tank capacity.	N/A	N/A	N/A
	> Draw-off connection.	N/A	N/A	N/A
-	Fire Service Inlet.	N/A	N/A	N/A
	> Access to tank.	N/A	N/A	N/A
	Overhead tank capacity.	5,000 Ltr	20,000 Ltr	MF
15.	Exit Signage.	Required	Provided	MF
16.	Provision of Lifts.			
	Pressurization of lift shaft.	N/A	N/A	N/A
	2. Pressurization of lift lobby.	N/A	N/A	N/A
	3. Communication in lift car.	N/A	N/A	N/A
	4. Fireman's switch.	N/A	N/A	N/A
			N/A	N/A
	5. Lift signage.	N/A		
17	Standby Power Supply	Required	Provided (DG Set)	MI
18.	Refuge Area		274	1 21
101	1. Total area	NA	NA	N/
	1. Total area	NA	NA	NA

19.	Fire Control Room.	1	•	NIA
17.		NA	NA	NA
 Detector System Panel. Flow Switch Panel. PA system Panel. Battery backup Building floor plan 	 Flow Switch Panel. PA system Panel. 	NA	NA	NA
		NA	NA	NA
		NA	NA	NA
	4. Battery backup	NA	NA	NA
		Required	02 No's Co2 type fire	MR
20.	Special Fire Protection System for the Protection of special Risk, if any.		extinguisher provided	and the second

The fire protection system provided in the building were tested and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards on fire prevention and fire safety measures as required under rules, renewal of the FSC issued vide letter No. F.6/DFS/MS/2013/SZ/1366 dated 31.12 2013, under rule 37 of the Delhi Fire Service Rules, 2010 is recommended.

Accordingly DFA is put up for perusal and signature please

Signature of the Inspecting Officer

Name

: R.N. Singh

Designation: ADO

Div. Officer (SD)

Dy Golses

9