GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE: NEW DELHI - 110001

No F 6 / DFS / MS / 2017 / 913

Dated 23 /6 42017

FIRE SAFETY CERTIFICATE

Certified that the Multi Level Automated Car Parking Cum Commercial Complex at Kamla Nagar, Delhi comprised of 8 Level basement, G + 02 Upper floors owned/occupied by MCD was issued FSC vide letter no. F-6/DFS/MS/2014/WZ/565 dated 05/05/2014 and have deemed complied with the fire prevention and fire safety requirement in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and verified by the officer concerned of fire service on 07/06/2017 in the presence of Mr. Pranav kumar and that the building/ premises is fit for occupancy Parking Cum Commercial Complex building with effect from/2017 for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Conditions for the validity of Fire Safety Certificate:

- 1. Means of escape shall not be kept locked or bolted from outside and shall be easioy open able by guests in an event of emergency.2.
- 2. All employees shall be acquainted with the use and maintenance of all the fire fighting installation/equipments. 3.
- 3. The fire suppression / protection arrangements provided in the guest house are minimize losses, if maintained in good working condition. These systems cannot give any guarantee that there will be no fire or losses in the event of one.
- 4. Any loss of life and property due to non-functional of fire safety arrangements and other installations shall be the responsibility of the license.
- 5. This report may not in any way be treated as regularization of unauthorized construction, if any.
- 6. The basement shall only be used for car parking, 08 level in crated with brick wall.
- 7. The owner / occupier shall submit a declaration every year in form "K" provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.Delhigovt.nic.in

Issued on 23.06.2017 at New Delhi by

Chief Fire Officer Ph-011-23414250

Copy to:-

- 1. The Executive Engineer, Project-III / Rohini Zone, M C D Office Complex, Under
- . Ground Car Parking, Asif Ali Road, Delhi Gate, New Delhi-110002

INSPECTION REPORT

1. Name & address of the building: Multi Level Automated Car Parking Complex at Kamla Nagar

2. Type of Occupancy

: Parking Cum Commercial Complex

3. Type of Case

: Renewal

4. Details of previous NOC

: F.6/DFS/MS/2014/WZ/565 dated 05/05/2014

5. Fire Safety directives letter No : F6/DFS/MS/BP/2008/2907 Dated 21/10/2008

6. Date of inspection

: 07/06/2017

7. Name of the Inspecting Officers: DCFO (WZ) & ADO (RN)

8. Name and designation of officers

from the building side

: Mr. Pranav Kumar

9. Year of Construction

: 2013

10. Applicant's letter No.

: Diary no.4190 dated 05/04/2017

	Minimum Standards on fire prevention and fire safety U/R 33	NBC Requirement	Provided at site	Remarks MR/NMR	
1	Access to building				
	Road width	6 mtr	14.3 mtr	M/R	
	• Gate width	5 mtr	5 mtr	M/R	
	Width of internal road	N/A	N/A	N/A	
2	Number, Width, Type & Arrangement of Exits				
	a. Number of staircases		x		
	Upper Floors	06	06	M/R	
	Basements	06	06	M/R	
	b. Width of staircases				
	• Upper Floors	2 S/C of 1.5 m & 02 lifts from G.F to upper floor	Provided	M.R	
	• Basements	6 S/C of 1.25 CM & 06 car lift in B/W	(i) 1060 mm to 1160 mm (ii) 960 mm to 1150 mm (iii) 1030 mm to 1170 mm (iv) 1080 mm to 1130 mm (v) 1080 mm to 1170 mm (vi) 1030 mm to 1200 mm	Request received from management may be accepted	
	c. Protection of exits				
	Fire check door	Required	Provided	M/R	
	• Pressurization	02	02	M/R	
	e. No. of continuous staircases to terrace	N/A	N/A	N/A	
		N/A	N/A	N/A	
	g. Width of Corridor h. Door Size	1 mtr x 2.1 mtr	Height of some doors still less than 2.1 mtr due to ventilation duct in staircase lobby	Request received from management may be accepted	

3	Compartmentation.				
	Fire check door	Required	Provided	M/R	
	Sealing of electrical shafts	Required	Provided	M/R	
	Fire Rating of shaft door	N/A	N/A	N/A	
	Water Curtain	N/A	N/A	N/A	
100	Fire Dampers	N/A	N/A	N/A	
1	Smoke Management System.				
	• Basements	30 a/c per hour	Exhaust fan Provided	M/R	
	Upper floors	12 a/c per hour	Natural Ventilation	M/R	
5	Fire Extinguishers		**		
	Total numbers	102 Water Co2	Water Co2= 10, 9 ltr each DCP type= 120, 5kg each	M/R	
	• Types	DCP type / co2	Mechanical form= 6, 9 ltr	M/R	
	IS marking	ISI marked	Co2 type = 6 , 6 kg each	M/R	
6	First-Aid Hose Reels.				
	Total numbers on each floor	06	06 + 02	M.R	
	 Length of hose reel hose 		02 additional hose reel provided		
		30 m	Provided	M.R	
	Nozzle diameter	5 mm	Provided	M.R	
7	Automatic fire detection and alarming system.				
	Type of detectors				
	Location of Main Panel	On G.F	Provided	M.R	
	Location of Repeater Panel	N/A	N/A	N/A	
	Alternate source of power	Required	Provided	M/R	
	Hooters' Location	Common areas	Provided	M.R	
	1.000			2.5/50	
8	MOEFA	Required	Provided	M/R	
	MOEFA Public Address System.	Required	Provided Provided	M/R M/R	
9	Public Address System. Automatic Sprinkler System.				
9	Public Address System. Automatic Sprinkler System. Basement	Required	Provided	M/R	
9	Public Address System. Automatic Sprinkler System. Basement	Required	Provided Provided Provided	M/R	
	Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling	Required Required Required	Provided Provided	M/R M/R M/R	
9	Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants	Required Required Required N/A	Provided Provided Provided No false celling at present	M/R M/R M/R N/A	
9	Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants Size of riser/down-comer	Required Required Required	Provided Provided Provided No false celling at present 06 + 02 02 additional hydrants	M/R M/R M/R	
9	Public Address System. Automatic Sprinkler System. Basement Upper Floor Sprinkler above false ceiling Internal Hydrants	Required Required Required N/A	Provided Provided Provided No false celling at present	M/R M/R M/R N/A	

12	Yard Hydrants.		, , ,		
	Total number of hydrants	05	Provided	M/R	
	Hose Box	05	Provided	M/R	
13	Pumping Arrangements.				
	Ground Level		,		
	Discharge of main Pump	2850 LPM	Provided	M/R	
	Head of Main pump	60 M	Provided	M/R	
	Number of main pumps	02	Provided	M/R	
	Jockey Pump out put	180 LPM	Provided	M/R	
	Jockey pump head	60 M	Provided	M/R	
	Standby Pump out put	2850 LPM	Provided	M/R	
	Standby Pump Head	60 m	Provided	M/R	
	➤ Auto Starting/ Manual	Required	Provided	M/R	
	stopping > Pump House Access	Required	Provided	M/R	
	Terrace level				
	Discharge of pump	N.A	N.A	N.A	
	Head of the pump	N.A	N.A	N.A	
	Power Supply	N.A	N.A	N.A	
	Auto Starting of pump	N.A	N.A	N.A	
14	Captive Water Storage for fire fighting		***************************************	.151	
	Underground tank capacity	120,000 ltr	Provided	M.R	
	> Draw-off connection	Required	Provided	M/R	
	Fire service inlet	Required	Provided	M/R	
	> Access to tank	Required	Provided	M/R	
	Overhead Tank capacity	75000 ltr	Provided	M.R	
15	Exit Signage.	Required	Provided	M/R	
16	Provision of Lifts.				
29	Pressurization of Lift Shaft	N.A	N.A	N.A	
	Pressurization of Lift lobby	N.A	N.A	N.A	
	Communication In lift Car	N.A	N.A	N.A	
	Fireman's Grounding Switch	N.A	N.A	N.A	
	Lift Signage	N.A	N.A	N.A	
17	Standby power supply	Required	Provided	M/R	

18	Refuge Area.			
	> Total Area	N.A	N.A	N.A
	> Location	N.A	N.A	N.A
19	Fire Control Room			
	Detector System Panel	Required	Provided	M/R
	 Flow Switch Panel 	Required	Provided	M/R
	PA System Panel	Required	Provided	M/R
	Batter backup	N.A	N.A	N.A
	 Building Floor Plans 	N.A	N.A	N.A
20	Special Fire Protection Systems for Protection of special Risks, if any:	N.A	N.A	N.A

The fire protection systems provided in the building were test checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of the fire prevention and fire safety measures as required under the rules the NOC issued vide letter no. F.6/DFS/MS/2014/WZ/565 dated 05/05/2014 renewal under rule 35 of the Delhi Fire Service rules 2010 is recommended.

Sugh

Signature of the Inspecting Officer

Name Sured Suyl
Designation Do (NW) Name

Signature of the Inspecting Officer

Name Rajesh Cumar Designation ADO/RN.