FORM 'H'

FORM FOR ISSUING FIRE SAFETY CERTIFICATE

[Refer sub - rule (1) of rule 35]

GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS: DELHI FIRE SERVICE, CONNAUGHT PLACE

NEW DELHI

No.F6/DFS/MS/2017/WZ/ 930

Dated: 28 /06/2017

FIRE SAFETY CERTIFICATE

Certified that the Plot No. C -4, 5, 6, located at Netaji Subhash Place, Pitampura, Delhi – 110034 comprised of 2 Blocks (B+G+10 Upper Floors & B+G+5 Upper Floors) was issued FSC vide Letter No. F6/DFS/MS/2014/WZ/269 dated 25-02-2014. The premises was re inspected by the officers concerned of this department on 24-05-2017 in the presence of Mr. Sunil Jain (Vice President) and found that the said building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rule, 2010 and that the premises is fit for occupancy class "Mercantile & Business Building" Group F & Group E with effect from for a period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules, 2010.

Issued on ... 28. / . 0.6/1.7... at New Delhi by.

(Att) Garg) Chief Fire Officer, Delhi Fire Service.

Copy to:

Sh. Sunil Jain (Vice President)
 Plot No. C – 4, 5, 6,
 Netaji Subhash Place, Pitampura, Delhi – 110034.

Following fire safety directives must be adhered to:-

- 1. All the fire safety arrangements provided therein shall be maintained in good working condition at all times.
- 2. Any loss of life or property due to non-functional fire safety measures shall be at the risk and responsibility of the management.
- 3. The trained staff should be available round the clock.
- 4. Any deviations w.r.t. construction shall be verified by the concerned building sanctioning agency.
- 5. The certificate may not be treated in any case for the regularization of the unauthorized construction, if any.
- 6. The owner/ occupier shall apply for renewal of this Fire Safety Certificate to the Director in Form 'J' [sub rule (1) of rule 37] along with a copy of this certificate, six months prior to its expiry.
- 7. Basement shall be used strictly as per building bye laws.
- 8. The owner/occupier shall submit a declaration every year in the form 'K' provided in the first schedule of Delhi Fire Service Rules 2010, form is available on www.dfs.delhigovt.nic.in.

1. Name & address of the building: C-4,5,6, Netaji Subhash Place, Pitam Pura, Delhi

2. Type of Occupance : Mercantile + Business (Mixed), 2 Blocks (B+G+10 Upper Floor & B+G+5 Upper Floor)

3. Type of Case

: Renewal

4. Details of previous NOC: Letter No. F6/DFS/MS/2014/WZ/269 dated 25-02-14

5. Fire Safety directives Letter No. F6/DFS/MS/BP/2001/542 dated 28-03-2001

6. Date of inspection

: 24-05-2017

7. Name of the Inspecting Officer: DO (West) & ADO (WP)

8. Name and designation of Officer

from the building side

: Sh. Sunil Jain (Vice President)

9. Year of Construction

: 2001

10. Applicant's letter No.: UBL/DIR/ACN/DFS/2K17/0231 dated 02-05-2017

C			2K17/0231 dated 02	-03-2017			
S No	Minimum standards on fire	BBL	Provided at	Remarks MR/NMR			
	prevention and fire safety U/R 33	Requirements	site				
1.	Access of building						
	Road width	24 m	Provided	MR			
	Gate width	6 m		MR			
	 Width of internal road 	6 m		MR			
2.	Number, width, Type & Arrangeme						
	a. Number of staircases	IIIS OF CAILS					
	Upper floors	2	2	1 (D			
	Basements	2		MR			
	b. Width of staircases	2		MR			
	Upper floors	1.5m & 1m	Duari d - 1/01 1)			
	Basements	1.5m & 1m	Provided(Old case				
	c. Protection of exits	1.5111 & 1111	Provided(Old case) MR			
	Fire check door	D 1					
	Pressurization	Required	Provided	MR			
	d. No of continuous staircase	Required	Open able window	w MR			
	to terrace	Required	Provided	MR			
	e. Width Of Corridor	1.5m	Provided(Old case	e) MR			
	f. Door Size	1m	Provided(Old case	e) MR			
3.	Compartmentation			/			
	Fire check door	Required	Provided	MR			
	 Sealing of electrical shafts 	Required	Provided	MR			
	 Fire Rating of shaft door 	Required	Provided				
	 Water Curtain 	Not Required	Not Required	MR			
	 Fire Dampers 	Required	Provided	NR			
4.	Smoke managements System		Tiovided	MR			
	Basements	30 a/c per hour	Exhaust Fans Prov	vided MD			
	 Upper floors 	12 a/c per hour	Open able Window				
5.	Fire Extinguishers	Por Mour	open able willdov	w MR			
	Total numbers	45 nos.	Provided	MD			
	Types	CO2 & WCO2	Provided	MR			
	IS marking	ISI marked	Provided	MR			
6.	First – Aid Hose Reels		TTOVICE	MR			
	Total numbers on each floor	1	Provided	100			
	• Length of hose reel hose	30 m	Provided	MR			
	No-1- 1	<i>-</i>	Trovided	MR			

		Type of detectors	Smoke & rieat	Tiovided		MR	
		Location of Main Panel	Required	Provided		MR	
		Location of Repeater Panel	Required	Provided		MR	
		• Alternate source of power	Required	Provided		MR	
		Hooters' Location	Required	Provided			
	7.10		Required	Provided		MR	
8.		EFA	Required	Provided		MR	
9.	Pub	lic Address System	1				
10.	Automatic Sprinkler System Required Provided MR						
		Basements Linear Floor	Required	Provided	MR		
		 Upper Floor Sprinkler above false ceiling	Required	Provided	MR		
	7						
11.	Inte	• Size of riser/down- comer	150 mm	Provided	MR		
			1	Provided	MR		
		• Number of hydrants per					
		floor	Required	Provided	MR		
		Hose Box	1				
12.	Ya	rd Hydrants	5	Provided	MR		
		Total number of hydrants	Required	Provided	MR		
		Hose Box	Required				
13.	Pu	mping Arrangements					
		Ground Level	2850 lpm	Provided	MR		
		 Discharge of main pump 	75 m	Provided	MR		
la la		Head of main pump		Provided	MR		
		Number of main pumps	220.1	Provided	MR		
		Jockey pump out put	220 lpm	Provided	MR		
		Jockey pump head	75 m	Provided	MR		
		Standby Pump out put	2850 lpm	Provided	MR		
		Standby Pump Head	75 m	Provided &	MR		
		Auto Staring/Manual	Required	Functional	IVIIC		
		stopping	2 1	Provided	MR		
		Pump House Access	Required	Provided	IVIIC		
		 Terrace level 		NID	NR		
		Discharge of pump	Not Required	NR	NR		
		Head of the pump	Not Required	NR	NR		
		> Power supply	Not Required	NR	NR		
		> Auto starting of pump	Not Required	NR	INK		
14	1 (Captive water Storage for fire figh	ting	- 111	MD		
12	7.	Under ground tank capacit	y 2,00,000 nues	Provided	MR		
		Draw of connection	Required	Provided	MR		
		Fire service inlet	Required	Provided	ME		
		> Access to tank	Required	Provided	MF		
		 Overhead Tank capacity 	30, 000 litres	Provided	MF		
1	5	Exit Signage	Required	Provided	MI	<	
		Provision of Lifts					
1	6.	> Pressurization of Lift Shat	ft Required	Provided	MI		
		 Pressurization of lift lobby 		Provided	M		
				Provided	M		
		1.0	Required	Provided	M		
			Required	Provided	M	R	
		Switch Lift Signage	required				
		Lift Signage	Required	Provided	M	R	
	17.	Standby power supply	7.54				
	18.	Refuge Area	Old Case	Old Case		ld Case	
> Total area		5 th , 7 th , 9 th Fl		N.	IR.		
Location				,	,		
19. Fire control room							
		1	Required	Provided	N	1R	
		> Detector system panel	Required	Provided	N	1R	
		> Flow Switch Panel	Required	Provided	N	1R	
		> PA System Panel	Required	Descrided	N	/IR	

					- 24			
20.	Special Fire Protecti Protection of specia	on Systems for l Risks, if any;	NR	NR	NR			
	functional at the time In view of the de safety as required F6/DFS/MS/2014/W.	The fire protection systems provided in the building were test checked and found notional at the time of inspection. In view of the deemed compliance of minimum standards on fire prevention and fire						
	Signature of the Insp	ecting Officer	Signature o	f the Inspec	ting Officer			
	Name Udavir Singh	I .	Name Sh M	Iukesh Veri	ma			
	Designation ADO	/WP	Designation	n DO/West				
	Dyofo -	on leav	-e					
	CCO	Vert to						