GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2017/ ND2 / 938

Dated : 29/6/17

FIRE SAFETY CERTIFICATE

Certified that the Ved Palace Guest House located at 3804-06, Gali Ram Nath Patwa, Pahar Ganj, New Delhi comprised of Ground + 03 Upper floors, Ground floor (04 guest rooms + Reception), 1st floor to 3rd floor (06 guest rooms at each floor) and Terrace floor (sealed by MCD), total 22 guest rooms was granted FSC by this department vide letter No.F6/DFS/MS/GH/2014/NDZ/728 dated 13/06/14. The premises was re-inspected by the officer concerned of this department on 15/06/17 in the presence of Mr. Rakesh Kumar (Manager) and found that the said guest house building have deemed complied with the fire prevention and fire safety requirements in accordance with rule 33 of the Delhi Fire Service Rules, 2010 and that the premises is fit for occupancy class Residential, Sub Division-A-1 as above 22 guest rooms only with effect from -23-1-511-7--- for period of three years in accordance with rule 36 unless renewed under rule 37 or sooner cancelled under Rule 40 and subject to compliance of the conditions under rule 38 of the Delhi Fire Service Rules 2010, printed below.

Issued -- 29/6/17 -at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service de me

Copy to:-

- 1. The Joint Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi ref. letter no. 869/Addl. C.P./ Lic (11) dated 05/05/17.
- 2. The Manager, Ved Palace Guest House at 3804-06, Gali Ram Nath Patwa, Pahar Ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.

3. The trained fire fighting staff should be available round the clock.

- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

- N/16-

	INSP	ECTION REPO	ORT				
1.	Name & address of the building		Ved Palace Guest House at 3804-06, Gali				
		Ram Nath Patwa, Pahar Ganj, New Delhi					
2.	Type of occupancy:-	Residentia	l, Sub Division-A-1				
	Gr. + 03 Upper floors (total 22 Guest rooms) Ground floor (04 guest rooms + Reception), 1 st floor to 3 rd floor (06 guest rooms at each floor) and						
3	Type of case:-	Terrace floor (sealed by MCD). Renewal					
	Details of previous FSC:-	No. F6/DFS/MS/GH/2014/NDZ/728 dated					
·	Details of previous 1 Se.	13/06/14.					
	Fire safety directives No	N/A					
	Date of inspection:-	15/06/17					
	Name of the inspecting officer	, , ,					
8.	Name & designation of officer						
From t	he building side:-	Mr. Rakas	sh Kumar (Manager))			
9.	Year of construction:-	2001					
10.	Applicant's letter No:-	869/Joint C	P./ Lic.(H) dated 0:	5/05/17.			
				Old Case			
S.No.	Minimum Standards on fire	Requirement/	Provided at site	Remarks			
	Prevention and fire safety	Existing fire		MR/NMR			
	U/R 33	safety arrangements					
1.	Access to Building	arrangements	,				
	1) Road width	N/A	03 mtr.	N/A			
	2) Gate width	N/A	N/A	N/A			
	3)Width of internal road	N/A	N/A	N/A			
2.							
4 .	Number, Width Type & Arrangement of Exits A. Number of staircases						
	1. Upper floors	01 Nos.	01 Nos.	MR			
	2. Basements	N/A	N/A	N/A			
	B. Width of staircase	14/14	14/71	14/14			
	1. Upper floors	0.80 mtr.	1.08 mtr.	MR			
	2. Basements	N/A	N/A	N/A			
	C. Protection of exits	IVA	IN/A	IN/A			
	1. Fire check door	N/A	. N/A	N/A			
	2. Pressurization	N/A	N/A				
	D. No. of continuous	01	01	N/A MR			
	staircase to terrace	OI.	V.I	IVIIX			
	E. Width of corridor	01 mtr.	0f mtr.	01 mtr.			
	F. Door size	01 mtr.					
3.		Of mir.	01 mtr.	01 mtr.			
J.	Compartmentation	127/4	27/4	127/			
	1) Fire check door	N/A	N/A	N/A			
	2) Sealing of electrical shafts	N/A	N/A	N/A			
	3) Fire rating of shaft door	N/A	N/A	N/A			
	4) Water curtain	N/A	N/A	N/A			
	5) Fire Dampers	N/A	N/A	N/A			
4.	Smoke Management System			<u> </u>			
	1) Basements	30 ACPH	N/A	N/A			
1	2) Upper floors	12 ACPH	Natural	MR			
5.	Fire Extinguishers			1 8			
	1) Total numbers	10 Nos.	12 Nos.	MR			

*	(a) T	AT	3C & CO2	Λ1	BC & CO2	N	IR .
	2) Types		quired	-	ovided		IR
	3) ISI marking	No	quireu	11	Ovided	14	
6.	First-Aid Hose Reel	or 01		01	1	1	1R
	1) Total number of eachfloo		mtr.) mtr.	-	IR IR
	2) Length of hose reel hose				5 mm		ÍR
	3) Nozzle diameter		mm) IIIII	IV	IK
7.	Automatic Fire Detection & Alarming System 1) Type of detectors N/A N/A						I/A
	1) Type of detectors						I/A
	2) Location of main panel	N/					J/A
	3) Location of repeater pane				N/A N/A		J/A
	4) Alternate source of power						J/A
	5) Hooter's Location	N/		N/A			
8.	MOEFA		equired		rovided	-	/IR
9.	Public Address System		equired	P	rovided	1	ИR
10.	Automatic Sprinkler Syst	em				1	T / A
	1) Basement	N/			I/A		N/A
	2) Upper floors	N/			I/A	-	N/A
	3) Sprinkler above false ceiling	N/	'A	N	I/A	1	N/A
11.	Internal Hydrants						
11.	1) Size of riser/down-come	er N	/A	N	J/A	7	V/A
	2) Number of hydrants per				V/A		V/A
	floor	14/					
	3) Hose box	N/	/A	N	J/A	1	V/A
12.	Yard Hydrants	1 1/		1			
12.			/A	N	J/A	1	N/A
	2) Hose box		/A		V/A		N/A
13.	Pumping Arrangement					+	
13.	1) Ground level		N/A		N/A	1	N/A
		in	N/A		N/A	1	N/A
	1 1	111	IVA		14/21		1077
	b) Head of main pu	mn	N/A		N/A		N/A
			N/A		N/A		N/A
		Number of main pump			N/A		N/A
			N/A N/A	- 19	N/A		N/A
			N/A	5	N/A		N/A
			N/A		N/A		N/A
		tand by pump head uto starting/Manual			N/A	- Constant	N/A
	,	ınual	N/A		INIT	O DECEMBER OF THE PARTY OF THE	1 1/11
	stopping					-	
		Terrace level		1	450 LPM		MR
		Discharge of pump		1	30 mtr.		MR
	b) Head of pump			1	Provided		MR
	c) Power supply		Required		Provided		MR
	d) Auto starting of	pump	Required		Flovided		IVIIV
14.	Captive Water Storage			ıg	NI/A		N/A
	1) Under ground tank ca		N/A		N/A		N/A
	a) Draw-off connec		N/A		N/A		N/A N/A
	b) Fire service inle	t	N/A		N/A		IN/A

	c) Access to tank	Required	Provided	MR	
	d) Over head tank capacity	2500 ltr.	2500 ltr.	MR	
15.	Exit Signage.	Required	Provided	MR	
16.	Provision of Lifts.				
	a) Pressurization of lift	N/A	N/A	N/A	
	b) Pressurization of lift lobby	N/A	N/A	N/A	
	c) Communication in lift car	N/A	N/A	N/A	
	d) Fireman's switch	N/A	N/A	N/A	
4	e) Lift signage	N/A	N/A	N/A	
17.	Stand by Power Supply	Required	Provided	MR	
18.	Refuge Area	N/A	N/A	N/A	
10.	Total area location	N/A	N/A	N/A	
19.	Fire Control Room	N/A	N/A	N/A	
	a) Detector system panel	N/A	N/A	N/A	
	b) Flow switch panel	N/A	N/A	N/A	
	c) PA system panel	N/A	N/A	N/A	
	d) Battery backup	N/A	N/A	N/A	
	e) Building floor plan	N/A	N/A	N/A	
20.	G Drotection of enecial				

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2014/NDZ/728 dated 13/06/2014 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma Designation: - ADO (CC)

39/c/052 33/6/12/29/6 Doled

Dy CRO (XDZ)