GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEADQUARTERS: DELHI FIRE SERVICE: NEW DELHI- 110 001

No. f6/0fs/ons/2017/967

Dated: 6/7/17

FIRE SAFETY CERTIFICATE

(Vipin Kental)
Chief Fire Officer
T. No.011- 23412225

OIC

Copy to:-1. Sh. B.D.Sukla, DGM (Engg), NBCC, Block No.04, GPRA, New Moti Bagh, N.D.

2 .President, GPRA Residents Association, Block No.06, GPRA, New Moti Bagh, New Delhi-110023.

Conditions for the validity of fire safety certificate are as under:-

1. All the means of escape shall be kept free of all type of obstruction all the time.

2. The employees shall be acquainted with the use and maintenance of all fire equipments and method of smooth and speedy safe evacuation of occupants in case of emergency.

3. All fire fighting equipments shall be maintained in perfect working condition all time and any lapse rendering non-functional of fire safety measures, management shall be responsible.

4. Any deviation, with regards to construction, ventilation, occupancy, electric installation etc. may be got verified from the concerned authorities.

5. This Fire Safety Certificate may not be treated in any case for regularizations of unauthorized construction unauthorized use of land if any.

6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rule 2010. The form is available on www.dfs.delhigovt.nic.in.

7. The owner/occupier shall apply for renewal of this Fire Safety Certificate, six month prior to its expiry.

		INC	DECTION	DEDODT				
1	Name & address of the building M/s Block No.04. General Pool Residential Accommodation							
1	ivalle & address of the building	M/s Block No.04, General Pool Residential Accommodation						
	Type of Occupancy		(GPRA), New Moti Bagh, New Delhi-110023. Residential Building "A"					
2		9						
3	Type of case	Renewal						
4	Details of previous NOC		No.F6/DFS/MS/2012/2458, Dated 10.07.2012.					
5	Fire safety directives letter No	F.6/DFS	F.6/DFS/MS/CGHS/BP/2007/1304, Dated- 08.05.2007.					
6	Date of inspection	01.07.20	7.2017.					
7	Name of the inspecting Officers	Vedpal ADO.						
	Name and designation of officers	Sh. B.D.Sukla DGM (Electrical) NBCC.						
8	from the building side							
9	Building Comprised of	Stilt+09Upper floors. (Stilt=Parking & Upper Floors=04 Reside flats at each floor).						
10	Year of construction	2007-2010						
11	Applicant's letter No.	NBCC/E	NBCC/DGM/NMB/2017/330, Dated 09.06.2017.					
S. NO.	Minimum Standards on fire							
3. NO.	prevention and fire safety U/R		ments as	Provided at site	Remarks			
	33	per	BBL		MR / NMR			
1								
1	Access to building 1) Road width	0.00		05	Turb			
	2) Gate width	9m 5m		25m	MR			
	3) Width of internal road	6m		6m	MR MR			
2	Number, width Type & arrangem		its	John	INIT			
	a. Number of staircases							
	1. Upper floors	06nos.		06nos.	MR			
	2. basements	N/A		N/A	N/A			
	b. Width of staircase							
	1. Upper floors	1.25m/90	Ocm	1no=1.5m, 1no=1.25m & 4nos=90cm(each)	MR			
	2. Basements	N/A		N/A	N/A			
	c. Protection of exits	14//-			TW// X			
	1. Fire check door	Required		Provided	MR			
	2. Pressurization	N/A		N/A	N/A			
	d. No. of continuous staircase to terrace	06nos.		06nos.	MR			
	e. Width of corridor	N/A		N/A	N/A			
	f. Door size	1 Mtr		1Mtr	MR			
3	Compartmentation.							
	1. Fire check door	Required		Provided	MR			
	2. Sealing of electrical shafts	Required		Provided	MR			
	3. Fire Rating of shaft door	N/A		N/A	N/A			
	4. water curtain5. Fire dampers	N/A N/A		N/A	N/A			
4	Smoke Management system.	IIN/A		N/A	N/A			
	basement	30 a/c pe	er hour	N/A	N/A			
	Upper Floors	12 a/c pe		Natural Ventilation	MR			
5	Fire Extinguishers							
	total numbers	ABC & WCO2		48nos.	MR			
	Types			ABC & Water CO2	MR			
G	ISI marking	ISI Mark		ISI Mark MR				
6	First-Aid Hose Reels.	02555		00	IMP			
	total numbers on each floor Length of Hose reel hose	02nos.		02nos.	MR			
	Nozzle Diameter	30m 5mm		30m	MR			
	THOZZIC DIAMETER	SHILL		5mm	MR			

7	Automatic fire detection and alarming system						
	Type of detectors	N/A	N/A	N/A			
	location of Main Panel	N/A	N/A	N/A			
	location of Repeater panel	N/A	N/A	N/A			
	Alternate source of power	N/A	N/A	N/A			
	hooter's location	N/A	N/A	N/A			
8	MOEFA	Required	Provided	MR			
9	Public Address System.	Required	Provided	MR			
10	Automatic Sprinkler System.	, to quit ou	T TOVIGE G	IVIIX			
	basement	N/A	N/A	N/A			
	upper floors	N/A	N/A	N/A			
	sprinkler above false ceiling	N/A	N/A	N/A			
11	Internal Hydrants	14//	IN/A				
	Size of riser/down-corner	150mm	150mm	MR			
	Number of Hydrants per floor	02nos.	02nos.	MR			
	hose Box	02nos.	02nos.	MR			
12	Yard Hydrants.	021103.	021105.	IVIR			
	total number of hydrants	02nos.	02nos.	MR			
	hose box	02nos.	02nos.	MR			
13	Pumping arrangements	021103.	021105.	IVIC			
	1. Ground level	N/A	N/A	N/A			
	a. Discharge of main Pump	N/A	N/A	N/A			
	b.Head of main pump	N/A	N/A				
	c.Number of main pumps	N/A	N/A	N/A			
	d.jockey pump out put	N/A		N/A			
	e.jockey pump head	N/A	N/A	N/A			
	f. Standby Pump output	N/A	N/A	N/A			
	g.Stanby Pump head		N/A	N/A			
		N/A N/A	N/A	N/A			
	h.Auto Starting/Manual stopping		N/A	N/A			
	pump house access 2.Terrace level	N/A	N/A	N/A			
	a. Discharge of pump	900LPM	90O+180LPM	IMP			
				MR			
	b. head of the pump	40m	40m(each)	MR			
	c. Power supply	Required	Provided	MR			
	d. Auto starting of pump	Required	Provided	MR			
	Captive water storage for fire						
14	fighting						
	1. Underground tank capacity	250000Liters	250000Liters common for	MR			
			entire complex				
	a. Draw-off connection	Required	Provided	MR			
	b. fire service inlet	Required	Provided	MR			
	c.Access to tank	Required	Provided	MR			
	Over head tank Capacity	25000Litrs	25000Liters	MR			
15	Exit Signage.	Required	Provided	MR			
16	Provision of lifts.						
	a. Pressurization of lift shaft	N/A	N/A	N/A			
	b. pressurization of lift lobby	N/A	N/A	N/A			
	c. communication in lift car	Required	Provided	MR			
	d. Fireman's grounding switch	Required	Provided	MR			
	e. Lift signage	Required	Provided	MR			
17	Standby power supply	Required	Provided	MR			
18	Refuge Area.		Not Required				
	total area	N/A	N/A	N/A			
	location	N/A	N/A	N/A			
19	Fire control room						
	a. detector system Panel	N/A	N/A	N/A			
	b. Flow switch Panel	N/A	N/A	N/A			
	c. PA system Panel	Required	Provided	MR			

1/12

	A STATE OF THE PARTY OF THE PAR	COLUMN TWO IS NOT THE OWNER.	the second section of the second section is a second section of the second section of the second section is a second section of the section of the second section of the section of the second section of the second section of the sect							
20	Chasial	Cilvo.	Duntantian		£	protection of			1.6	
U	Special	rire	Protection	systems	TOP	protection of	Shecia	ricke	it anv. N	I/A
and the second second	The second secon	The same of the same of		9,0001110		Proceduction of	Special	HISKS.	II aliv. I	W/M

The fire protection systems provided in the building were test checked at random and found functional at the time of inspection. In view of the deemed compliance of the minimum standards on fire prevention and fire safety required under the rules the FSC issued vide letter No.F.6/DFS/MS/2012/2458, dated 10.07.2012 renewal under rule 37 of the Delhi Fire Service Rule 2010 is recommended.

Accordingly DFA is put up for your approval and signature please.

Signature of the inspecting officer

Name: Vedpal

Designation: ADO

D.O. (S.D)

Dielash

Uptir

Dy ord 52)



Chocops

start 4/7

m.scell

F7 ho

W