GOVERNMENT OF NATIONAL CAPITAL TERRITORY OF DELHI HEAD QUARTERS, DELHI FIRE SERVICE, NEW DELHI - 110001

No.F6/DFS/MS/GH/2017/

Dated :- 13/07/(7

FIRE SAFETY CERTIFICATE

Issued -13 1-17-at New Delhi by.

(Vipin Kental) Chief Fire Officer Delhi Fire Service

Copy to:-

- 1. The Addl. Commissioner of Police (Lic), First Floor, P.S. Defence Colony New Delhi.
- 2. The Manager, Krishna Plaza Guest House at Plot No. 1, Block 80 –A, Krishna Plaza, Main Bazar, Pahar ganj, New Delhi.

Condition for the validity of fire safety certificate

- 1. All the fire safety arrangements provided therein shall be maintained in good working conditions at all times.
- 2. Any loss of life or property due to non functional fire safety measures shall be at the responsibility of the management.
- 3. The trained fire fighting staff should be available round the clock.
- 4. Any deviation w.r.t. construction etc. shall be verified by the concerned building sanctioning authority.
- 5. This fire safety certificate may not be treated in any case for regularization of unauthorized construction, if any.
- 6. The owner / occupier shall submit a declaration every year in form 'K' provided in the first schedule of Delhi Fire Service Rules 2010. The form is available on www.dfs.delhigovt.nic.in
- 7. The means of escape shall be kept unobstructed / unlocked for unhindered evacuation in case of an emergency.
- 8. The owner/occupier shall apply for renewal of this Fire Safety Certificate to the Director in form 'J' [sub rule (I) of rule 37] along with a copy of this Certificate, six month prior to its expiry".

| | NII | 0 | | |
|-------|--------------------------------|--------------------|---------------------------------------|------------------|
| | | | | |
| | INSP | ECTION REPO | RT | |
| 1. | Name & address of the building | Krishna Plaza | Guest House locate | d at Plot No. 1 |
| | | Block 80-A, k | Krishna Market, Mai | n Bazar, Pahar |
| | | Ganj, New De | | |
| 2. | Type of occupancy:- | Residential, | Sub Division-A-1 | |
| | | B + Stilt + Gr. + | 03 Upper floors (total27 | Guest rooms) |
| | | Basement (Hall), S | tilt (Parking), Ground flo | oor (Reception + |
| 3 | Type of case:- | Renewal | 3 rd floor (09 guest rooms | s at each floor) |
| | Details of previous FSC:- | | MS/GH/2013/ND2 | 7/1107 datad |
| 7, | Details of previous 13C | | M3/GH/2013/ND2 | 2/112/ dated |
| 5 | Fine sefety directives No | 23/10/13. | | |
| 5. | Fire safety directives No | N/A | | |
| 6. | 1 | 04/07/17 | | |
| | and the map to this office. | - Sh. Manoj k | Kumar Sharma (AD | OO/CC) |
| 1 | Name & designation of officer | | | |
| | ne building side:- | Mr. Bitto (N | Manager) | |
| 9. | Year of construction:- | 2012 | | |
| 10. | Applicant's letter No:- | Nil dated Nil | | |
| | | | | Old Case |
| S.No. | Minimum Standards on fire | Requirement/ | Provided at site | Remarks |
| | Prevention and fire safety | Existing fire | | MR/NMR |
| | II/D 22 | safety | | |

| S.No. | Minimum Standards on fire Prevention and fire safety U/R 33 | Requirement/ Existing fire safety arrangements | Provided at site | Remarks MR/NMR |
|-------|---|---|-------------------------------|-------------------|
| 1. | Access to Building | | | |
| | 1) Road width | N/A | 06 mtr. Approx | MR |
| | 2) Gate width | N/A | Directly accessible from Road | N/A |
| | 3) Width of internal road | N/A | N/A | N/A |
| 2. | Number, Width Type & Arr | angement of E | xits | |
| | A. Number of staircases | | | |
| | 1. Upper floors | 01 Nos. | 02 Nos. | MR |
| | 2. Basements | 01 Nos. | 02 Nos. | MR |
| | B. Width of staircase | | - 12 Ne 1 - 25 V 1 | |
| | 1. Upper floors | 0.80 mtr. | 1.50 &0.80 mtr. | MR |
| | 2. Basements | 1.50 mtr. | 1.50 &1.25 mtr. | N/A |
| | C. Protection of exits | - × | | |
| | 1. Fire check door | N/A | N/A | N/A |
| | 2. Pressurization | N/A | N/A | N/A |
| | D. No. of continuous | 01 | 01 | MR |
| | staircase to terrace | | | |
| | E. Width of corridor | N/A | N/A | N/A |
| | F. Door size | N/A | 206 cms x 80 cms | N/A |
| 3. | Compartmentation | | | |
| | 1) Fire check door | N/A | N/A | N/A |
| | 2) Sealing of electrical shafts | N/A | N/A | N/A |
| | 3) Fire rating of shaft door | N/A | N/A | N/A |
| | 4) Water curtain | N/A | N/A | N/A |
| | 5) Fire Dampers | N/A | N/A | N/A |
| 4. | Smoke Management System | | | |
| | 1) Basements | 30 ACPH | Exhaust fans | MR |
| | 2) Upper floors | 12 a/c per hour | Natural | MR |

| | 1) Total numbers | 18 Nos. | 18 Nos. | MR |
|--------|--|----------------|-----------|--|
| | 2) Types | ABC & CO2 | ABC & CO2 | MR |
| | 3) ISI macking | Required | Provided | MR |
| 6. | First-Aid Hose Recl | | | |
| | 1) Total number of eachfloor | 01 | 01 | MR |
| | 2) Length of hose ree hose | 30 mir. | 30 intr. | MR |
| | 3) Nozzle diameter | 05 mm | 05 mm | MR |
| 7. | Automatic Fire Detection & | Alarming Syste | em | THE STATE OF THE S |
| | 1) Type of detectors | N/A | N/A | N/A |
| | 2) Location of main panel | N/A | N/A | N/A |
| | 3) Location of repeater panel | N/A | N/A | N/A |
| V 7 12 | 4) Alternate source of power | N/A | N/A | N/A |
| | 5) Hooter's Location | N/A | N/A | N/A |
| 8. | MOEFA (E/Light) | Required | Provided | MR |
| 9. | Public Address System | Required | Provided | MR |
| 10. | Automatic Sprinkler System | | | |
| | 1) Basement | Required | Provided | MR. |
| 1 3 | 2) Upper floors | N/A | N/A | N/A |
| - T | 3) Sprinkler above faise | N/A | N/A | N/A |
| | ceiling | | | |
| 11. | Internal Hydrants | | | A NEW YORK |
| | 1) Size of riser/down-comer. | N/A | N/A | N/A |
| | 2) Number of hydrants per | N/A | N/A | N/A ····· |
| | floor | | | |
| | 3) Hose box | N/A | N/A | N/A |
| 12. | Yard Hydrants | | | |
| | 1) Total number of hydrants | N/A | N!/A | N/A |
| 10 | | N/A | N/A | N/A |
| 13. | Pumping Arrangement | | | , |
| | 1) Ground level | N/A | N/A | N/A |
| | a) Discharge of rain | N/A | N/A | NA |
| | pump | | | |
| | b) Head of main pump | N/A | N/A- | N/A |
| | c) Number of main pump | N/A | N/A | NA |
| | d) Jockey pump out put | N/A | N/A | N/A |
| | e) Jockey pump head | N/A | N/A | N/A |
| | f) Stand by purap output | N/A | N/A | N/A |
| | g) Stand by pure head | N/A | N/A | N/A |
| | h) Auto starting Manual | N/A | N/A | N/A |
| | stopping 2) Terrace level ¹¹ | | | <u> </u> |
| | | 150 I DM | AFO I DM | (1) |
| | a) Discharge of pump b) Head of pump | 450 LPM | 450 LPM | MR |
| | | 30 intr. | 30 mtr. | MR. |
| | c) Power supply d) Auto starting of pump | Required | Provided | -MR |
| | d) Auto starting of pump | Required | Provided | MR |
| | 14.00 | | | |
| | | | | La |

| 14. | Captive Water Storage for | Fire Fighting | | |
|-------|---|-----------------------------------|-----------------------------------|-----|
| | Under ground tank capacity | N/A | N/A | N/A |
| | a) Draw-off connection | N/A | N/A | N/A |
| | b) Fire service inlet | N/A | N/A | N/A |
| | c) Access to tank | N/A | N/A | N/A |
| • | d) Over head tank capacity | 5000 ltr. | 5,000 ltr. | MR |
| 15. | Exit Signage. | Required | Provided | MR |
| 16. | Provision of Lifts. | | A STATE OF THE | |
| | a) Pressurization of lift shaft | N/A | N/A | N/A |
| | b) Pressurization of lift lobby | N/A | N/A | N/A |
| | c) Communication in lift car | N/A | N/A | N/A |
| | d) Fireman's switch | N/A | N/A | N/A |
| | e) Lift signage | N/A | N/A | N/A |
| 17. | Stand by Power Supply | Required | Provided | MR |
| 18. | Refuge Area | N/A | N/A | N/A |
| | Total area location | N/A | N/A | N/A |
| 19. | Fire Control Room | N/A | N/A | N/A |
| | a) Detector system panel | N/A | N/A | N/A |
| E. 3. | b) Flow switch panel | N/A | N/A | N/A |
| | c) PA system panel | N/A | N/A | N/A |
| | d) Battery backup | N/A | N/A | N/A |
| | e) Building floor plan | N/A | N/A | N/A |
| 20. | Special Fire Protection Syste Risk, if any: One ABC type fire elect. Panel. | m for Protect extinguisher for | ion of special bund provided near | MR |

The fire protection systems provided in the building were randomly tested, checked and found functional at the time of inspection.

Shortcomings communicated vide letter No. F6/DFS/MS/GH/2017/1576 dated 20/06/2017 have been rectified.

In view of the deemed compliance of the minimum standards of fire prevention and fire safety measures as required under the rules the FSC issued vide letter no. F6/DFS/MS/GH/2013/NDZ/1127 dated 23/10/2013 renewal under rule 35 of the Delhi Fire Service rules 2010, is recommended.

Signature of the Inspecting Officer

Name: - M.K. Sharma

Doleps) A. (F.D.

Exthat's use of basement in premise